



Covora - Flat Top - Standard Grilles

(T50 / T24)



115mm



135mm



175mm




235mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
550	600	183	70	C5506SF	272	104	C5506HF	350	134	C5506DF			
	700	230	88	C5507SF	341	131	C5507HF	438	168	C5507DF	622	238	C5507TF
	800	275	105	C5508SF	409	157	C5508HF	525	201	C5508DF	747	286	C5508TF
	900	321	123	C5509SF	477	183	C5509HF	612	235	C5509DF	871	334	C5509TF
	1000	367	140	C5510SF	546	209	C5510HF	700	268	C5510DF			
	1100	413	158	C5511SF	613	235	C5511HF	788	302	C5511DF	1120	429	C5511TF
	1200	458	176	C5512SF	682	261	C5512HF	875	335	C5512DF	1244	477	C5512TF
	1300	505	193	C5513SF	750	287	C5513HF	962	368	C5513DF	1369	524	C5513TF
	1400	550	211	C5514SF	818	313	C5514HF	1050	402	C5514DF	1493	572	C5514TF
	1500	596	228	C5515SF									
	1600	642	246	C5516SF	954	365	C5516HF	1225	469	C5516DF	1742	667	C5516TF
	1800	733	281	C5518SF	1091	418	C5518HF	1400	536	C5518DF	1991	763	C5518TF
	2000	825	316	C5520SF	1227	470	C5520HF	1574	603	C5520DF	2239	858	C5520TF
	2200	917	351	C5522SF				1750	670	C5522DF	2488	953	C5522TF
	2400	1008	386	C5524SF				1925	737	C5524DF			
	2600	1100	421	C5526SF				2100	804	C5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T24)



Casing Depth

115mm


135mm

175mm

235mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
650	600	241	92	C6506SF	348	133	C6506HF	449	172	C6506DF			
	700	302	116	C6507SF	435	167	C6507HF	561	215	C6507DF	797	305	C6507TF
	800	361	138	C6508SF	522	200	C6508HF	672	257	C6508DF	957	366	C6508TF
	900	422	162	C6509SF	609	233	C6509HF	784	300	C6509DF	1116	427	C6509TF
	1000	482	185	C6510SF	696	267	C6510HF	896	343	C6510DF	1275	488	C6510TF
	1100	542	208	C6511SF	782	300	C6511HF	1008	386	C6511DF	1435	549	C6511TF
	1200	603	231	C6512SF	870	333	C6512HF	1121	429	C6512DF	1594	610	C6512TF
	1300	663	254	C6513SF	957	366	C6513HF	1233	472	C6513DF	1753	672	C6513TF
	1400	723	277	C6514SF	1043	399	C6514HF	1345	515	C6514DF	1913	733	C6514TF
	1500	783	300	C6515SF	1130	433	C6515HF	1457	558	C6515DF			
	1600	844	323	C6516SF	1218	466	C6516HF	1569	601	C6516DF			
	1700	904	346	C6517SF	1305	500	C6517HF	1681	644	C6517DF			
	1800	964	369	C6518SF	1391	533	C6518HF	1792	687	C6518DF	2551	977	C6518TF
	2000	1085	416	C6520SF	1566	600	C6520HF	2017	772	C6520DF	2869	1099	C6520TF
	2200	1205	462	C6522SF	1739	666	C6522HF	2241	858	C6522DF	3188	1221	C6522TF
	2400	1325	508	C6524SF	1913	733	C6524HF	2465	944	C6524DF	3507	1343	C6524TF
	2600	1446	554	C6526SF	2087	799	C6526HF	2690	1030	C6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T24)



Casing Depth

115mm


135mm

175mm

235mm



Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
750	600	295	113	C7506SF	418	160	C7506HF	538	206	C7506DF			
	700	368	141	C7507SF	523	200	C7507HF	674	258	C7507DF	959	367	C7507TF
	800	442	169	C7508SF	627	240	C7508HF	808	310	C7508DF	1150	440	C7508TF
	900	516	198	C7509SF	732	281	C7509HF	943	361	C7509DF	1341	514	C7509TF
	1000	589	226	C7510SF	837	320	C7510HF	1077	412	C7510DF	1533	587	C7510TF
	1100	663	254	C7511SF	942	361	C7511HF	1212	464	C7511DF	1725	661	C7511TF
	1200	737	282	C7512SF	1046	401	C7512HF	1347	516	C7512DF	1916	734	C7512TF
	1300	811	311	C7513SF	1151	441	C7513HF	1481	567	C7513DF	2108	807	C7513TF
	1400	885	339	C7514SF	1255	481	C7514HF	1616	619	C7514DF	2300	881	C7514TF
	1500	958	367	C7515SF	1360	521	C7515HF	1751	670	C7515DF	2491	954	C7515TF
	1600	1032	395	C7516SF	1464	561	C7516HF	1885	722	C7516DF	2682	1027	C7516TF
	1700	1105	423	C7517SF	1569	601	C7517HF	2020	774	C7517DF			
	1800	1179	452	C7518SF	1673	641	C7518HF	2155	825	C7518DF	3445	1319	C7518TF
	2000	1326	508	C7520SF	1882	721	C7520HF	2423	928	C7520DF	3449	1321	C7520TF
	2200	1474	564	C7522SF	2092	801	C7522HF	2693	1031	C7522DF	3832	1468	C7522TF
	2400	1622	621	C7524SF	2301	881	C7524HF	2963	1135	C7524DF	4216	1615	C7524TF
	2600	1768	677	C7526SF	2510	961	C7526HF	3232	1238	C7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T24)



Casing Depth

115mm


135mm

175mm

235mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
850	500				364	139	C8505HF	466	179	C8505DF			
	600	344	132	C8506SF	485	186	C8506HF	622	238	C8506DF	885	339	C8506TF
	700	431	165	C8507SF	606	232	C8507HF	778	298	C8507DF	1105	423	C8507TF
	800	517	198	C8508SF	727	278	C8508HF	933	357	C8508DF	1326	508	C8508TF
	900	603	231	C8509SF	848	325	C8509HF	1088	417	C8509DF	1548	593	C8509TF
	1000	689	264	C8510SF	970	372	C8510HF	1244	477	C8510DF	1768	677	C8510TF
	1100	775	297	C8511SF	1091	418	C8511HF	1399	536	C8511DF	1990	762	C8511TF
	1200	862	330	C8512SF	1212	464	C8512HF	1555	595	C8512DF	2211	847	C8512TF
	1300	948	363	C8513SF	1333	511	C8513HF	1711	655	C8513DF	2431	931	C8513TF
	1400	1034	396	C8514SF	1454	557	C8514HF	1865	714	C8514DF	2653	1016	C8514TF
	1500	1120	429	C8515SF	1576	604	C8515HF	2021	774	C8515DF			
	1600	1206	462	C8516SF	1697	650	C8516HF	2177	834	C8516DF	3095	1186	C8516TF
	1700	1292	495	C8517SF	1818	696	C8517HF	2333	893	C8517DF			
	1800	1379	528	C8518SF	1939	743	C8518HF	2488	953	C8518DF	3537	1355	C8518TF
	2000	1550	594	C8520SF	2182	836	C8520HF	2799	1072	C8520DF	3979	1524	C8520TF
	2200	1723	660	C8522SF	2424	929	C8522HF	3110	1191	C8522DF	4422	1693	C8522TF
	2400	1896	726	C8524SF	2666	1021	C8524HF	3420	1310	C8524DF			
	2600	2067	792	C8526SF	2909	1114	C8526HF	3732	1429	C8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T24)



Casing Depth

115mm


135mm

175mm

235mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
950	600	390	149	C9506SF	548	210	C9506HF	699	268	C9506DF	992	380	C9506TF
	700	488	187	C9507SF	685	262	C9507HF	874	335	C9507DF	1241	475	C9507TF
	800	586	224	C9508SF	821	315	C9508HF	1048	402	C9508DF	1489	570	C9508TF
	900	683	261	C9509SF	959	367	C9509HF	1223	468	C9509DF	1737	665	C9509TF
	1000	781	299	C9510SF	1096	420	C9510HF	1397	535	C9510DF	1985	760	C9510TF
	1100	878	336	C9511SF	1233	472	C9511HF	1573	602	C9511DF	2233	855	C9511TF
	1200	975	374	C9512SF	1370	525	C9512HF	1747	669	C9512DF	2481	950	C9512TF
	1300	1073	411	C9513SF	1507	577	C9513HF	1922	736	C9513DF	2730	1045	C9513TF
	1400	1170	448	C9514SF	1644	630	C9514HF	2097	803	C9514DF	2978	1141	C9514TF
	1500	1268	486	C9515SF	1781	682	C9515HF	2271	870	C9515DF			
	1600	1365	523	C9516SF	1918	735	C9516HF	2446	937	C9516DF	3474	1330	C9516TF
	1700	1463	560	C9517SF				2621	1004	C9517DF			
	1800	1561	598	C9518SF	2191	839	C9518HF	2795	1071	C9518DF	3970	1521	C9518TF
	2000	1756	673	C9520SF	2465	944	C9520HF	3144	1204	C9520DF			
	2200	1951	747	C9522SF				3494	1338	C9522DF			
	2400	2146	822	C9524SF				3844	1472	C9524DF			
	2600	2341	896	C9526SF				4193	1606	C9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T24)



Casing Depth

115mm

135mm

175mm

235mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1150	600	469	180	C1106SF	665	255	C1106HF	834	319	C1106DF	1180	452	C1106TF
	700	587	225	C1107SF	831	318	C1107HF	1043	399	C1107DF	1476	565	C1107TF
	800	704	270	C1108SF	998	382	C1108HF	1251	479	C1108DF	1771	678	C1108TF
	900	821	315	C1109SF	1164	446	C1109HF	1460	559	C1109DF	2066	791	C1109TF
	1000	938	359	C1110SF	1330	509	C1110HF	1668	639	C1110DF	2361	904	C1110TF
	1100	1056	404	C1111SF				1877	719	C1111DF	2656	1017	C1111TF
	1200	1173	449	C1112SF				2085	799	C1112DF	2951	1130	C1112TF
	1300	1290	494	C1113SF									
	1400	1408	539	C1114SF				2503	959	C1114DF			
	1600	1642	629	C1116SF				2919	1118	C1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*