



Covora - Flat Top - Standard Grilles

(T50 / T30)



Casing Depth

115mm


135mm

175mm

235mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
550	600	183	94	C5506SF	272	140	C5506HF	350	179	C5506DF			
	700	230	118	C5507SF	341	175	C5507HF	438	225	C5507DF	622	319	C5507TF
	800	275	141	C5508SF	409	210	C5508HF	525	269	C5508DF	747	383	C5508TF
	900	321	165	C5509SF	477	245	C5509HF	612	314	C5509DF	871	447	C5509TF
	1000	367	188	C5510SF	546	280	C5510HF	700	359	C5510DF			
	1100	413	212	C5511SF	613	315	C5511HF	788	404	C5511DF	1120	574	C5511TF
	1200	458	235	C5512SF	682	350	C5512HF	875	449	C5512DF	1244	638	C5512TF
	1300	505	259	C5513SF	750	385	C5513HF	962	494	C5513DF	1369	702	C5513TF
	1400	550	282	C5514SF	818	420	C5514HF	1050	539	C5514DF	1493	766	C5514TF
	1500	596	306	C5515SF									
	1600	642	329	C5516SF	954	489	C5516HF	1225	628	C5516DF	1742	894	C5516TF
	1800	733	376	C5518SF	1091	560	C5518HF	1400	718	C5518DF	1991	1021	C5518TF
	2000	825	423	C5520SF	1227	630	C5520HF	1574	808	C5520DF	2239	1149	C5520TF
	2200	917	470	C5522SF				1750	898	C5522DF	2488	1277	C5522TF
	2400	1008	517	C5524SF				1925	988	C5524DF			
	2600	1100	564	C5526SF				2100	1077	C5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T30)



115mm



135mm



175mm




235mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
650	600	241	124	C6506SF	348	179	C6506HF	449	230	C6506DF			
	700	302	155	C6507SF	435	223	C6507HF	561	288	C6507DF	797	409	C6507TF
	800	361	185	C6508SF	522	268	C6508HF	672	345	C6508DF	957	491	C6508TF
	900	422	216	C6509SF	609	312	C6509HF	784	402	C6509DF	1116	573	C6509TF
	1000	482	247	C6510SF	696	357	C6510HF	896	460	C6510DF	1275	654	C6510TF
	1100	542	278	C6511SF	782	401	C6511HF	1008	517	C6511DF	1435	736	C6511TF
	1200	603	309	C6512SF	870	446	C6512HF	1121	575	C6512DF	1594	818	C6512TF
	1300	663	340	C6513SF	957	491	C6513HF	1233	632	C6513DF	1753	899	C6513TF
	1400	723	371	C6514SF	1043	535	C6514HF	1345	690	C6514DF	1913	981	C6514TF
	1500	783	402	C6515SF	1130	580	C6515HF	1457	747	C6515DF			
	1600	844	433	C6516SF	1218	625	C6516HF	1569	805	C6516DF			
	1700	904	464	C6517SF	1305	669	C6517HF	1681	862	C6517DF			
	1800	964	494	C6518SF	1391	714	C6518HF	1792	920	C6518DF	2551	1309	C6518TF
	2000	1085	557	C6520SF	1566	803	C6520HF	2017	1035	C6520DF	2869	1472	C6520TF
	2200	1205	618	C6522SF	1739	892	C6522HF	2241	1150	C6522DF	3188	1635	C6522TF
	2400	1325	680	C6524SF	1913	981	C6524HF	2465	1265	C6524DF	3507	1799	C6524TF
	2600	1446	742	C6526SF	2087	1071	C6526HF	2690	1380	C6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Covora - Flat Top - Standard Grilles

(T50 / T30)



115mm



135mm



175mm




235mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
750	600	295	151	C7506SF	418	215	C7506HF	538	276	C7506DF			
	700	368	189	C7507SF	523	268	C7507HF	674	346	C7507DF	959	492	C7507TF
	800	442	227	C7508SF	627	322	C7508HF	808	415	C7508DF	1150	590	C7508TF
	900	516	265	C7509SF	732	376	C7509HF	943	484	C7509DF	1341	688	C7509TF
	1000	589	302	C7510SF	837	429	C7510HF	1077	552	C7510DF	1533	786	C7510TF
	1100	663	340	C7511SF	942	483	C7511HF	1212	622	C7511DF	1725	885	C7511TF
	1200	737	378	C7512SF	1046	536	C7512HF	1347	691	C7512DF	1916	983	C7512TF
	1300	811	416	C7513SF	1151	590	C7513HF	1481	760	C7513DF	2108	1081	C7513TF
	1400	885	454	C7514SF	1255	644	C7514HF	1616	829	C7514DF	2300	1180	C7514TF
	1500	958	491	C7515SF	1360	698	C7515HF	1751	898	C7515DF	2491	1278	C7515TF
	1600	1032	529	C7516SF	1464	751	C7516HF	1885	967	C7516DF	2682	1376	C7516TF
	1700	1105	567	C7517SF	1569	805	C7517HF	2020	1036	C7517DF			
	1800	1179	605	C7518SF	1673	858	C7518HF	2155	1105	C7518DF	3445	1767	C7518TF
	2000	1326	680	C7520SF	1882	966	C7520HF	2423	1243	C7520DF	3449	1769	C7520TF
	2200	1474	756	C7522SF	2092	1073	C7522HF	2693	1382	C7522DF	3832	1966	C7522TF
	2400	1622	832	C7524SF	2301	1180	C7524HF	2963	1520	C7524DF	4216	2163	C7524TF
	2600	1768	907	C7526SF	2510	1288	C7526HF	3232	1658	C7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T30)



115mm



135mm



175mm




235mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
850	500				364	187	C8505HF	466	239	C8505DF			
	600	344	177	C8506SF	485	249	C8506HF	622	319	C8506DF	885	454	C8506TF
	700	431	221	C8507SF	606	311	C8507HF	778	399	C8507DF	1105	567	C8507TF
	800	517	265	C8508SF	727	373	C8508HF	933	478	C8508DF	1326	680	C8508TF
	900	603	310	C8509SF	848	435	C8509HF	1088	558	C8509DF	1548	794	C8509TF
	1000	689	353	C8510SF	970	498	C8510HF	1244	638	C8510DF	1768	907	C8510TF
	1100	775	398	C8511SF	1091	560	C8511HF	1399	718	C8511DF	1990	1021	C8511TF
	1200	862	442	C8512SF	1212	622	C8512HF	1555	798	C8512DF	2211	1134	C8512TF
	1300	948	486	C8513SF	1333	684	C8513HF	1711	878	C8513DF	2431	1247	C8513TF
	1400	1034	531	C8514SF	1454	746	C8514HF	1865	957	C8514DF	2653	1361	C8514TF
	1500	1120	574	C8515SF	1576	809	C8515HF	2021	1037	C8515DF			
	1600	1206	619	C8516SF	1697	871	C8516HF	2177	1117	C8516DF	3095	1588	C8516TF
	1700	1292	663	C8517SF	1818	933	C8517HF	2333	1197	C8517DF			
	1800	1379	707	C8518SF	1939	995	C8518HF	2488	1276	C8518DF	3537	1814	C8518TF
	2000	1550	795	C8520SF	2182	1120	C8520HF	2799	1436	C8520DF	3979	2041	C8520TF
	2200	1723	884	C8522SF	2424	1244	C8522HF	3110	1595	C8522DF	4422	2268	C8522TF
	2400	1896	972	C8524SF	2666	1368	C8524HF	3420	1755	C8524DF			
	2600	2067	1061	C8526SF	2909	1493	C8526HF	3732	1914	C8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T30)



Casing Depth

115mm


135mm

175mm

235mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
950	600	390	200	C9506SF	548	281	C9506HF	699	358	C9506DF	992	509	C9506TF
	700	488	250	C9507SF	685	352	C9507HF	874	448	C9507DF	1241	636	C9507TF
	800	586	300	C9508SF	821	421	C9508HF	1048	538	C9508DF	1489	764	C9508TF
	900	683	350	C9509SF	959	492	C9509HF	1223	627	C9509DF	1737	891	C9509TF
	1000	781	400	C9510SF	1096	562	C9510HF	1397	717	C9510DF	1985	1018	C9510TF
	1100	878	450	C9511SF	1233	632	C9511HF	1573	807	C9511DF	2233	1146	C9511TF
	1200	975	500	C9512SF	1370	703	C9512HF	1747	896	C9512DF	2481	1273	C9512TF
	1300	1073	551	C9513SF	1507	773	C9513HF	1922	986	C9513DF	2730	1400	C9513TF
	1400	1170	600	C9514SF	1644	843	C9514HF	2097	1076	C9514DF	2978	1528	C9514TF
	1500	1268	651	C9515SF	1781	914	C9515HF	2271	1165	C9515DF			
	1600	1365	700	C9516SF	1918	984	C9516HF	2446	1255	C9516DF	3474	1782	C9516TF
	1700	1463	751	C9517SF				2621	1345	C9517DF			
	1800	1561	801	C9518SF	2191	1124	C9518HF	2795	1434	C9518DF	3970	2037	C9518TF
	2000	1756	901	C9520SF	2465	1265	C9520HF	3144	1613	C9520DF			
	2200	1951	1001	C9522SF				3494	1792	C9522DF			
	2400	2146	1101	C9524SF				3844	1972	C9524DF			
	2600	2341	1201	C9526SF				4193	2151	C9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Covora - Flat Top - Standard Grilles

(T50 / T30)



Casing Depth

115mm

135mm

175mm

235mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1150	600	469	241	C1106SF	665	341	C1106HF	834	428	C1106DF	1180	605	C1106TF
	700	587	301	C1107SF	831	426	C1107HF	1043	535	C1107DF	1476	757	C1107TF
	800	704	361	C1108SF	998	512	C1108HF	1251	642	C1108DF	1771	909	C1108TF
	900	821	421	C1109SF	1164	597	C1109HF	1460	749	C1109DF	2066	1060	C1109TF
	1000	938	481	C1110SF	1330	682	C1110HF	1668	856	C1110DF	2361	1211	C1110TF
	1100	1056	541	C1111SF				1877	963	C1111DF	2656	1362	C1111TF
	1200	1173	602	C1112SF				2085	1070	C1112DF	2951	1514	C1112TF
	1300	1290	662	C1113SF									
	1400	1408	722	C1114SF				2503	1284	C1114DF			
	1600	1642	842	C1116SF				2919	1498	C1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*