

DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
550	600	165	50	DEFF5506SF	245	74	DEFF5506HF	314	95	DEFF5506DF			
	700	206	62	DEFF5507SF	306	93	DEFF5507HF	394	119	DEFF5507DF	559	169	DEFF5507TF
	800	247	75	DEFF5508SF	368	111	DEFF5508HF	472	143	DEFF5508DF	671	203	DEFF5508TF
	900	289	87	DEFF5509SF	429	129	DEFF5509HF	550	166	DEFF5509DF	783	237	DEFF5509TF
	1000	330	100	DEFF5510SF	490	148	DEFF5510HF	629	190	DEFF5510DF			
	1100	371	112	DEFF5511SF	551	166	DEFF5511HF	708	214	DEFF5511DF	1006	304	DEFF5511TF
	1200	412	124	DEFF5512SF	613	185	DEFF5512HF	786	237	DEFF5512DF	1118	338	DEFF5512TF
	1300	454	137	DEFF5513SF	674	204	DEFF5513HF	865	261	DEFF5513DF	1230	372	DEFF5513TF
	1400	494	149	DEFF5514SF	735	222	DEFF5514HF	944	285	DEFF5514DF	1342	405	DEFF5514TF
	1500	536	162	DEFF5515SF									
	1600	577	174	DEFF5516SF	858	259	DEFF5516HF	1101	332	DEFF5516DF	1566	473	DEFF5516TF
	1800	659	199	DEFF5518SF	981	296	DEFF5518HF	1258	380	DEFF5518DF	1790	540	DEFF5518TF
	2000	742	224	DEFF5520SF	1103	333	DEFF5520HF	1415	427	DEFF5520DF	2013	608	DEFF5520TF
	2200	824	249	DEFF5522SF				1573	475	DEFF5522DF	2237	676	DEFF5522TF
	2400	906	274	DEFF5524SF				1730	523	DEFF5524DF			
	2600	989	299	DEFF5526SF				1887	570	DEFF5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
650	600	217	65	DEFF6506SF	313	94	DEFF6506HF	403	122	DEFF6506DF			
	700	271	82	DEFF6507SF	391	118	DEFF6507HF	504	152	DEFF6507DF	717	216	DEFF6507TF
	800	325	98	DEFF6508SF	469	142	DEFF6508HF	604	182	DEFF6508DF	860	260	DEFF6508TF
	900	379	115	DEFF6509SF	547	165	DEFF6509HF	705	213	DEFF6509DF	1003	303	DEFF6509TF
	1000	434	131	DEFF6510SF	626	189	DEFF6510HF	806	243	DEFF6510DF	1146	346	DEFF6510TF
	1100	487	147	DEFF6511SF	703	212	DEFF6511HF	906	274	DEFF6511DF	1290	389	DEFF6511TF
	1200	542	164	DEFF6512SF	782	236	DEFF6512HF	1007	304	DEFF6512DF	1433	433	DEFF6512TF
	1300	596	180	DEFF6513SF	860	260	DEFF6513HF	1108	335	DEFF6513DF	1576	476	DEFF6513TF
	1400	650	196	DEFF6514SF	938	283	DEFF6514HF	1209	365	DEFF6514DF	1719	519	DEFF6514TF
	1500	704	213	DEFF6515SF	1016	307	DEFF6515HF	1310	395	DEFF6515DF			
	1600	758	229	DEFF6516SF	1094	331	DEFF6516HF	1410	426	DEFF6516DF			
	1700	813	245	DEFF6517SF	1173	354	DEFF6517HF	1511	456	DEFF6517DF			
	1800	866	262	DEFF6518SF	1250	378	DEFF6518HF	1611	487	DEFF6518DF	2293	692	DEFF6518TF
	2000	975	295	DEFF6520SF	1407	425	DEFF6520HF	1813	547	DEFF6520DF	2579	779	DEFF6520TF
	2200	1083	327	DEFF6522SF	1563	472	DEFF6522HF	2014	608	DEFF6522DF	2866	865	DEFF6522TF
	2400	1191	360	DEFF6524SF	1719	519	DEFF6524HF	2216	669	DEFF6524DF	3152	952	DEFF6524TF
	2600	1300	393	DEFF6526SF	1876	567	DEFF6526HF	2418	730	DEFF6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
750	600	265	80	DEFF7506SF	376	114	DEFF7506HF	484	146	DEFF7506DF			
	700	331	100	DEFF7507SF	470	142	DEFF7507HF	606	183	DEFF7507DF	862	260	DEFF7507TF
	800	398	120	DEFF7508SF	564	170	DEFF7508HF	726	219	DEFF7508DF	1034	312	DEFF7508TF
	900	464	140	DEFF7509SF	658	199	DEFF7509HF	847	256	DEFF7509DF	1206	364	DEFF7509TF
	1000	530	160	DEFF7510SF	752	227	DEFF7510HF	968	292	DEFF7510DF	1378	416	DEFF7510TF
	1100	596	180	DEFF7511SF	846	256	DEFF7511HF	1090	329	DEFF7511DF	1550	468	DEFF7511TF
	1200	662	200	DEFF7512SF	940	284	DEFF7512HF	1210	366	DEFF7512DF	1722	520	DEFF7512TF
	1300	729	220	DEFF7513SF	1034	312	DEFF7513HF	1331	402	DEFF7513DF	1894	572	DEFF7513TF
	1400	795	240	DEFF7514SF	1128	341	DEFF7514HF	1453	439	DEFF7514DF	2067	624	DEFF7514TF
	1500	861	260	DEFF7515SF	1222	369	DEFF7515HF	1574	475	DEFF7515DF	2239	676	DEFF7515TF
	1600	927	280	DEFF7516SF	1316	397	DEFF7516HF	1694	512	DEFF7516DF	2411	728	DEFF7516TF
	1700	994	300	DEFF7517SF	1410	426	DEFF7517HF	1816	548	DEFF7517DF			
	1800	1060	320	DEFF7518SF	1504	454	DEFF7518HF	1937	585	DEFF7518DF			
	2000	1192	360	DEFF7520SF	1692	511	DEFF7520HF	2178	658	DEFF7520DF	3100	936	DEFF7520TF
	2200	1325	400	DEFF7522SF	1880	568	DEFF7522HF	2421	731	DEFF7522DF	3445	1040	DEFF7522TF
	2400	1458	440	DEFF7524SF	2068	625	DEFF7524HF	2663	804	DEFF7524DF	3790	1144	DEFF7524TF
	2600	1590	480	DEFF7526SF	2256	681	DEFF7526HF	2905	877	DEFF7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
850	500				327	99	DEFF8505HF	419	127	DEFF8505DF			
	600	310	93	DEFF8506SF	436	132	DEFF8506HF	559	169	DEFF8506DF	795	240	DEFF8506TF
	700	387	117	DEFF8507SF	545	165	DEFF8507HF	699	211	DEFF8507DF	994	300	DEFF8507TF
	800	465	140	DEFF8508SF	654	197	DEFF8508HF	838	253	DEFF8508DF	1192	360	DEFF8508TF
	900	542	164	DEFF8509SF	762	230	DEFF8509HF	978	295	DEFF8509DF	1391	420	DEFF8509TF
	1000	619	187	DEFF8510SF	872	263	DEFF8510HF	1118	338	DEFF8510DF	1590	480	DEFF8510TF
	1100	697	210	DEFF8511SF	981	296	DEFF8511HF	1258	380	DEFF8511DF	1789	540	DEFF8511TF
	1200	774	234	DEFF8512SF	1090	329	DEFF8512HF	1398	422	DEFF8512DF	1987	600	DEFF8512TF
	1300	852	257	DEFF8513SF	1198	362	DEFF8513HF	1538	464	DEFF8513DF	2186	660	DEFF8513TF
	1400	930	281	DEFF8514SF	1307	395	DEFF8514HF	1677	506	DEFF8514DF	2385	720	DEFF8514TF
	1500	1006	304	DEFF8515SF	1417	428	DEFF8515HF	1817	549	DEFF8515DF			
	1600	1084	327	DEFF8516SF	1526	461	DEFF8516HF	1957	591	DEFF8516DF	2782	840	DEFF8516TF
	1700	1162	351	DEFF8517SF	1634	494	DEFF8517HF	2097	633	DEFF8517DF			
	1800	1239	374	DEFF8518SF	1743	526	DEFF8518HF	2236	675	DEFF8518DF	3179	960	DEFF8518TF
	2000	1394	421	DEFF8520SF	1962	592	DEFF8520HF	2516	760	DEFF8520DF	3577	1080	DEFF8520TF
	2200	1549	468	DEFF8522SF	2179	658	DEFF8522HF	2795	844	DEFF8522DF	3974	1200	DEFF8522TF
	2400	1704	515	DEFF8524SF	2397	724	DEFF8524HF	3074	928	DEFF8524DF			
	2600	1858	561	DEFF8526SF	2615	790	DEFF8526HF	3354	1013	DEFF8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
950	600	350	106	DEFF9506SF	493	149	DEFF9506HF	628	190	DEFF9506DF	892	269	DEFF9506TF
	700	438	132	DEFF9507SF	616	186	DEFF9507HF	786	237	DEFF9507DF	1115	337	DEFF9507TF
	800	526	159	DEFF9508SF	738	223	DEFF9508HF	942	285	DEFF9508DF	1338	404	DEFF9508TF
	900	614	185	DEFF9509SF	862	260	DEFF9509HF	1099	332	DEFF9509DF	1562	472	DEFF9509TF
	1000	702	212	DEFF9510SF	985	297	DEFF9510HF	1256	379	DEFF9510DF	1784	539	DEFF9510TF
	1100	789	238	DEFF9511SF	1108	335	DEFF9511HF	1414	427	DEFF9511DF	2007	606	DEFF9511TF
	1200	877	265	DEFF9512SF	1231	372	DEFF9512HF	1570	474	DEFF9512DF	2230	674	DEFF9512TF
	1300	965	291	DEFF9513SF	1354	409	DEFF9513HF	1727	522	DEFF9513DF	2454	741	DEFF9513TF
	1400	1052	318	DEFF9514SF	1478	446	DEFF9514HF	1885	569	DEFF9514DF	2677	808	DEFF9514TF
	1500	1140	344	DEFF9515SF	1601	483	DEFF9515HF	2042	617	DEFF9515DF			
	1600	1227	371	DEFF9516SF	1724	521	DEFF9516HF	2198	664	DEFF9516DF	3122	943	DEFF9516TF
	1700	1315	397	DEFF9517SF				2356	712	DEFF9517DF			
	1800	1403	424	DEFF9518SF	1970	595	DEFF9518HF	2513	759	DEFF9518DF	3569	1078	DEFF9518TF
	2000	1578	477	DEFF9520SF	2216	669	DEFF9520HF	2826	854	DEFF9520DF			
	2200	1754	530	DEFF9522SF				3141	949	DEFF9522DF			
	2400	1929	582	DEFF9524SF				3455	1043	DEFF9524DF			
	2600	2104	635	DEFF9526SF				3769	1138	DEFF9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1150	600	422	127	DEFF1106SF	598	180	DEFF1106HF	750	226	DEFF1106DF	1061	320	DEFF1106TF
	700	527	159	DEFF1107SF	747	226	DEFF1107HF	938	283	DEFF1107DF	1326	401	DEFF1107TF
	800	633	191	DEFF1108SF	897	271	DEFF1108HF	1125	340	DEFF1108DF	1592	481	DEFF1108TF
	900	738	223	DEFF1109SF	1046	316	DEFF1109HF	1312	396	DEFF1109DF	1857	561	DEFF1109TF
	1000	843	255	DEFF1110SF	1195	361	DEFF1110HF	1499	453	DEFF1110DF	2122	641	DEFF1110TF
	1100	949	287	DEFF1111SF				1687	510	DEFF1111DF	2387	721	DEFF1111TF
	1200	1054	318	DEFF1112SF				1874	566	DEFF1112DF	2653	801	DEFF1112TF
	1300	1160	350	DEFF1113SF									
	1400	1266	382	DEFF1114SF				2250	679	DEFF1114DF			
	1600	1476	446	DEFF1116SF				2624	792	DEFF1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*