

DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
550	600	165	63	DEFF5506SF	245	94	DEFF5506HF	314	120	DEFF5506DF			
	700	206	79	DEFF5507SF	306	117	DEFF5507HF	394	151	DEFF5507DF	559	214	DEFF5507TF
	800	247	95	DEFF5508SF	368	141	DEFF5508HF	472	181	DEFF5508DF	671	257	DEFF5508TF
	900	289	111	DEFF5509SF	429	164	DEFF5509HF	550	211	DEFF5509DF	783	300	DEFF5509TF
	1000	330	126	DEFF5510SF	490	188	DEFF5510HF	629	241	DEFF5510DF			
	1100	371	142	DEFF5511SF	551	211	DEFF5511HF	708	271	DEFF5511DF	1006	385	DEFF5511TF
	1200	412	158	DEFF5512SF	613	235	DEFF5512HF	786	301	DEFF5512DF	1118	428	DEFF5512TF
	1300	454	174	DEFF5513SF	674	258	DEFF5513HF	865	331	DEFF5513DF	1230	471	DEFF5513TF
	1400	494	189	DEFF5514SF	735	282	DEFF5514HF	944	362	DEFF5514DF	1342	514	DEFF5514TF
	1500	536	205	DEFF5515SF									
	1600	577	221	DEFF5516SF	858	328	DEFF5516HF	1101	422	DEFF5516DF	1566	600	DEFF5516TF
	1800	659	252	DEFF5518SF	981	376	DEFF5518HF	1258	482	DEFF5518DF	1790	685	DEFF5518TF
	2000	742	284	DEFF5520SF	1103	423	DEFF5520HF	1415	542	DEFF5520DF	2013	771	DEFF5520TF
	2200	824	316	DEFF5522SF				1573	602	DEFF5522DF	2237	857	DEFF5522TF
	2400	906	347	DEFF5524SF				1730	663	DEFF5524DF			
	2600	989	379	DEFF5526SF				1887	723	DEFF5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
650	600	217	83	DEFF6506SF	313	120	DEFF6506HF	403	154	DEFF6506DF			
	700	271	104	DEFF6507SF	391	150	DEFF6507HF	504	193	DEFF6507DF	717	275	DEFF6507TF
	800	325	124	DEFF6508SF	469	180	DEFF6508HF	604	231	DEFF6508DF	860	329	DEFF6508TF
	900	379	145	DEFF6509SF	547	210	DEFF6509HF	705	270	DEFF6509DF	1003	384	DEFF6509TF
	1000	434	166	DEFF6510SF	626	240	DEFF6510HF	806	309	DEFF6510DF	1146	439	DEFF6510TF
	1100	487	187	DEFF6511SF	703	269	DEFF6511HF	906	347	DEFF6511DF	1290	494	DEFF6511TF
	1200	542	207	DEFF6512SF	782	299	DEFF6512HF	1007	386	DEFF6512DF	1433	549	DEFF6512TF
	1300	596	228	DEFF6513SF	860	329	DEFF6513HF	1108	424	DEFF6513DF	1576	604	DEFF6513TF
	1400	650	249	DEFF6514SF	938	359	DEFF6514HF	1209	463	DEFF6514DF	1719	658	DEFF6514TF
	1500	704	270	DEFF6515SF	1016	389	DEFF6515HF	1310	502	DEFF6515DF			
	1600	758	290	DEFF6516SF	1094	419	DEFF6516HF	1410	540	DEFF6516DF			
	1700	813	311	DEFF6517SF	1173	449	DEFF6517HF	1511	579	DEFF6517DF			
	1800	866	332	DEFF6518SF	1250	479	DEFF6518HF	1611	617	DEFF6518DF	2293	878	DEFF6518TF
	2000	975	374	DEFF6520SF	1407	539	DEFF6520HF	1813	694	DEFF6520DF	2579	988	DEFF6520TF
	2200	1083	415	DEFF6522SF	1563	599	DEFF6522HF	2014	772	DEFF6522DF	2866	1098	DEFF6522TF
	2400	1191	456	DEFF6524SF	1719	658	DEFF6524HF	2216	849	DEFF6524DF	3152	1207	DEFF6524TF
	2600	1300	498	DEFF6526SF	1876	719	DEFF6526HF	2418	926	DEFF6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
750	600	265	101	DEFF7506SF	376	144	DEFF7506HF	484	185	DEFF7506DF			
	700	331	127	DEFF7507SF	470	180	DEFF7507HF	606	232	DEFF7507DF	862	330	DEFF7507TF
	800	398	152	DEFF7508SF	564	216	DEFF7508HF	726	278	DEFF7508DF	1034	396	DEFF7508TF
	900	464	178	DEFF7509SF	658	252	DEFF7509HF	847	324	DEFF7509DF	1206	462	DEFF7509TF
	1000	530	203	DEFF7510SF	752	288	DEFF7510HF	968	371	DEFF7510DF	1378	528	DEFF7510TF
	1100	596	228	DEFF7511SF	846	324	DEFF7511HF	1090	417	DEFF7511DF	1550	594	DEFF7511TF
	1200	662	254	DEFF7512SF	940	360	DEFF7512HF	1210	464	DEFF7512DF	1722	660	DEFF7512TF
	1300	729	279	DEFF7513SF	1034	396	DEFF7513HF	1331	510	DEFF7513DF	1894	726	DEFF7513TF
	1400	795	305	DEFF7514SF	1128	432	DEFF7514HF	1453	556	DEFF7514DF	2067	792	DEFF7514TF
	1500	861	330	DEFF7515SF	1222	468	DEFF7515HF	1574	603	DEFF7515DF	2239	858	DEFF7515TF
	1600	927	355	DEFF7516SF	1316	504	DEFF7516HF	1694	649	DEFF7516DF	2411	923	DEFF7516TF
	1700	994	381	DEFF7517SF	1410	540	DEFF7517HF	1816	696	DEFF7517DF			
	1800	1060	406	DEFF7518SF	1504	576	DEFF7518HF	1937	742	DEFF7518DF			
	2000	1192	457	DEFF7520SF	1692	648	DEFF7520HF	2178	834	DEFF7520DF	3100	1187	DEFF7520TF
	2200	1325	507	DEFF7522SF	1880	720	DEFF7522HF	2421	927	DEFF7522DF	3445	1319	DEFF7522TF
	2400	1458	558	DEFF7524SF	2068	792	DEFF7524HF	2663	1020	DEFF7524DF	3790	1451	DEFF7524TF
	2600	1590	609	DEFF7526SF	2256	864	DEFF7526HF	2905	1113	DEFF7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
850	500				327	125	DEFF8505HF	419	161	DEFF8505DF			
	600	310	119	DEFF8506SF	436	167	DEFF8506HF	559	214	DEFF8506DF	795	305	DEFF8506TF
	700	387	148	DEFF8507SF	545	209	DEFF8507HF	699	268	DEFF8507DF	994	381	DEFF8507TF
	800	465	178	DEFF8508SF	654	250	DEFF8508HF	838	321	DEFF8508DF	1192	457	DEFF8508TF
	900	542	208	DEFF8509SF	762	292	DEFF8509HF	978	375	DEFF8509DF	1391	533	DEFF8509TF
	1000	619	237	DEFF8510SF	872	334	DEFF8510HF	1118	428	DEFF8510DF	1590	609	DEFF8510TF
	1100	697	267	DEFF8511SF	981	376	DEFF8511HF	1258	482	DEFF8511DF	1789	685	DEFF8511TF
	1200	774	297	DEFF8512SF	1090	417	DEFF8512HF	1398	535	DEFF8512DF	1987	761	DEFF8512TF
	1300	852	326	DEFF8513SF	1198	459	DEFF8513HF	1538	589	DEFF8513DF	2186	837	DEFF8513TF
	1400	930	356	DEFF8514SF	1307	501	DEFF8514HF	1677	642	DEFF8514DF	2385	913	DEFF8514TF
	1500	1006	385	DEFF8515SF	1417	543	DEFF8515HF	1817	696	DEFF8515DF			
	1600	1084	415	DEFF8516SF	1526	584	DEFF8516HF	1957	749	DEFF8516DF	2782	1066	DEFF8516TF
	1700	1162	445	DEFF8517SF	1634	626	DEFF8517HF	2097	803	DEFF8517DF			
	1800	1239	475	DEFF8518SF	1743	668	DEFF8518HF	2236	856	DEFF8518DF	3179	1218	DEFF8518TF
	2000	1394	534	DEFF8520SF	1962	751	DEFF8520HF	2516	964	DEFF8520DF	3577	1370	DEFF8520TF
	2200	1549	593	DEFF8522SF	2179	835	DEFF8522HF	2795	1071	DEFF8522DF	3974	1522	DEFF8522TF
	2400	1704	653	DEFF8524SF	2397	918	DEFF8524HF	3074	1177	DEFF8524DF			
	2600	1858	712	DEFF8526SF	2615	1002	DEFF8526HF	3354	1285	DEFF8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
950	600	350	134	DEFF9506SF	493	189	DEFF9506HF	628	241	DEFF9506DF	892	342	DEFF9506TF
	700	438	168	DEFF9507SF	616	236	DEFF9507HF	786	301	DEFF9507DF	1115	427	DEFF9507TF
	800	526	202	DEFF9508SF	738	283	DEFF9508HF	942	361	DEFF9508DF	1338	513	DEFF9508TF
	900	614	235	DEFF9509SF	862	330	DEFF9509HF	1099	421	DEFF9509DF	1562	598	DEFF9509TF
	1000	702	269	DEFF9510SF	985	377	DEFF9510HF	1256	481	DEFF9510DF	1784	683	DEFF9510TF
	1100	789	302	DEFF9511SF	1108	424	DEFF9511HF	1414	541	DEFF9511DF	2007	769	DEFF9511TF
	1200	877	336	DEFF9512SF	1231	472	DEFF9512HF	1570	601	DEFF9512DF	2230	854	DEFF9512TF
	1300	965	370	DEFF9513SF	1354	519	DEFF9513HF	1727	662	DEFF9513DF	2454	940	DEFF9513TF
	1400	1052	403	DEFF9514SF	1478	566	DEFF9514HF	1885	722	DEFF9514DF	2677	1025	DEFF9514TF
	1500	1140	437	DEFF9515SF	1601	613	DEFF9515HF	2042	782	DEFF9515DF			
	1600	1227	470	DEFF9516SF	1724	660	DEFF9516HF	2198	842	DEFF9516DF	3122	1196	DEFF9516TF
	1700	1315	504	DEFF9517SF				2356	902	DEFF9517DF			
	1800	1403	537	DEFF9518SF	1970	754	DEFF9518HF	2513	962	DEFF9518DF	3569	1367	DEFF9518TF
	2000	1578	605	DEFF9520SF	2216	849	DEFF9520HF	2826	1083	DEFF9520DF			
	2200	1754	672	DEFF9522SF				3141	1203	DEFF9522DF			
	2400	1929	739	DEFF9524SF				3455	1323	DEFF9524DF			
	2600	2104	806	DEFF9526SF				3769	1443	DEFF9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1150	600	422	161	DEFF1106SF	598	229	DEFF1106HF	750	287	DEFF1106DF	1061	406	DEFF1106TF
	700	527	202	DEFF1107SF	747	286	DEFF1107HF	938	359	DEFF1107DF	1326	508	DEFF1107TF
	800	633	242	DEFF1108SF	897	343	DEFF1108HF	1125	431	DEFF1108DF	1592	610	DEFF1108TF
	900	738	283	DEFF1109SF	1046	401	DEFF1109HF	1312	502	DEFF1109DF	1857	711	DEFF1109TF
	1000	843	323	DEFF1110SF	1195	458	DEFF1110HF	1499	574	DEFF1110DF	2122	813	DEFF1110TF
	1100	949	363	DEFF1111SF				1687	646	DEFF1111DF	2387	914	DEFF1111TF
	1200	1054	404	DEFF1112SF				1874	718	DEFF1112DF	2653	1016	DEFF1112TF
	1300	1160	444	DEFF1113SF									
	1400	1266	485	DEFF1114SF				2250	862	DEFF1114DF			
	1600	1476	565	DEFF1116SF				2624	1005	DEFF1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*