



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T30)



150mm



165mm



200mm




260mm

Casing Depth



Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
550	600	165	85	DEFF5506SF	245	126	DEFF5506HF	314	161	DEFF5506DF			
	700	206	106	DEFF5507SF	306	157	DEFF5507HF	394	202	DEFF5507DF	559	287	DEFF5507TF
	800	247	127	DEFF5508SF	368	189	DEFF5508HF	472	242	DEFF5508DF	671	344	DEFF5508TF
	900	289	148	DEFF5509SF	429	220	DEFF5509HF	550	282	DEFF5509DF	783	402	DEFF5509TF
	1000	330	169	DEFF5510SF	490	252	DEFF5510HF	629	323	DEFF5510DF			
	1100	371	190	DEFF5511SF	551	283	DEFF5511HF	708	363	DEFF5511DF	1006	516	DEFF5511TF
	1200	412	211	DEFF5512SF	613	314	DEFF5512HF	786	403	DEFF5512DF	1118	574	DEFF5512TF
	1300	454	233	DEFF5513SF	674	346	DEFF5513HF	865	444	DEFF5513DF	1230	631	DEFF5513TF
	1400	494	254	DEFF5514SF	735	377	DEFF5514HF	944	484	DEFF5514DF	1342	689	DEFF5514TF
	1500	536	275	DEFF5515SF									
	1600	577	296	DEFF5516SF	858	440	DEFF5516HF	1101	565	DEFF5516DF	1566	803	DEFF5516TF
	1800	659	338	DEFF5518SF	981	503	DEFF5518HF	1258	646	DEFF5518DF	1790	918	DEFF5518TF
	2000	742	380	DEFF5520SF	1103	566	DEFF5520HF	1415	726	DEFF5520DF	2013	1033	DEFF5520TF
	2200	824	423	DEFF5522SF				1573	807	DEFF5522DF	2237	1147	DEFF5522TF
	2400	906	465	DEFF5524SF				1730	888	DEFF5524DF			
	2600	989	507	DEFF5526SF				1887	968	DEFF5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
650	600	217	111	DEFF6506SF	313	160	DEFF6506HF	403	207	DEFF6506DF			
	700	271	139	DEFF6507SF	391	201	DEFF6507HF	504	259	DEFF6507DF	717	368	DEFF6507TF
	800	325	167	DEFF6508SF	469	240	DEFF6508HF	604	310	DEFF6508DF	860	441	DEFF6508TF
	900	379	195	DEFF6509SF	547	281	DEFF6509HF	705	362	DEFF6509DF	1003	515	DEFF6509TF
	1000	434	222	DEFF6510SF	626	321	DEFF6510HF	806	413	DEFF6510DF	1146	588	DEFF6510TF
	1100	487	250	DEFF6511SF	703	361	DEFF6511HF	906	465	DEFF6511DF	1290	662	DEFF6511TF
	1200	542	278	DEFF6512SF	782	401	DEFF6512HF	1007	517	DEFF6512DF	1433	735	DEFF6512TF
	1300	596	306	DEFF6513SF	860	441	DEFF6513HF	1108	568	DEFF6513DF	1576	808	DEFF6513TF
	1400	650	333	DEFF6514SF	938	481	DEFF6514HF	1209	620	DEFF6514DF	1719	882	DEFF6514TF
	1500	704	361	DEFF6515SF	1016	521	DEFF6515HF	1310	672	DEFF6515DF			
	1600	758	389	DEFF6516SF	1094	561	DEFF6516HF	1410	724	DEFF6516DF			
	1700	813	417	DEFF6517SF	1173	602	DEFF6517HF	1511	775	DEFF6517DF			
	1800	866	444	DEFF6518SF	1250	641	DEFF6518HF	1611	827	DEFF6518DF	2293	1176	DEFF6518TF
	2000	975	500	DEFF6520SF	1407	722	DEFF6520HF	1813	930	DEFF6520DF	2579	1323	DEFF6520TF
	2200	1083	556	DEFF6522SF	1563	802	DEFF6522HF	2014	1033	DEFF6522DF	2866	1470	DEFF6522TF
	2400	1191	611	DEFF6524SF	1719	882	DEFF6524HF	2216	1137	DEFF6524DF	3152	1617	DEFF6524TF
	2600	1300	667	DEFF6526SF	1876	962	DEFF6526HF	2418	1240	DEFF6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T30)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
750	600	265	136	DEFF7506SF	376	193	DEFF7506HF	484	248	DEFF7506DF			
	700	331	170	DEFF7507SF	470	241	DEFF7507HF	606	311	DEFF7507DF	862	442	DEFF7507TF
	800	398	204	DEFF7508SF	564	289	DEFF7508HF	726	373	DEFF7508DF	1034	530	DEFF7508TF
	900	464	238	DEFF7509SF	658	338	DEFF7509HF	847	435	DEFF7509DF	1206	618	DEFF7509TF
	1000	530	272	DEFF7510SF	752	386	DEFF7510HF	968	497	DEFF7510DF	1378	707	DEFF7510TF
	1100	596	306	DEFF7511SF	846	434	DEFF7511HF	1090	559	DEFF7511DF	1550	795	DEFF7511TF
	1200	662	340	DEFF7512SF	940	482	DEFF7512HF	1210	621	DEFF7512DF	1722	884	DEFF7512TF
	1300	729	374	DEFF7513SF	1034	531	DEFF7513HF	1331	683	DEFF7513DF	1894	972	DEFF7513TF
	1400	795	408	DEFF7514SF	1128	579	DEFF7514HF	1453	745	DEFF7514DF	2067	1060	DEFF7514TF
	1500	861	442	DEFF7515SF	1222	627	DEFF7515HF	1574	807	DEFF7515DF	2239	1149	DEFF7515TF
	1600	927	476	DEFF7516SF	1316	675	DEFF7516HF	1694	869	DEFF7516DF	2411	1237	DEFF7516TF
	1700	994	510	DEFF7517SF	1410	724	DEFF7517HF	1816	932	DEFF7517DF			
	1800	1060	544	DEFF7518SF	1504	772	DEFF7518HF	1937	994	DEFF7518DF			
	2000	1192	611	DEFF7520SF	1692	868	DEFF7520HF	2178	1118	DEFF7520DF	3100	1590	DEFF7520TF
	2200	1325	680	DEFF7522SF	1880	964	DEFF7522HF	2421	1242	DEFF7522DF	3445	1767	DEFF7522TF
	2400	1458	748	DEFF7524SF	2068	1061	DEFF7524HF	2663	1366	DEFF7524DF	3790	1944	DEFF7524TF
	2600	1590	815	DEFF7526SF	2256	1157	DEFF7526HF	2905	1490	DEFF7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
850	500				327	168	DEFF8505HF	419	215	DEFF8505DF			
	600	310	159	DEFF8506SF	436	224	DEFF8506HF	559	287	DEFF8506DF	795	408	DEFF8506TF
	700	387	199	DEFF8507SF	545	279	DEFF8507HF	699	359	DEFF8507DF	994	510	DEFF8507TF
	800	465	238	DEFF8508SF	654	335	DEFF8508HF	838	430	DEFF8508DF	1192	611	DEFF8508TF
	900	542	278	DEFF8509SF	762	391	DEFF8509HF	978	502	DEFF8509DF	1391	714	DEFF8509TF
	1000	619	318	DEFF8510SF	872	447	DEFF8510HF	1118	574	DEFF8510DF	1590	815	DEFF8510TF
	1100	697	357	DEFF8511SF	981	503	DEFF8511HF	1258	645	DEFF8511DF	1789	918	DEFF8511TF
	1200	774	397	DEFF8512SF	1090	559	DEFF8512HF	1398	717	DEFF8512DF	1987	1019	DEFF8512TF
	1300	852	437	DEFF8513SF	1198	615	DEFF8513HF	1538	789	DEFF8513DF	2186	1121	DEFF8513TF
	1400	930	477	DEFF8514SF	1307	671	DEFF8514HF	1677	860	DEFF8514DF	2385	1223	DEFF8514TF
	1500	1006	516	DEFF8515SF	1417	727	DEFF8515HF	1817	932	DEFF8515DF			
	1600	1084	556	DEFF8516SF	1526	783	DEFF8516HF	1957	1004	DEFF8516DF	2782	1427	DEFF8516TF
	1700	1162	596	DEFF8517SF	1634	838	DEFF8517HF	2097	1076	DEFF8517DF			
	1800	1239	636	DEFF8518SF	1743	894	DEFF8518HF	2236	1147	DEFF8518DF	3179	1631	DEFF8518TF
	2000	1394	715	DEFF8520SF	1962	1006	DEFF8520HF	2516	1291	DEFF8520DF	3577	1835	DEFF8520TF
	2200	1549	795	DEFF8522SF	2179	1118	DEFF8522HF	2795	1434	DEFF8522DF	3974	2039	DEFF8522TF
	2400	1704	874	DEFF8524SF	2397	1230	DEFF8524HF	3074	1577	DEFF8524DF			
	2600	1858	953	DEFF8526SF	2615	1342	DEFF8526HF	3354	1721	DEFF8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T30)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
950	600	350	180	DEFF9506SF	493	253	DEFF9506HF	628	322	DEFF9506DF	892	458	DEFF9506TF
	700	438	225	DEFF9507SF	616	316	DEFF9507HF	786	403	DEFF9507DF	1115	572	DEFF9507TF
	800	526	270	DEFF9508SF	738	379	DEFF9508HF	942	483	DEFF9508DF	1338	687	DEFF9508TF
	900	614	315	DEFF9509SF	862	442	DEFF9509HF	1099	564	DEFF9509DF	1562	801	DEFF9509TF
	1000	702	360	DEFF9510SF	985	505	DEFF9510HF	1256	644	DEFF9510DF	1784	915	DEFF9510TF
	1100	789	405	DEFF9511SF	1108	568	DEFF9511HF	1414	725	DEFF9511DF	2007	1030	DEFF9511TF
	1200	877	450	DEFF9512SF	1231	632	DEFF9512HF	1570	806	DEFF9512DF	2230	1144	DEFF9512TF
	1300	965	495	DEFF9513SF	1354	695	DEFF9513HF	1727	886	DEFF9513DF	2454	1259	DEFF9513TF
	1400	1052	540	DEFF9514SF	1478	758	DEFF9514HF	1885	967	DEFF9514DF	2677	1373	DEFF9514TF
	1500	1140	585	DEFF9515SF	1601	821	DEFF9515HF	2042	1047	DEFF9515DF			
	1600	1227	630	DEFF9516SF	1724	884	DEFF9516HF	2198	1128	DEFF9516DF	3122	1602	DEFF9516TF
	1700	1315	675	DEFF9517SF				2356	1209	DEFF9517DF			
	1800	1403	720	DEFF9518SF	1970	1010	DEFF9518HF	2513	1289	DEFF9518DF	3569	1831	DEFF9518TF
	2000	1578	810	DEFF9520SF	2216	1137	DEFF9520HF	2826	1450	DEFF9520DF			
	2200	1754	900	DEFF9522SF				3141	1611	DEFF9522DF			
	2400	1929	989	DEFF9524SF				3455	1773	DEFF9524DF			
	2600	2104	1079	DEFF9526SF				3769	1933	DEFF9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Flat Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1150	600	422	216	DEFF1106SF	598	307	DEFF1106HF	750	385	DEFF1106DF	1061	544	DEFF1106TF
	700	527	270	DEFF1107SF	747	383	DEFF1107HF	938	481	DEFF1107DF	1326	680	DEFF1107TF
	800	633	325	DEFF1108SF	897	460	DEFF1108HF	1125	577	DEFF1108DF	1592	817	DEFF1108TF
	900	738	379	DEFF1109SF	1046	537	DEFF1109HF	1312	673	DEFF1109DF	1857	953	DEFF1109TF
	1000	843	433	DEFF1110SF	1195	613	DEFF1110HF	1499	769	DEFF1110DF	2122	1089	DEFF1110TF
	1100	949	487	DEFF1111SF				1687	866	DEFF1111DF	2387	1225	DEFF1111TF
	1200	1054	541	DEFF1112SF				1874	962	DEFF1112DF	2653	1361	DEFF1112TF
	1300	1160	595	DEFF1113SF									
	1400	1266	649	DEFF1114SF				2250	1154	DEFF1114DF			
	1600	1476	757	DEFF1116SF				2624	1346	DEFF1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*