





DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T20)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
600	600	165	50	DESF6006SF	245	74	DESF6006HF	314	95	DESF6006DF			
	700	206	62	DESF6007SF	306	93	DESF6007HF	394	119	DESF6007DF	559	169	DESF6007TF
	800	247	75	DESF6008SF	368	111	DESF6008HF	472	143	DESF6008DF	671	203	DESF6008TF
	900	289	87	DESF6009SF	429	129	DESF6009HF	550	166	DESF6009DF	783	237	DESF6009TF
	1000	330	100	DESF6010SF	490	148	DESF6010HF	629	190	DESF6010DF			
	1100	371	112	DESF6011SF	551	166	DESF6011HF	708	214	DESF6011DF	1006	304	DESF6011TF
	1200	412	124	DESF6012SF	613	185	DESF6012HF	786	237	DESF6012DF	1118	338	DESF6012TF
	1300	454	137	DESF6013SF	674	204	DESF6013HF	865	261	DESF6013DF	1230	372	DESF6013TF
	1400	494	149	DESF6014SF	735	222	DESF6014HF	944	285	DESF6014DF	1342	405	DESF6014TF
	1500	536	162	DESF6015SF									
	1600	577	174	DESF6016SF	858	259	DESF6016HF	1101	332	DESF6016DF	1566	473	DESF6016TF
	1800	659	199	DESF6018SF	981	296	DESF6018HF	1258	380	DESF6018DF	1790	540	DESF6018TF
	2000	742	224	DESF6020SF	1103	333	DESF6020HF	1415	427	DESF6020DF	2013	608	DESF6020TF
	2200	824	249	DESF6022SF				1573	475	DESF6022DF	2237	676	DESF6022TF
	2400	906	274	DESF6024SF				1730	523	DESF6024DF			
	2600	989	299	DESF6026SF				1887	570	DESF6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T20)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
700	600	217	65	DESF7006SF	313	94	DESF7006HF	403	122	DESF7006DF			
	700	271	82	DESF7007SF	391	118	DESF7007HF	504	152	DESF7007DF	717	216	DESF7007TF
	800	325	98	DESF7008SF	469	142	DESF7008HF	604	182	DESF7008DF	860	260	DESF7008TF
	900	379	115	DESF7009SF	547	165	DESF7009HF	705	213	DESF7009DF	1003	303	DESF7009TF
	1000	434	131	DESF7010SF	626	189	DESF7010HF	806	243	DESF7010DF	1146	346	DESF7010TF
	1100	487	147	DESF7011SF	703	212	DESF7011HF	906	274	DESF7011DF	1290	389	DESF7011TF
	1200	542	164	DESF7012SF	782	236	DESF7012HF	1007	304	DESF7012DF	1433	433	DESF7012TF
	1300	596	180	DESF7013SF	860	260	DESF7013HF	1108	335	DESF7013DF	1576	476	DESF7013TF
	1400	650	196	DESF7014SF	938	283	DESF7014HF	1209	365	DESF7014DF	1719	519	DESF7014TF
	1500	704	213	DESF7015SF	1016	307	DESF7015HF	1310	395	DESF7015DF			
	1600	758	229	DESF7016SF	1094	331	DESF7016HF	1410	426	DESF7016DF			
	1700	813	245	DESF7017SF	1173	354	DESF7017HF	1511	456	DESF7017DF			
	1800	866	262	DESF7018SF	1250	378	DESF7018HF	1611	487	DESF7018DF	2293	692	DESF7018TF
	2000	975	295	DESF7020SF	1407	425	DESF7020HF	1813	547	DESF7020DF	2579	779	DESF7020TF
	2200	1083	327	DESF7022SF	1563	472	DESF7022HF	2014	608	DESF7022DF	2866	865	DESF7022TF
	2400	1191	360	DESF7024SF	1719	519	DESF7024HF	2216	669	DESF7024DF	3152	952	DESF7024TF
	2600	1300	393	DESF7026SF	1876	567	DESF7026HF	2418	730	DESF7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
800	600	265	80	DESF8006SF	376	114	DESF8006HF	484	146	DESF8006DF			
	700	331	100	DESF8007SF	470	142	DESF8007HF	606	183	DESF8007DF	862	260	DESF8007TF
	800	398	120	DESF8008SF	564	170	DESF8008HF	726	219	DESF8008DF	1034	312	DESF8008TF
	900	464	140	DESF8009SF	658	199	DESF8009HF	847	256	DESF8009DF	1206	364	DESF8009TF
	1000	530	160	DESF8010SF	752	227	DESF8010HF	968	292	DESF8010DF	1378	416	DESF8010TF
	1100	596	180	DESF8011SF	846	256	DESF8011HF	1090	329	DESF8011DF	1550	468	DESF8011TF
	1200	662	200	DESF8012SF	940	284	DESF8012HF	1210	366	DESF8012DF	1722	520	DESF8012TF
	1300	729	220	DESF8013SF	1034	312	DESF8013HF	1331	402	DESF8013DF	1894	572	DESF8013TF
	1400	795	240	DESF8014SF	1128	341	DESF8014HF	1453	439	DESF8014DF	2067	624	DESF8014TF
	1500	861	260	DESF8015SF	1222	369	DESF8015HF	1574	475	DESF8015DF	2239	676	DESF8015TF
	1600	927	280	DESF8016SF	1316	397	DESF8016HF	1694	512	DESF8016DF	2411	728	DESF8016TF
	1700	994	300	DESF8017SF	1410	426	DESF8017HF	1816	548	DESF8017DF			
	1800	1060	320	DESF8018SF	1504	454	DESF8018HF	1937	585	DESF8018DF			
	2000	1192	360	DESF8020SF	1692	511	DESF8020HF	2178	658	DESF8020DF	3100	936	DESF8020TF
	2200	1325	400	DESF8022SF	1880	568	DESF8022HF	2421	731	DESF8022DF	3445	1040	DESF8022TF
	2400	1458	440	DESF8024SF	2068	625	DESF8024HF	2663	804	DESF8024DF	3790	1144	DESF8024TF
	2600	1590	480	DESF8026SF	2256	681	DESF8026HF	2905	877	DESF8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
900	500				327	99	DESF9005HF	419	127	DESF9005DF			
	600	310	93	DESF9006SF	436	132	DESF9006HF	559	169	DESF9006DF	795	240	DESF9006TF
	700	387	117	DESF9007SF	545	165	DESF9007HF	699	211	DESF9007DF	994	300	DESF9007TF
	800	465	140	DESF9008SF	654	197	DESF9008HF	838	253	DESF9008DF	1192	360	DESF9008TF
	900	542	164	DESF9009SF	762	230	DESF9009HF	978	295	DESF9009DF	1391	420	DESF9009TF
	1000	619	187	DESF9010SF	872	263	DESF9010HF	1118	338	DESF9010DF	1590	480	DESF9010TF
	1100	697	210	DESF9011SF	981	296	DESF9011HF	1258	380	DESF9011DF	1789	540	DESF9011TF
	1200	774	234	DESF9012SF	1090	329	DESF9012HF	1398	422	DESF9012DF	1987	600	DESF9012TF
	1300	852	257	DESF9013SF	1198	362	DESF9013HF	1538	464	DESF9013DF	2186	660	DESF9013TF
	1400	930	281	DESF9014SF	1307	395	DESF9014HF	1677	506	DESF9014DF	2385	720	DESF9014TF
	1500	1006	304	DESF9015SF	1417	428	DESF9015HF	1817	549	DESF9015DF			
	1600	1084	327	DESF9016SF	1526	461	DESF9016HF	1957	591	DESF9016DF	2782	840	DESF9016TF
	1700	1162	351	DESF9017SF	1634	494	DESF9017HF	2097	633	DESF9017DF			
	1800	1239	374	DESF9018SF	1743	526	DESF9018HF	2236	675	DESF9018DF	3179	960	DESF9018TF
	2000	1394	421	DESF9020SF	1962	592	DESF9020HF	2516	760	DESF9020DF	3577	1080	DESF9020TF
	2200	1549	468	DESF9022SF	2179	658	DESF9022HF	2795	844	DESF9022DF	3974	1200	DESF9022TF
	2400	1704	515	DESF9024SF	2397	724	DESF9024HF	3074	928	DESF9024DF			
	2600	1858	561	DESF9026SF	2615	790	DESF9026HF	3354	1013	DESF9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1000	600	350	106	DESF1006SF	493	149	DESF1006HF	628	190	DESF1006DF	892	269	DESF1006TF
	700	438	132	DESF1007SF	616	186	DESF1007HF	786	237	DESF1007DF	1115	337	DESF1007TF
	800	526	159	DESF1008SF	738	223	DESF1008HF	942	285	DESF1008DF	1338	404	DESF1008TF
	900	614	185	DESF1009SF	862	260	DESF1009HF	1099	332	DESF1009DF	1562	472	DESF1009TF
	1000	702	212	DESF1010SF	985	297	DESF1010HF	1256	379	DESF1010DF	1784	539	DESF1010TF
	1100	789	238	DESF1011SF	1108	335	DESF1011HF	1414	427	DESF1011DF	2007	606	DESF1011TF
	1200	877	265	DESF1012SF	1231	372	DESF1012HF	1570	474	DESF1012DF	2230	674	DESF1012TF
	1300	965	291	DESF1013SF	1354	409	DESF1013HF	1727	522	DESF1013DF	2454	741	DESF1013TF
	1400	1052	318	DESF1014SF	1478	446	DESF1014HF	1885	569	DESF1014DF	2677	808	DESF1014TF
	1500	1140	344	DESF1015SF	1601	483	DESF1015HF	2042	617	DESF1015DF			
	1600	1227	371	DESF1016SF	1724	521	DESF1016HF	2198	664	DESF1016DF	3122	943	DESF1016TF
	1700	1315	397	DESF1017SF				2356	712	DESF1017DF			
	1800	1403	424	DESF1018SF	1970	595	DESF1018HF	2513	759	DESF1018DF	3569	1078	DESF1018TF
	2000	1578	477	DESF1020SF	2216	669	DESF1020HF	2826	854	DESF1020DF			
	2200	1754	530	DESF1022SF				3141	949	DESF1022DF			
	2400	1929	582	DESF1024SF				3455	1043	DESF1024DF			
	2600	2104	635	DESF1026SF				3769	1138	DESF1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1200	600	422	127	DESF1206SF	598	180	DESF1206HF	750	226	DESF1206DF	1061	320	DESF1206TF
	700	527	159	DESF1207SF	747	226	DESF1207HF	938	283	DESF1207DF	1326	401	DESF1207TF
	800	633	191	DESF1208SF	897	271	DESF1208HF	1125	340	DESF1208DF	1592	481	DESF1208TF
	900	738	223	DESF1209SF	1046	316	DESF1209HF	1312	396	DESF1209DF	1857	561	DESF1209TF
	1000	843	255	DESF1210SF	1195	361	DESF1210HF	1499	453	DESF1210DF	2122	641	DESF1210TF
	1100	949	287	DESF1211SF				1687	510	DESF1211DF	2387	721	DESF1211TF
	1200	1054	318	DESF1212SF				1874	566	DESF1212DF	2653	801	DESF1212TF
	1300	1160	350	DESF1213SF									
	1400	1266	382	DESF1214SF				2250	679	DESF1214DF			
	1600	1476	446	DESF1216SF				2624	792	DESF1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*