



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
600	600	165	63	DESF6006SF	245	94	DESF6006HF	314	120	DESF6006DF			
	700	206	79	DESF6007SF	306	117	DESF6007HF	394	151	DESF6007DF	559	214	DESF6007TF
	800	247	95	DESF6008SF	368	141	DESF6008HF	472	181	DESF6008DF	671	257	DESF6008TF
	900	289	111	DESF6009SF	429	164	DESF6009HF	550	211	DESF6009DF	783	300	DESF6009TF
	1000	330	126	DESF6010SF	490	188	DESF6010HF	629	241	DESF6010DF			
	1100	371	142	DESF6011SF	551	211	DESF6011HF	708	271	DESF6011DF	1006	385	DESF6011TF
	1200	412	158	DESF6012SF	613	235	DESF6012HF	786	301	DESF6012DF	1118	428	DESF6012TF
	1300	454	174	DESF6013SF	674	258	DESF6013HF	865	331	DESF6013DF	1230	471	DESF6013TF
	1400	494	189	DESF6014SF	735	282	DESF6014HF	944	362	DESF6014DF	1342	514	DESF6014TF
	1500	536	205	DESF6015SF									
	1600	577	221	DESF6016SF	858	328	DESF6016HF	1101	422	DESF6016DF	1566	600	DESF6016TF
	1800	659	252	DESF6018SF	981	376	DESF6018HF	1258	482	DESF6018DF	1790	685	DESF6018TF
	2000	742	284	DESF6020SF	1103	423	DESF6020HF	1415	542	DESF6020DF	2013	771	DESF6020TF
	2200	824	316	DESF6022SF				1573	602	DESF6022DF	2237	857	DESF6022TF
	2400	906	347	DESF6024SF				1730	663	DESF6024DF			
	2600	989	379	DESF6026SF				1887	723	DESF6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
700	600	217	83	DESF7006SF	313	120	DESF7006HF	403	154	DESF7006DF			
	700	271	104	DESF7007SF	391	150	DESF7007HF	504	193	DESF7007DF	717	275	DESF7007TF
	800	325	124	DESF7008SF	469	180	DESF7008HF	604	231	DESF7008DF	860	329	DESF7008TF
	900	379	145	DESF7009SF	547	210	DESF7009HF	705	270	DESF7009DF	1003	384	DESF7009TF
	1000	434	166	DESF7010SF	626	240	DESF7010HF	806	309	DESF7010DF	1146	439	DESF7010TF
	1100	487	187	DESF7011SF	703	269	DESF7011HF	906	347	DESF7011DF	1290	494	DESF7011TF
	1200	542	207	DESF7012SF	782	299	DESF7012HF	1007	386	DESF7012DF	1433	549	DESF7012TF
	1300	596	228	DESF7013SF	860	329	DESF7013HF	1108	424	DESF7013DF	1576	604	DESF7013TF
	1400	650	249	DESF7014SF	938	359	DESF7014HF	1209	463	DESF7014DF	1719	658	DESF7014TF
	1500	704	270	DESF7015SF	1016	389	DESF7015HF	1310	502	DESF7015DF			
	1600	758	290	DESF7016SF	1094	419	DESF7016HF	1410	540	DESF7016DF			
	1700	813	311	DESF7017SF	1173	449	DESF7017HF	1511	579	DESF7017DF			
	1800	866	332	DESF7018SF	1250	479	DESF7018HF	1611	617	DESF7018DF	2293	878	DESF7018TF
	2000	975	374	DESF7020SF	1407	539	DESF7020HF	1813	694	DESF7020DF	2579	988	DESF7020TF
	2200	1083	415	DESF7022SF	1563	599	DESF7022HF	2014	772	DESF7022DF	2866	1098	DESF7022TF
	2400	1191	456	DESF7024SF	1719	658	DESF7024HF	2216	849	DESF7024DF	3152	1207	DESF7024TF
	2600	1300	498	DESF7026SF	1876	719	DESF7026HF	2418	926	DESF7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
800	600	265	101	DESF8006SF	376	144	DESF8006HF	484	185	DESF8006DF			
	700	331	127	DESF8007SF	470	180	DESF8007HF	606	232	DESF8007DF	862	330	DESF8007TF
	800	398	152	DESF8008SF	564	216	DESF8008HF	726	278	DESF8008DF	1034	396	DESF8008TF
	900	464	178	DESF8009SF	658	252	DESF8009HF	847	324	DESF8009DF	1206	462	DESF8009TF
	1000	530	203	DESF8010SF	752	288	DESF8010HF	968	371	DESF8010DF	1378	528	DESF8010TF
	1100	596	228	DESF8011SF	846	324	DESF8011HF	1090	417	DESF8011DF	1550	594	DESF8011TF
	1200	662	254	DESF8012SF	940	360	DESF8012HF	1210	464	DESF8012DF	1722	660	DESF8012TF
	1300	729	279	DESF8013SF	1034	396	DESF8013HF	1331	510	DESF8013DF	1894	726	DESF8013TF
	1400	795	305	DESF8014SF	1128	432	DESF8014HF	1453	556	DESF8014DF	2067	792	DESF8014TF
	1500	861	330	DESF8015SF	1222	468	DESF8015HF	1574	603	DESF8015DF	2239	858	DESF8015TF
	1600	927	355	DESF8016SF	1316	504	DESF8016HF	1694	649	DESF8016DF	2411	923	DESF8016TF
	1700	994	381	DESF8017SF	1410	540	DESF8017HF	1816	696	DESF8017DF			
	1800	1060	406	DESF8018SF	1504	576	DESF8018HF	1937	742	DESF8018DF			
	2000	1192	457	DESF8020SF	1692	648	DESF8020HF	2178	834	DESF8020DF	3100	1187	DESF8020TF
	2200	1325	507	DESF8022SF	1880	720	DESF8022HF	2421	927	DESF8022DF	3445	1319	DESF8022TF
	2400	1458	558	DESF8024SF	2068	792	DESF8024HF	2663	1020	DESF8024DF	3790	1451	DESF8024TF
	2600	1590	609	DESF8026SF	2256	864	DESF8026HF	2905	1113	DESF8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
900	500				327	125	DESF9005HF	419	161	DESF9005DF			
	600	310	119	DESF9006SF	436	167	DESF9006HF	559	214	DESF9006DF	795	305	DESF9006TF
	700	387	148	DESF9007SF	545	209	DESF9007HF	699	268	DESF9007DF	994	381	DESF9007TF
	800	465	178	DESF9008SF	654	250	DESF9008HF	838	321	DESF9008DF	1192	457	DESF9008TF
	900	542	208	DESF9009SF	762	292	DESF9009HF	978	375	DESF9009DF	1391	533	DESF9009TF
	1000	619	237	DESF9010SF	872	334	DESF9010HF	1118	428	DESF9010DF	1590	609	DESF9010TF
	1100	697	267	DESF9011SF	981	376	DESF9011HF	1258	482	DESF9011DF	1789	685	DESF9011TF
	1200	774	297	DESF9012SF	1090	417	DESF9012HF	1398	535	DESF9012DF	1987	761	DESF9012TF
	1300	852	326	DESF9013SF	1198	459	DESF9013HF	1538	589	DESF9013DF	2186	837	DESF9013TF
	1400	930	356	DESF9014SF	1307	501	DESF9014HF	1677	642	DESF9014DF	2385	913	DESF9014TF
	1500	1006	385	DESF9015SF	1417	543	DESF9015HF	1817	696	DESF9015DF			
	1600	1084	415	DESF9016SF	1526	584	DESF9016HF	1957	749	DESF9016DF	2782	1066	DESF9016TF
	1700	1162	445	DESF9017SF	1634	626	DESF9017HF	2097	803	DESF9017DF			
	1800	1239	475	DESF9018SF	1743	668	DESF9018HF	2236	856	DESF9018DF	3179	1218	DESF9018TF
	2000	1394	534	DESF9020SF	1962	751	DESF9020HF	2516	964	DESF9020DF	3577	1370	DESF9020TF
	2200	1549	593	DESF9022SF	2179	835	DESF9022HF	2795	1071	DESF9022DF	3974	1522	DESF9022TF
	2400	1704	653	DESF9024SF	2397	918	DESF9024HF	3074	1177	DESF9024DF			
	2600	1858	712	DESF9026SF	2615	1002	DESF9026HF	3354	1285	DESF9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1000	600	350	134	DESF1006SF	493	189	DESF1006HF	628	241	DESF1006DF	892	342	DESF1006TF
	700	438	168	DESF1007SF	616	236	DESF1007HF	786	301	DESF1007DF	1115	427	DESF1007TF
	800	526	202	DESF1008SF	738	283	DESF1008HF	942	361	DESF1008DF	1338	513	DESF1008TF
	900	614	235	DESF1009SF	862	330	DESF1009HF	1099	421	DESF1009DF	1562	598	DESF1009TF
	1000	702	269	DESF1010SF	985	377	DESF1010HF	1256	481	DESF1010DF	1784	683	DESF1010TF
	1100	789	302	DESF1011SF	1108	424	DESF1011HF	1414	541	DESF1011DF	2007	769	DESF1011TF
	1200	877	336	DESF1012SF	1231	472	DESF1012HF	1570	601	DESF1012DF	2230	854	DESF1012TF
	1300	965	370	DESF1013SF	1354	519	DESF1013HF	1727	662	DESF1013DF	2454	940	DESF1013TF
	1400	1052	403	DESF1014SF	1478	566	DESF1014HF	1885	722	DESF1014DF	2677	1025	DESF1014TF
	1500	1140	437	DESF1015SF	1601	613	DESF1015HF	2042	782	DESF1015DF			
	1600	1227	470	DESF1016SF	1724	660	DESF1016HF	2198	842	DESF1016DF	3122	1196	DESF1016TF
	1700	1315	504	DESF1017SF				2356	902	DESF1017DF			
	1800	1403	537	DESF1018SF	1970	754	DESF1018HF	2513	962	DESF1018DF	3569	1367	DESF1018TF
	2000	1578	605	DESF1020SF	2216	849	DESF1020HF	2826	1083	DESF1020DF			
	2200	1754	672	DESF1022SF				3141	1203	DESF1022DF			
	2400	1929	739	DESF1024SF				3455	1323	DESF1024DF			
	2600	2104	806	DESF1026SF				3769	1443	DESF1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1200	600	422	161	DESF1206SF	598	229	DESF1206HF	750	287	DESF1206DF	1061	406	DESF1206TF
	700	527	202	DESF1207SF	747	286	DESF1207HF	938	359	DESF1207DF	1326	508	DESF1207TF
	800	633	242	DESF1208SF	897	343	DESF1208HF	1125	431	DESF1208DF	1592	610	DESF1208TF
	900	738	283	DESF1209SF	1046	401	DESF1209HF	1312	502	DESF1209DF	1857	711	DESF1209TF
	1000	843	323	DESF1210SF	1195	458	DESF1210HF	1499	574	DESF1210DF	2122	813	DESF1210TF
	1100	949	363	DESF1211SF				1687	646	DESF1211DF	2387	914	DESF1211TF
	1200	1054	404	DESF1212SF				1874	718	DESF1212DF	2653	1016	DESF1212TF
	1300	1160	444	DESF1213SF									
	1400	1266	485	DESF1214SF				2250	862	DESF1214DF			
	1600	1476	565	DESF1216SF				2624	1005	DESF1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*