





DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T30)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
600	600	165	85	DESF6006SF	245	126	DESF6006HF	314	161	DESF6006DF			
	700	206	106	DESF6007SF	306	157	DESF6007HF	394	202	DESF6007DF	559	287	DESF6007TF
	800	247	127	DESF6008SF	368	189	DESF6008HF	472	242	DESF6008DF	671	344	DESF6008TF
	900	289	148	DESF6009SF	429	220	DESF6009HF	550	282	DESF6009DF	783	402	DESF6009TF
	1000	330	169	DESF6010SF	490	252	DESF6010HF	629	323	DESF6010DF			
	1100	371	190	DESF6011SF	551	283	DESF6011HF	708	363	DESF6011DF	1006	516	DESF6011TF
	1200	412	211	DESF6012SF	613	314	DESF6012HF	786	403	DESF6012DF	1118	574	DESF6012TF
	1300	454	233	DESF6013SF	674	346	DESF6013HF	865	444	DESF6013DF	1230	631	DESF6013TF
	1400	494	254	DESF6014SF	735	377	DESF6014HF	944	484	DESF6014DF	1342	689	DESF6014TF
	1500	536	275	DESF6015SF									
	1600	577	296	DESF6016SF	858	440	DESF6016HF	1101	565	DESF6016DF	1566	803	DESF6016TF
	1800	659	338	DESF6018SF	981	503	DESF6018HF	1258	646	DESF6018DF	1790	918	DESF6018TF
	2000	742	380	DESF6020SF	1103	566	DESF6020HF	1415	726	DESF6020DF	2013	1033	DESF6020TF
	2200	824	423	DESF6022SF				1573	807	DESF6022DF	2237	1147	DESF6022TF
	2400	906	465	DESF6024SF				1730	888	DESF6024DF			
	2600	989	507	DESF6026SF				1887	968	DESF6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
700	600	217	111	DESF7006SF	313	160	DESF7006HF	403	207	DESF7006DF			
	700	271	139	DESF7007SF	391	201	DESF7007HF	504	259	DESF7007DF	717	368	DESF7007TF
	800	325	167	DESF7008SF	469	240	DESF7008HF	604	310	DESF7008DF	860	441	DESF7008TF
	900	379	195	DESF7009SF	547	281	DESF7009HF	705	362	DESF7009DF	1003	515	DESF7009TF
	1000	434	222	DESF7010SF	626	321	DESF7010HF	806	413	DESF7010DF	1146	588	DESF7010TF
	1100	487	250	DESF7011SF	703	361	DESF7011HF	906	465	DESF7011DF	1290	662	DESF7011TF
	1200	542	278	DESF7012SF	782	401	DESF7012HF	1007	517	DESF7012DF	1433	735	DESF7012TF
	1300	596	306	DESF7013SF	860	441	DESF7013HF	1108	568	DESF7013DF	1576	808	DESF7013TF
	1400	650	333	DESF7014SF	938	481	DESF7014HF	1209	620	DESF7014DF	1719	882	DESF7014TF
	1500	704	361	DESF7015SF	1016	521	DESF7015HF	1310	672	DESF7015DF			
	1600	758	389	DESF7016SF	1094	561	DESF7016HF	1410	724	DESF7016DF			
	1700	813	417	DESF7017SF	1173	602	DESF7017HF	1511	775	DESF7017DF			
	1800	866	444	DESF7018SF	1250	641	DESF7018HF	1611	827	DESF7018DF	2293	1176	DESF7018TF
	2000	975	500	DESF7020SF	1407	722	DESF7020HF	1813	930	DESF7020DF	2579	1323	DESF7020TF
	2200	1083	556	DESF7022SF	1563	802	DESF7022HF	2014	1033	DESF7022DF	2866	1470	DESF7022TF
	2400	1191	611	DESF7024SF	1719	882	DESF7024HF	2216	1137	DESF7024DF	3152	1617	DESF7024TF
	2600	1300	667	DESF7026SF	1876	962	DESF7026HF	2418	1240	DESF7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
800	600	265	136	DESF8006SF	376	193	DESF8006HF	484	248	DESF8006DF			
	700	331	170	DESF8007SF	470	241	DESF8007HF	606	311	DESF8007DF	862	442	DESF8007TF
	800	398	204	DESF8008SF	564	289	DESF8008HF	726	373	DESF8008DF	1034	530	DESF8008TF
	900	464	238	DESF8009SF	658	338	DESF8009HF	847	435	DESF8009DF	1206	618	DESF8009TF
	1000	530	272	DESF8010SF	752	386	DESF8010HF	968	497	DESF8010DF	1378	707	DESF8010TF
	1100	596	306	DESF8011SF	846	434	DESF8011HF	1090	559	DESF8011DF	1550	795	DESF8011TF
	1200	662	340	DESF8012SF	940	482	DESF8012HF	1210	621	DESF8012DF	1722	884	DESF8012TF
	1300	729	374	DESF8013SF	1034	531	DESF8013HF	1331	683	DESF8013DF	1894	972	DESF8013TF
	1400	795	408	DESF8014SF	1128	579	DESF8014HF	1453	745	DESF8014DF	2067	1060	DESF8014TF
	1500	861	442	DESF8015SF	1222	627	DESF8015HF	1574	807	DESF8015DF	2239	1149	DESF8015TF
	1600	927	476	DESF8016SF	1316	675	DESF8016HF	1694	869	DESF8016DF	2411	1237	DESF8016TF
	1700	994	510	DESF8017SF	1410	724	DESF8017HF	1816	932	DESF8017DF			
	1800	1060	544	DESF8018SF	1504	772	DESF8018HF	1937	994	DESF8018DF			
	2000	1192	611	DESF8020SF	1692	868	DESF8020HF	2178	1118	DESF8020DF	3100	1590	DESF8020TF
	2200	1325	680	DESF8022SF	1880	964	DESF8022HF	2421	1242	DESF8022DF	3445	1767	DESF8022TF
	2400	1458	748	DESF8024SF	2068	1061	DESF8024HF	2663	1366	DESF8024DF	3790	1944	DESF8024TF
	2600	1590	815	DESF8026SF	2256	1157	DESF8026HF	2905	1490	DESF8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
900	500				327	168	DESF9005HF	419	215	DESF9005DF			
	600	310	159	DESF9006SF	436	224	DESF9006HF	559	287	DESF9006DF	795	408	DESF9006TF
	700	387	199	DESF9007SF	545	279	DESF9007HF	699	359	DESF9007DF	994	510	DESF9007TF
	800	465	238	DESF9008SF	654	335	DESF9008HF	838	430	DESF9008DF	1192	611	DESF9008TF
	900	542	278	DESF9009SF	762	391	DESF9009HF	978	502	DESF9009DF	1391	714	DESF9009TF
	1000	619	318	DESF9010SF	872	447	DESF9010HF	1118	574	DESF9010DF	1590	815	DESF9010TF
	1100	697	357	DESF9011SF	981	503	DESF9011HF	1258	645	DESF9011DF	1789	918	DESF9011TF
	1200	774	397	DESF9012SF	1090	559	DESF9012HF	1398	717	DESF9012DF	1987	1019	DESF9012TF
	1300	852	437	DESF9013SF	1198	615	DESF9013HF	1538	789	DESF9013DF	2186	1121	DESF9013TF
	1400	930	477	DESF9014SF	1307	671	DESF9014HF	1677	860	DESF9014DF	2385	1223	DESF9014TF
	1500	1006	516	DESF9015SF	1417	727	DESF9015HF	1817	932	DESF9015DF			
	1600	1084	556	DESF9016SF	1526	783	DESF9016HF	1957	1004	DESF9016DF	2782	1427	DESF9016TF
	1700	1162	596	DESF9017SF	1634	838	DESF9017HF	2097	1076	DESF9017DF			
	1800	1239	636	DESF9018SF	1743	894	DESF9018HF	2236	1147	DESF9018DF	3179	1631	DESF9018TF
	2000	1394	715	DESF9020SF	1962	1006	DESF9020HF	2516	1291	DESF9020DF	3577	1835	DESF9020TF
	2200	1549	795	DESF9022SF	2179	1118	DESF9022HF	2795	1434	DESF9022DF	3974	2039	DESF9022TF
	2400	1704	874	DESF9024SF	2397	1230	DESF9024HF	3074	1577	DESF9024DF			
	2600	1858	953	DESF9026SF	2615	1342	DESF9026HF	3354	1721	DESF9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1000	600	350	180	DESF1006SF	493	253	DESF1006HF	628	322	DESF1006DF	892	458	DESF1006TF
	700	438	225	DESF1007SF	616	316	DESF1007HF	786	403	DESF1007DF	1115	572	DESF1007TF
	800	526	270	DESF1008SF	738	379	DESF1008HF	942	483	DESF1008DF	1338	687	DESF1008TF
	900	614	315	DESF1009SF	862	442	DESF1009HF	1099	564	DESF1009DF	1562	801	DESF1009TF
	1000	702	360	DESF1010SF	985	505	DESF1010HF	1256	644	DESF1010DF	1784	915	DESF1010TF
	1100	789	405	DESF1011SF	1108	568	DESF1011HF	1414	725	DESF1011DF	2007	1030	DESF1011TF
	1200	877	450	DESF1012SF	1231	632	DESF1012HF	1570	806	DESF1012DF	2230	1144	DESF1012TF
	1300	965	495	DESF1013SF	1354	695	DESF1013HF	1727	886	DESF1013DF	2454	1259	DESF1013TF
	1400	1052	540	DESF1014SF	1478	758	DESF1014HF	1885	967	DESF1014DF	2677	1373	DESF1014TF
	1500	1140	585	DESF1015SF	1601	821	DESF1015HF	2042	1047	DESF1015DF			
	1600	1227	630	DESF1016SF	1724	884	DESF1016HF	2198	1128	DESF1016DF	3122	1602	DESF1016TF
	1700	1315	675	DESF1017SF				2356	1209	DESF1017DF			
	1800	1403	720	DESF1018SF	1970	1010	DESF1018HF	2513	1289	DESF1018DF	3569	1831	DESF1018TF
	2000	1578	810	DESF1020SF	2216	1137	DESF1020HF	2826	1450	DESF1020DF			
	2200	1754	900	DESF1022SF				3141	1611	DESF1022DF			
	2400	1929	989	DESF1024SF				3455	1773	DESF1024DF			
	2600	2104	1079	DESF1026SF				3769	1933	DESF1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Floor Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1200	600	422	216	DESF1206SF	598	307	DESF1206HF	750	385	DESF1206DF	1061	544	DESF1206TF
	700	527	270	DESF1207SF	747	383	DESF1207HF	938	481	DESF1207DF	1326	680	DESF1207TF
	800	633	325	DESF1208SF	897	460	DESF1208HF	1125	577	DESF1208DF	1592	817	DESF1208TF
	900	738	379	DESF1209SF	1046	537	DESF1209HF	1312	673	DESF1209DF	1857	953	DESF1209TF
	1000	843	433	DESF1210SF	1195	613	DESF1210HF	1499	769	DESF1210DF	2122	1089	DESF1210TF
	1100	949	487	DESF1211SF				1687	866	DESF1211DF	2387	1225	DESF1211TF
	1200	1054	541	DESF1212SF				1874	962	DESF1212DF	2653	1361	DESF1212TF
	1300	1160	595	DESF1213SF									
	1400	1266	649	DESF1214SF				2250	1154	DESF1214DF			
	1600	1476	757	DESF1216SF				2624	1346	DESF1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*