


DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
600	600	165	50	DESW6006SF	245	74	DESW6006HF	314	95	DESW6006DF			
	700	206	62	DESW6007SF	306	93	DESW6007HF	394	119	DESW6007DF	559	169	DESW6007TF
	800	247	75	DESW6008SF	368	111	DESW6008HF	472	143	DESW6008DF	671	203	DESW6008TF
	900	289	87	DESW6009SF	429	129	DESW6009HF	550	166	DESW6009DF	783	237	DESW6009TF
	1000	330	100	DESW6010SF	490	148	DESW6010HF	629	190	DESW6010DF			
	1100	371	112	DESW6011SF	551	166	DESW6011HF	708	214	DESW6011DF	1006	304	DESW6011TF
	1200	412	124	DESW6012SF	613	185	DESW6012HF	786	237	DESW6012DF	1118	338	DESW6012TF
	1300	454	137	DESW6013SF	674	204	DESW6013HF	865	261	DESW6013DF	1230	372	DESW6013TF
	1400	494	149	DESW6014SF	735	222	DESW6014HF	944	285	DESW6014DF	1342	405	DESW6014TF
	1500	536	162	DESW6015SF									
	1600	577	174	DESW6016SF	858	259	DESW6016HF	1101	332	DESW6016DF	1566	473	DESW6016TF
	1800	659	199	DESW6018SF	981	296	DESW6018HF	1258	380	DESW6018DF	1790	540	DESW6018TF
	2000	742	224	DESW6020SF	1103	333	DESW6020HF	1415	427	DESW6020DF	2013	608	DESW6020TF
	2200	824	249	DESW6022SF				1573	475	DESW6022DF	2237	676	DESW6022TF
	2400	906	274	DESW6024SF				1730	523	DESW6024DF			
	2600	989	299	DESW6026SF				1887	570	DESW6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
700	600	217	65	DESW7006SF	313	94	DESW7006HF	403	122	DESW7006DF			
	700	271	82	DESW7007SF	391	118	DESW7007HF	504	152	DESW7007DF	717	216	DESW7007TF
	800	325	98	DESW7008SF	469	142	DESW7008HF	604	182	DESW7008DF	860	260	DESW7008TF
	900	379	115	DESW7009SF	547	165	DESW7009HF	705	213	DESW7009DF	1003	303	DESW7009TF
	1000	434	131	DESW7010SF	626	189	DESW7010HF	806	243	DESW7010DF	1146	346	DESW7010TF
	1100	487	147	DESW7011SF	703	212	DESW7011HF	906	274	DESW7011DF	1290	389	DESW7011TF
	1200	542	164	DESW7012SF	782	236	DESW7012HF	1007	304	DESW7012DF	1433	433	DESW7012TF
	1300	596	180	DESW7013SF	860	260	DESW7013HF	1108	335	DESW7013DF	1576	476	DESW7013TF
	1400	650	196	DESW7014SF	938	283	DESW7014HF	1209	365	DESW7014DF	1719	519	DESW7014TF
	1500	704	213	DESW7015SF	1016	307	DESW7015HF	1310	395	DESW7015DF			
	1600	758	229	DESW7016SF	1094	331	DESW7016HF	1410	426	DESW7016DF			
	1700	813	245	DESW7017SF	1173	354	DESW7017HF	1511	456	DESW7017DF			
	1800	866	262	DESW7018SF	1250	378	DESW7018HF	1611	487	DESW7018DF	2293	692	DESW7018TF
	2000	975	295	DESW7020SF	1407	425	DESW7020HF	1813	547	DESW7020DF	2579	779	DESW7020TF
	2200	1083	327	DESW7022SF	1563	472	DESW7022HF	2014	608	DESW7022DF	2866	865	DESW7022TF
	2400	1191	360	DESW7024SF	1719	519	DESW7024HF	2216	669	DESW7024DF	3152	952	DESW7024TF
	2600	1300	393	DESW7026SF	1876	567	DESW7026HF	2418	730	DESW7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T20)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
800	600	265	80	DESW8006SF	376	114	DESW8006HF	484	146	DESW8006DF			
	700	331	100	DESW8007SF	470	142	DESW8007HF	606	183	DESW8007DF	862	260	DESW8007TF
	800	398	120	DESW8008SF	564	170	DESW8008HF	726	219	DESW8008DF	1034	312	DESW8008TF
	900	464	140	DESW8009SF	658	199	DESW8009HF	847	256	DESW8009DF	1206	364	DESW8009TF
	1000	530	160	DESW8010SF	752	227	DESW8010HF	968	292	DESW8010DF	1378	416	DESW8010TF
	1100	596	180	DESW8011SF	846	256	DESW8011HF	1090	329	DESW8011DF	1550	468	DESW8011TF
	1200	662	200	DESW8012SF	940	284	DESW8012HF	1210	366	DESW8012DF	1722	520	DESW8012TF
	1300	729	220	DESW8013SF	1034	312	DESW8013HF	1331	402	DESW8013DF	1894	572	DESW8013TF
	1400	795	240	DESW8014SF	1128	341	DESW8014HF	1453	439	DESW8014DF	2067	624	DESW8014TF
	1500	861	260	DESW8015SF	1222	369	DESW8015HF	1574	475	DESW8015DF	2239	676	DESW8015TF
	1600	927	280	DESW8016SF	1316	397	DESW8016HF	1694	512	DESW8016DF	2411	728	DESW8016TF
	1700	994	300	DESW8017SF	1410	426	DESW8017HF	1816	548	DESW8017DF			
	1800	1060	320	DESW8018SF	1504	454	DESW8018HF	1937	585	DESW8018DF			
	2000	1192	360	DESW8020SF	1692	511	DESW8020HF	2178	658	DESW8020DF	3100	936	DESW8020TF
	2200	1325	400	DESW8022SF	1880	568	DESW8022HF	2421	731	DESW8022DF	3445	1040	DESW8022TF
	2400	1458	440	DESW8024SF	2068	625	DESW8024HF	2663	804	DESW8024DF	3790	1144	DESW8024TF
	2600	1590	480	DESW8026SF	2256	681	DESW8026HF	2905	877	DESW8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
900	500				327	99	DESW9005HF	419	127	DESW9005DF			
	600	310	93	DESW9006SF	436	132	DESW9006HF	559	169	DESW9006DF	795	240	DESW9006TF
	700	387	117	DESW9007SF	545	165	DESW9007HF	699	211	DESW9007DF	994	300	DESW9007TF
	800	465	140	DESW9008SF	654	197	DESW9008HF	838	253	DESW9008DF	1192	360	DESW9008TF
	900	542	164	DESW9009SF	762	230	DESW9009HF	978	295	DESW9009DF	1391	420	DESW9009TF
	1000	619	187	DESW9010SF	872	263	DESW9010HF	1118	338	DESW9010DF	1590	480	DESW9010TF
	1100	697	210	DESW9011SF	981	296	DESW9011HF	1258	380	DESW9011DF	1789	540	DESW9011TF
	1200	774	234	DESW9012SF	1090	329	DESW9012HF	1398	422	DESW9012DF	1987	600	DESW9012TF
	1300	852	257	DESW9013SF	1198	362	DESW9013HF	1538	464	DESW9013DF	2186	660	DESW9013TF
	1400	930	281	DESW9014SF	1307	395	DESW9014HF	1677	506	DESW9014DF	2385	720	DESW9014TF
	1500	1006	304	DESW9015SF	1417	428	DESW9015HF	1817	549	DESW9015DF			
	1600	1084	327	DESW9016SF	1526	461	DESW9016HF	1957	591	DESW9016DF	2782	840	DESW9016TF
	1700	1162	351	DESW9017SF	1634	494	DESW9017HF	2097	633	DESW9017DF			
	1800	1239	374	DESW9018SF	1743	526	DESW9018HF	2236	675	DESW9018DF	3179	960	DESW9018TF
	2000	1394	421	DESW9020SF	1962	592	DESW9020HF	2516	760	DESW9020DF	3577	1080	DESW9020TF
	2200	1549	468	DESW9022SF	2179	658	DESW9022HF	2795	844	DESW9022DF	3974	1200	DESW9022TF
	2400	1704	515	DESW9024SF	2397	724	DESW9024HF	3074	928	DESW9024DF			
	2600	1858	561	DESW9026SF	2615	790	DESW9026HF	3354	1013	DESW9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1000	600	350	106	DESW1006SF	493	149	DESW1006HF	628	190	DESW1006DF	892	269	DESW1006TF
	700	438	132	DESW1007SF	616	186	DESW1007HF	786	237	DESW1007DF	1115	337	DESW1007TF
	800	526	159	DESW1008SF	738	223	DESW1008HF	942	285	DESW1008DF	1338	404	DESW1008TF
	900	614	185	DESW1009SF	862	260	DESW1009HF	1099	332	DESW1009DF	1562	472	DESW1009TF
	1000	702	212	DESW1010SF	985	297	DESW1010HF	1256	379	DESW1010DF	1784	539	DESW1010TF
	1100	789	238	DESW1011SF	1108	335	DESW1011HF	1414	427	DESW1011DF	2007	606	DESW1011TF
	1200	877	265	DESW1012SF	1231	372	DESW1012HF	1570	474	DESW1012DF	2230	674	DESW1012TF
	1300	965	291	DESW1013SF	1354	409	DESW1013HF	1727	522	DESW1013DF	2454	741	DESW1013TF
	1400	1052	318	DESW1014SF	1478	446	DESW1014HF	1885	569	DESW1014DF	2677	808	DESW1014TF
	1500	1140	344	DESW1015SF	1601	483	DESW1015HF	2042	617	DESW1015DF			
	1600	1227	371	DESW1016SF	1724	521	DESW1016HF	2198	664	DESW1016DF	3122	943	DESW1016TF
	1700	1315	397	DESW1017SF				2356	712	DESW1017DF			
	1800	1403	424	DESW1018SF	1970	595	DESW1018HF	2513	759	DESW1018DF	3569	1078	DESW1018TF
	2000	1578	477	DESW1020SF	2216	669	DESW1020HF	2826	854	DESW1020DF			
	2200	1754	530	DESW1022SF				3141	949	DESW1022DF			
	2400	1929	582	DESW1024SF				3455	1043	DESW1024DF			
	2600	2104	635	DESW1026SF				3769	1138	DESW1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1200	600	422	127	DESW1206SF	598	180	DESW1206HF	750	226	DESW1206DF	1061	320	DESW1206TF
	700	527	159	DESW1207SF	747	226	DESW1207HF	938	283	DESW1207DF	1326	401	DESW1207TF
	800	633	191	DESW1208SF	897	271	DESW1208HF	1125	340	DESW1208DF	1592	481	DESW1208TF
	900	738	223	DESW1209SF	1046	316	DESW1209HF	1312	396	DESW1209DF	1857	561	DESW1209TF
	1000	843	255	DESW1210SF	1195	361	DESW1210HF	1499	453	DESW1210DF	2122	641	DESW1210TF
	1100	949	287	DESW1211SF				1687	510	DESW1211DF	2387	721	DESW1211TF
	1200	1054	318	DESW1212SF				1874	566	DESW1212DF	2653	801	DESW1212TF
	1300	1160	350	DESW1213SF									
	1400	1266	382	DESW1214SF				2250	679	DESW1214DF			
	1600	1476	446	DESW1216SF				2624	792	DESW1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*