

DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
600	600	165	63	DESW6006SF	245	94	DESW6006HF	314	120	DESW6006DF			
	700	206	79	DESW6007SF	306	117	DESW6007HF	394	151	DESW6007DF	559	214	DESW6007TF
	800	247	95	DESW6008SF	368	141	DESW6008HF	472	181	DESW6008DF	671	257	DESW6008TF
	900	289	111	DESW6009SF	429	164	DESW6009HF	550	211	DESW6009DF	783	300	DESW6009TF
	1000	330	126	DESW6010SF	490	188	DESW6010HF	629	241	DESW6010DF			
	1100	371	142	DESW6011SF	551	211	DESW6011HF	708	271	DESW6011DF	1006	385	DESW6011TF
	1200	412	158	DESW6012SF	613	235	DESW6012HF	786	301	DESW6012DF	1118	428	DESW6012TF
	1300	454	174	DESW6013SF	674	258	DESW6013HF	865	331	DESW6013DF	1230	471	DESW6013TF
	1400	494	189	DESW6014SF	735	282	DESW6014HF	944	362	DESW6014DF	1342	514	DESW6014TF
	1500	536	205	DESW6015SF									
	1600	577	221	DESW6016SF	858	328	DESW6016HF	1101	422	DESW6016DF	1566	600	DESW6016TF
	1800	659	252	DESW6018SF	981	376	DESW6018HF	1258	482	DESW6018DF	1790	685	DESW6018TF
	2000	742	284	DESW6020SF	1103	423	DESW6020HF	1415	542	DESW6020DF	2013	771	DESW6020TF
	2200	824	316	DESW6022SF				1573	602	DESW6022DF	2237	857	DESW6022TF
	2400	906	347	DESW6024SF				1730	663	DESW6024DF			
	2600	989	379	DESW6026SF				1887	723	DESW6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
700	600	217	83	DESW7006SF	313	120	DESW7006HF	403	154	DESW7006DF			
	700	271	104	DESW7007SF	391	150	DESW7007HF	504	193	DESW7007DF	717	275	DESW7007TF
	800	325	124	DESW7008SF	469	180	DESW7008HF	604	231	DESW7008DF	860	329	DESW7008TF
	900	379	145	DESW7009SF	547	210	DESW7009HF	705	270	DESW7009DF	1003	384	DESW7009TF
	1000	434	166	DESW7010SF	626	240	DESW7010HF	806	309	DESW7010DF	1146	439	DESW7010TF
	1100	487	187	DESW7011SF	703	269	DESW7011HF	906	347	DESW7011DF	1290	494	DESW7011TF
	1200	542	207	DESW7012SF	782	299	DESW7012HF	1007	386	DESW7012DF	1433	549	DESW7012TF
	1300	596	228	DESW7013SF	860	329	DESW7013HF	1108	424	DESW7013DF	1576	604	DESW7013TF
	1400	650	249	DESW7014SF	938	359	DESW7014HF	1209	463	DESW7014DF	1719	658	DESW7014TF
	1500	704	270	DESW7015SF	1016	389	DESW7015HF	1310	502	DESW7015DF			
	1600	758	290	DESW7016SF	1094	419	DESW7016HF	1410	540	DESW7016DF			
	1700	813	311	DESW7017SF	1173	449	DESW7017HF	1511	579	DESW7017DF			
	1800	866	332	DESW7018SF	1250	479	DESW7018HF	1611	617	DESW7018DF	2293	878	DESW7018TF
	2000	975	374	DESW7020SF	1407	539	DESW7020HF	1813	694	DESW7020DF	2579	988	DESW7020TF
	2200	1083	415	DESW7022SF	1563	599	DESW7022HF	2014	772	DESW7022DF	2866	1098	DESW7022TF
	2400	1191	456	DESW7024SF	1719	658	DESW7024HF	2216	849	DESW7024DF	3152	1207	DESW7024TF
	2600	1300	498	DESW7026SF	1876	719	DESW7026HF	2418	926	DESW7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
800	600	265	101	DESW8006SF	376	144	DESW8006HF	484	185	DESW8006DF			
	700	331	127	DESW8007SF	470	180	DESW8007HF	606	232	DESW8007DF	862	330	DESW8007TF
	800	398	152	DESW8008SF	564	216	DESW8008HF	726	278	DESW8008DF	1034	396	DESW8008TF
	900	464	178	DESW8009SF	658	252	DESW8009HF	847	324	DESW8009DF	1206	462	DESW8009TF
	1000	530	203	DESW8010SF	752	288	DESW8010HF	968	371	DESW8010DF	1378	528	DESW8010TF
	1100	596	228	DESW8011SF	846	324	DESW8011HF	1090	417	DESW8011DF	1550	594	DESW8011TF
	1200	662	254	DESW8012SF	940	360	DESW8012HF	1210	464	DESW8012DF	1722	660	DESW8012TF
	1300	729	279	DESW8013SF	1034	396	DESW8013HF	1331	510	DESW8013DF	1894	726	DESW8013TF
	1400	795	305	DESW8014SF	1128	432	DESW8014HF	1453	556	DESW8014DF	2067	792	DESW8014TF
	1500	861	330	DESW8015SF	1222	468	DESW8015HF	1574	603	DESW8015DF	2239	858	DESW8015TF
	1600	927	355	DESW8016SF	1316	504	DESW8016HF	1694	649	DESW8016DF	2411	923	DESW8016TF
	1700	994	381	DESW8017SF	1410	540	DESW8017HF	1816	696	DESW8017DF			
	1800	1060	406	DESW8018SF	1504	576	DESW8018HF	1937	742	DESW8018DF			
	2000	1192	457	DESW8020SF	1692	648	DESW8020HF	2178	834	DESW8020DF	3100	1187	DESW8020TF
	2200	1325	507	DESW8022SF	1880	720	DESW8022HF	2421	927	DESW8022DF	3445	1319	DESW8022TF
	2400	1458	558	DESW8024SF	2068	792	DESW8024HF	2663	1020	DESW8024DF	3790	1451	DESW8024TF
	2600	1590	609	DESW8026SF	2256	864	DESW8026HF	2905	1113	DESW8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T24)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
900	500				327	125	DESW9005HF	419	161	DESW9005DF			
	600	310	119	DESW9006SF	436	167	DESW9006HF	559	214	DESW9006DF	795	305	DESW9006TF
	700	387	148	DESW9007SF	545	209	DESW9007HF	699	268	DESW9007DF	994	381	DESW9007TF
	800	465	178	DESW9008SF	654	250	DESW9008HF	838	321	DESW9008DF	1192	457	DESW9008TF
	900	542	208	DESW9009SF	762	292	DESW9009HF	978	375	DESW9009DF	1391	533	DESW9009TF
	1000	619	237	DESW9010SF	872	334	DESW9010HF	1118	428	DESW9010DF	1590	609	DESW9010TF
	1100	697	267	DESW9011SF	981	376	DESW9011HF	1258	482	DESW9011DF	1789	685	DESW9011TF
	1200	774	297	DESW9012SF	1090	417	DESW9012HF	1398	535	DESW9012DF	1987	761	DESW9012TF
	1300	852	326	DESW9013SF	1198	459	DESW9013HF	1538	589	DESW9013DF	2186	837	DESW9013TF
	1400	930	356	DESW9014SF	1307	501	DESW9014HF	1677	642	DESW9014DF	2385	913	DESW9014TF
	1500	1006	385	DESW9015SF	1417	543	DESW9015HF	1817	696	DESW9015DF			
	1600	1084	415	DESW9016SF	1526	584	DESW9016HF	1957	749	DESW9016DF	2782	1066	DESW9016TF
	1700	1162	445	DESW9017SF	1634	626	DESW9017HF	2097	803	DESW9017DF			
	1800	1239	475	DESW9018SF	1743	668	DESW9018HF	2236	856	DESW9018DF	3179	1218	DESW9018TF
	2000	1394	534	DESW9020SF	1962	751	DESW9020HF	2516	964	DESW9020DF	3577	1370	DESW9020TF
	2200	1549	593	DESW9022SF	2179	835	DESW9022HF	2795	1071	DESW9022DF	3974	1522	DESW9022TF
	2400	1704	653	DESW9024SF	2397	918	DESW9024HF	3074	1177	DESW9024DF			
	2600	1858	712	DESW9026SF	2615	1002	DESW9026HF	3354	1285	DESW9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1000	600	350	134	DESW1006SF	493	189	DESW1006HF	628	241	DESW1006DF	892	342	DESW1006TF
	700	438	168	DESW1007SF	616	236	DESW1007HF	786	301	DESW1007DF	1115	427	DESW1007TF
	800	526	202	DESW1008SF	738	283	DESW1008HF	942	361	DESW1008DF	1338	513	DESW1008TF
	900	614	235	DESW1009SF	862	330	DESW1009HF	1099	421	DESW1009DF	1562	598	DESW1009TF
	1000	702	269	DESW1010SF	985	377	DESW1010HF	1256	481	DESW1010DF	1784	683	DESW1010TF
	1100	789	302	DESW1011SF	1108	424	DESW1011HF	1414	541	DESW1011DF	2007	769	DESW1011TF
	1200	877	336	DESW1012SF	1231	472	DESW1012HF	1570	601	DESW1012DF	2230	854	DESW1012TF
	1300	965	370	DESW1013SF	1354	519	DESW1013HF	1727	662	DESW1013DF	2454	940	DESW1013TF
	1400	1052	403	DESW1014SF	1478	566	DESW1014HF	1885	722	DESW1014DF	2677	1025	DESW1014TF
	1500	1140	437	DESW1015SF	1601	613	DESW1015HF	2042	782	DESW1015DF			
	1600	1227	470	DESW1016SF	1724	660	DESW1016HF	2198	842	DESW1016DF	3122	1196	DESW1016TF
	1700	1315	504	DESW1017SF				2356	902	DESW1017DF			
	1800	1403	537	DESW1018SF	1970	754	DESW1018HF	2513	962	DESW1018DF	3569	1367	DESW1018TF
	2000	1578	605	DESW1020SF	2216	849	DESW1020HF	2826	1083	DESW1020DF			
	2200	1754	672	DESW1022SF				3141	1203	DESW1022DF			
	2400	1929	739	DESW1024SF				3455	1323	DESW1024DF			
	2600	2104	806	DESW1026SF				3769	1443	DESW1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T24)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1200	600	422	161	DESW1206SF	598	229	DESW1206HF	750	287	DESW1206DF	1061	406	DESW1206TF
	700	527	202	DESW1207SF	747	286	DESW1207HF	938	359	DESW1207DF	1326	508	DESW1207TF
	800	633	242	DESW1208SF	897	343	DESW1208HF	1125	431	DESW1208DF	1592	610	DESW1208TF
	900	738	283	DESW1209SF	1046	401	DESW1209HF	1312	502	DESW1209DF	1857	711	DESW1209TF
	1000	843	323	DESW1210SF	1195	458	DESW1210HF	1499	574	DESW1210DF	2122	813	DESW1210TF
	1100	949	363	DESW1211SF				1687	646	DESW1211DF	2387	914	DESW1211TF
	1200	1054	404	DESW1212SF				1874	718	DESW1212DF	2653	1016	DESW1212TF
	1300	1160	444	DESW1213SF									
	1400	1266	485	DESW1214SF				2250	862	DESW1214DF			
	1600	1476	565	DESW1216SF				2624	1005	DESW1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*