



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
600	600	165	85	DESW6006SF	245	126	DESW6006HF	314	161	DESW6006DF			
	700	206	106	DESW6007SF	306	157	DESW6007HF	394	202	DESW6007DF	559	287	DESW6007TF
	800	247	127	DESW6008SF	368	189	DESW6008HF	472	242	DESW6008DF	671	344	DESW6008TF
	900	289	148	DESW6009SF	429	220	DESW6009HF	550	282	DESW6009DF	783	402	DESW6009TF
	1000	330	169	DESW6010SF	490	252	DESW6010HF	629	323	DESW6010DF			
	1100	371	190	DESW6011SF	551	283	DESW6011HF	708	363	DESW6011DF	1006	516	DESW6011TF
	1200	412	211	DESW6012SF	613	314	DESW6012HF	786	403	DESW6012DF	1118	574	DESW6012TF
	1300	454	233	DESW6013SF	674	346	DESW6013HF	865	444	DESW6013DF	1230	631	DESW6013TF
	1400	494	254	DESW6014SF	735	377	DESW6014HF	944	484	DESW6014DF	1342	689	DESW6014TF
	1500	536	275	DESW6015SF									
	1600	577	296	DESW6016SF	858	440	DESW6016HF	1101	565	DESW6016DF	1566	803	DESW6016TF
	1800	659	338	DESW6018SF	981	503	DESW6018HF	1258	646	DESW6018DF	1790	918	DESW6018TF
	2000	742	380	DESW6020SF	1103	566	DESW6020HF	1415	726	DESW6020DF	2013	1033	DESW6020TF
	2200	824	423	DESW6022SF				1573	807	DESW6022DF	2237	1147	DESW6022TF
	2400	906	465	DESW6024SF				1730	888	DESW6024DF			
	2600	989	507	DESW6026SF				1887	968	DESW6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
700	600	217	111	DESW7006SF	313	160	DESW7006HF	403	207	DESW7006DF			
	700	271	139	DESW7007SF	391	201	DESW7007HF	504	259	DESW7007DF	717	368	DESW7007TF
	800	325	167	DESW7008SF	469	240	DESW7008HF	604	310	DESW7008DF	860	441	DESW7008TF
	900	379	195	DESW7009SF	547	281	DESW7009HF	705	362	DESW7009DF	1003	515	DESW7009TF
	1000	434	222	DESW7010SF	626	321	DESW7010HF	806	413	DESW7010DF	1146	588	DESW7010TF
	1100	487	250	DESW7011SF	703	361	DESW7011HF	906	465	DESW7011DF	1290	662	DESW7011TF
	1200	542	278	DESW7012SF	782	401	DESW7012HF	1007	517	DESW7012DF	1433	735	DESW7012TF
	1300	596	306	DESW7013SF	860	441	DESW7013HF	1108	568	DESW7013DF	1576	808	DESW7013TF
	1400	650	333	DESW7014SF	938	481	DESW7014HF	1209	620	DESW7014DF	1719	882	DESW7014TF
	1500	704	361	DESW7015SF	1016	521	DESW7015HF	1310	672	DESW7015DF			
	1600	758	389	DESW7016SF	1094	561	DESW7016HF	1410	724	DESW7016DF			
	1700	813	417	DESW7017SF	1173	602	DESW7017HF	1511	775	DESW7017DF			
	1800	866	444	DESW7018SF	1250	641	DESW7018HF	1611	827	DESW7018DF	2293	1176	DESW7018TF
	2000	975	500	DESW7020SF	1407	722	DESW7020HF	1813	930	DESW7020DF	2579	1323	DESW7020TF
	2200	1083	556	DESW7022SF	1563	802	DESW7022HF	2014	1033	DESW7022DF	2866	1470	DESW7022TF
	2400	1191	611	DESW7024SF	1719	882	DESW7024HF	2216	1137	DESW7024DF	3152	1617	DESW7024TF
	2600	1300	667	DESW7026SF	1876	962	DESW7026HF	2418	1240	DESW7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
800	600	265	136	DESW8006SF	376	193	DESW8006HF	484	248	DESW8006DF			
	700	331	170	DESW8007SF	470	241	DESW8007HF	606	311	DESW8007DF	862	442	DESW8007TF
	800	398	204	DESW8008SF	564	289	DESW8008HF	726	373	DESW8008DF	1034	530	DESW8008TF
	900	464	238	DESW8009SF	658	338	DESW8009HF	847	435	DESW8009DF	1206	618	DESW8009TF
	1000	530	272	DESW8010SF	752	386	DESW8010HF	968	497	DESW8010DF	1378	707	DESW8010TF
	1100	596	306	DESW8011SF	846	434	DESW8011HF	1090	559	DESW8011DF	1550	795	DESW8011TF
	1200	662	340	DESW8012SF	940	482	DESW8012HF	1210	621	DESW8012DF	1722	884	DESW8012TF
	1300	729	374	DESW8013SF	1034	531	DESW8013HF	1331	683	DESW8013DF	1894	972	DESW8013TF
	1400	795	408	DESW8014SF	1128	579	DESW8014HF	1453	745	DESW8014DF	2067	1060	DESW8014TF
	1500	861	442	DESW8015SF	1222	627	DESW8015HF	1574	807	DESW8015DF	2239	1149	DESW8015TF
	1600	927	476	DESW8016SF	1316	675	DESW8016HF	1694	869	DESW8016DF	2411	1237	DESW8016TF
	1700	994	510	DESW8017SF	1410	724	DESW8017HF	1816	932	DESW8017DF			
	1800	1060	544	DESW8018SF	1504	772	DESW8018HF	1937	994	DESW8018DF			
	2000	1192	611	DESW8020SF	1692	868	DESW8020HF	2178	1118	DESW8020DF	3100	1590	DESW8020TF
	2200	1325	680	DESW8022SF	1880	964	DESW8022HF	2421	1242	DESW8022DF	3445	1767	DESW8022TF
	2400	1458	748	DESW8024SF	2068	1061	DESW8024HF	2663	1366	DESW8024DF	3790	1944	DESW8024TF
	2600	1590	815	DESW8026SF	2256	1157	DESW8026HF	2905	1490	DESW8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T30)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
900	500				327	168	DESW9005HF	419	215	DESW9005DF			
	600	310	159	DESW9006SF	436	224	DESW9006HF	559	287	DESW9006DF	795	408	DESW9006TF
	700	387	199	DESW9007SF	545	279	DESW9007HF	699	359	DESW9007DF	994	510	DESW9007TF
	800	465	238	DESW9008SF	654	335	DESW9008HF	838	430	DESW9008DF	1192	611	DESW9008TF
	900	542	278	DESW9009SF	762	391	DESW9009HF	978	502	DESW9009DF	1391	714	DESW9009TF
	1000	619	318	DESW9010SF	872	447	DESW9010HF	1118	574	DESW9010DF	1590	815	DESW9010TF
	1100	697	357	DESW9011SF	981	503	DESW9011HF	1258	645	DESW9011DF	1789	918	DESW9011TF
	1200	774	397	DESW9012SF	1090	559	DESW9012HF	1398	717	DESW9012DF	1987	1019	DESW9012TF
	1300	852	437	DESW9013SF	1198	615	DESW9013HF	1538	789	DESW9013DF	2186	1121	DESW9013TF
	1400	930	477	DESW9014SF	1307	671	DESW9014HF	1677	860	DESW9014DF	2385	1223	DESW9014TF
	1500	1006	516	DESW9015SF	1417	727	DESW9015HF	1817	932	DESW9015DF			
	1600	1084	556	DESW9016SF	1526	783	DESW9016HF	1957	1004	DESW9016DF	2782	1427	DESW9016TF
	1700	1162	596	DESW9017SF	1634	838	DESW9017HF	2097	1076	DESW9017DF			
	1800	1239	636	DESW9018SF	1743	894	DESW9018HF	2236	1147	DESW9018DF	3179	1631	DESW9018TF
	2000	1394	715	DESW9020SF	1962	1006	DESW9020HF	2516	1291	DESW9020DF	3577	1835	DESW9020TF
	2200	1549	795	DESW9022SF	2179	1118	DESW9022HF	2795	1434	DESW9022DF	3974	2039	DESW9022TF
	2400	1704	874	DESW9024SF	2397	1230	DESW9024HF	3074	1577	DESW9024DF			
	2600	1858	953	DESW9026SF	2615	1342	DESW9026HF	3354	1721	DESW9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1000	600	350	180	DESW1006SF	493	253	DESW1006HF	628	322	DESW1006DF	892	458	DESW1006TF
	700	438	225	DESW1007SF	616	316	DESW1007HF	786	403	DESW1007DF	1115	572	DESW1007TF
	800	526	270	DESW1008SF	738	379	DESW1008HF	942	483	DESW1008DF	1338	687	DESW1008TF
	900	614	315	DESW1009SF	862	442	DESW1009HF	1099	564	DESW1009DF	1562	801	DESW1009TF
	1000	702	360	DESW1010SF	985	505	DESW1010HF	1256	644	DESW1010DF	1784	915	DESW1010TF
	1100	789	405	DESW1011SF	1108	568	DESW1011HF	1414	725	DESW1011DF	2007	1030	DESW1011TF
	1200	877	450	DESW1012SF	1231	632	DESW1012HF	1570	806	DESW1012DF	2230	1144	DESW1012TF
	1300	965	495	DESW1013SF	1354	695	DESW1013HF	1727	886	DESW1013DF	2454	1259	DESW1013TF
	1400	1052	540	DESW1014SF	1478	758	DESW1014HF	1885	967	DESW1014DF	2677	1373	DESW1014TF
	1500	1140	585	DESW1015SF	1601	821	DESW1015HF	2042	1047	DESW1015DF			
	1600	1227	630	DESW1016SF	1724	884	DESW1016HF	2198	1128	DESW1016DF	3122	1602	DESW1016TF
	1700	1315	675	DESW1017SF				2356	1209	DESW1017DF			
	1800	1403	720	DESW1018SF	1970	1010	DESW1018HF	2513	1289	DESW1018DF	3569	1831	DESW1018TF
	2000	1578	810	DESW1020SF	2216	1137	DESW1020HF	2826	1450	DESW1020DF			
	2200	1754	900	DESW1022SF				3141	1611	DESW1022DF			
	2400	1929	989	DESW1024SF				3455	1773	DESW1024DF			
	2600	2104	1079	DESW1026SF				3769	1933	DESW1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean Extra - Sloped Top - Wall Mounted - IP3X Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1200	600	422	216	DESW1206SF	598	307	DESW1206HF	750	385	DESW1206DF	1061	544	DESW1206TF
	700	527	270	DESW1207SF	747	383	DESW1207HF	938	481	DESW1207DF	1326	680	DESW1207TF
	800	633	325	DESW1208SF	897	460	DESW1208HF	1125	577	DESW1208DF	1592	817	DESW1208TF
	900	738	379	DESW1209SF	1046	537	DESW1209HF	1312	673	DESW1209DF	1857	953	DESW1209TF
	1000	843	433	DESW1210SF	1195	613	DESW1210HF	1499	769	DESW1210DF	2122	1089	DESW1210TF
	1100	949	487	DESW1211SF				1687	866	DESW1211DF	2387	1225	DESW1211TF
	1200	1054	541	DESW1212SF				1874	962	DESW1212DF	2653	1361	DESW1212TF
	1300	1160	595	DESW1213SF									
	1400	1266	649	DESW1214SF				2250	1154	DESW1214DF			
	1600	1476	757	DESW1216SF				2624	1346	DESW1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*