


DeepClean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T20)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
550	600	183	55	DFF5506SF	272	82	DFF5506HF	350	106	DFF5506DF			
	700	230	69	DFF5507SF	341	103	DFF5507HF	438	132	DFF5507DF	622	188	DFF5507TF
	800	275	83	DFF5508SF	409	124	DFF5508HF	525	159	DFF5508DF	747	226	DFF5508TF
	900	321	97	DFF5509SF	477	144	DFF5509HF	612	185	DFF5509DF	871	263	DFF5509TF
	1000	367	111	DFF5510SF	546	165	DFF5510HF	700	211	DFF5510DF			
	1100	413	125	DFF5511SF	613	185	DFF5511HF	788	238	DFF5511DF	1120	338	DFF5511TF
	1200	458	138	DFF5512SF	682	206	DFF5512HF	875	264	DFF5512DF	1244	376	DFF5512TF
	1300	505	152	DFF5513SF	750	227	DFF5513HF	962	291	DFF5513DF	1369	413	DFF5513TF
	1400	550	166	DFF5514SF	818	247	DFF5514HF	1050	317	DFF5514DF	1493	451	DFF5514TF
	1500	596	180	DFF5515SF									
	1600	642	194	DFF5516SF	954	288	DFF5516HF	1225	370	DFF5516DF	1742	526	DFF5516TF
	1800	733	221	DFF5518SF	1091	330	DFF5518HF	1400	423	DFF5518DF	1991	601	DFF5518TF
	2000	825	249	DFF5520SF	1227	371	DFF5520HF	1574	475	DFF5520DF	2239	676	DFF5520TF
	2200	917	277	DFF5522SF				1750	528	DFF5522DF	2488	752	DFF5522TF
	2400	1008	305	DFF5524SF				1925	581	DFF5524DF			
	2600	1100	332	DFF5526SF				2100	634	DFF5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T20)



Casing Depth

145mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
650	600	241	73	DFF6506SF	348	105	DFF6506HF	449	135	DFF6506DF			
	700	302	91	DFF6507SF	435	131	DFF6507HF	561	169	DFF6507DF	797	241	DFF6507TF
	800	361	109	DFF6508SF	522	158	DFF6508HF	672	203	DFF6508DF	957	289	DFF6508TF
	900	422	127	DFF6509SF	609	184	DFF6509HF	784	237	DFF6509DF	1116	337	DFF6509TF
	1000	482	146	DFF6510SF	696	210	DFF6510HF	896	271	DFF6510DF	1275	385	DFF6510TF
	1100	542	164	DFF6511SF	782	236	DFF6511HF	1008	305	DFF6511DF	1435	433	DFF6511TF
	1200	603	182	DFF6512SF	870	263	DFF6512HF	1121	338	DFF6512DF	1594	481	DFF6512TF
	1300	663	200	DFF6513SF	957	289	DFF6513HF	1233	372	DFF6513DF	1753	529	DFF6513TF
	1400	723	218	DFF6514SF	1043	315	DFF6514HF	1345	406	DFF6514DF	1913	578	DFF6514TF
	1500	783	237	DFF6515SF	1130	341	DFF6515HF	1457	440	DFF6515DF			
	1600	844	255	DFF6516SF	1218	368	DFF6516HF	1569	474	DFF6516DF			
	1700	904	273	DFF6517SF	1305	394	DFF6517HF	1681	508	DFF6517DF			
	1800	964	291	DFF6518SF	1391	420	DFF6518HF	1792	541	DFF6518DF	2551	770	DFF6518TF
	2000	1085	328	DFF6520SF	1566	473	DFF6520HF	2017	609	DFF6520DF	2869	867	DFF6520TF
	2200	1205	364	DFF6522SF	1739	525	DFF6522HF	2241	677	DFF6522DF	3188	963	DFF6522TF
	2400	1325	400	DFF6524SF	1913	578	DFF6524HF	2465	745	DFF6524DF	3507	1059	DFF6524TF
	2600	1446	437	DFF6526SF	2087	630	DFF6526HF	2690	812	DFF6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T20)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
750	600	295	89	DFF7506SF	418	126	DFF7506HF	538	163	DFF7506DF			
	700	368	111	DFF7507SF	523	158	DFF7507HF	674	203	DFF7507DF	959	289	DFF7507TF
	800	442	134	DFF7508SF	627	189	DFF7508HF	808	244	DFF7508DF	1150	347	DFF7508TF
	900	516	156	DFF7509SF	732	221	DFF7509HF	943	285	DFF7509DF	1341	405	DFF7509TF
	1000	589	178	DFF7510SF	837	253	DFF7510HF	1077	325	DFF7510DF	1533	463	DFF7510TF
	1100	663	200	DFF7511SF	942	284	DFF7511HF	1212	366	DFF7511DF	1725	521	DFF7511TF
	1200	737	223	DFF7512SF	1046	316	DFF7512HF	1347	407	DFF7512DF	1916	579	DFF7512TF
	1300	811	245	DFF7513SF	1151	348	DFF7513HF	1481	447	DFF7513DF	2108	636	DFF7513TF
	1400	885	267	DFF7514SF	1255	379	DFF7514HF	1616	488	DFF7514DF	2300	695	DFF7514TF
	1500	958	289	DFF7515SF	1360	411	DFF7515HF	1751	529	DFF7515DF	2491	752	DFF7515TF
	1600	1032	312	DFF7516SF	1464	442	DFF7516HF	1885	569	DFF7516DF	2682	810	DFF7516TF
	1700	1105	334	DFF7517SF	1569	474	DFF7517HF	2020	610	DFF7517DF			
	1800	1179	356	DFF7518SF	1673	505	DFF7518HF	2155	651	DFF7518DF			
	2000	1326	400	DFF7520SF	1882	568	DFF7520HF	2423	732	DFF7520DF	3449	1042	DFF7520TF
	2200	1474	445	DFF7522SF	2092	632	DFF7522HF	2693	813	DFF7522DF	3832	1157	DFF7522TF
	2400	1622	490	DFF7524SF	2301	695	DFF7524HF	2963	895	DFF7524DF	4216	1273	DFF7524TF
	2600	1768	534	DFF7526SF	2510	758	DFF7526HF	3232	976	DFF7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T20)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
850	500				364	110	DFF8505HF	466	141	DFF8505DF			
	600	344	104	DFF8506SF	485	146	DFF8506HF	622	188	DFF8506DF	885	267	DFF8506TF
	700	431	130	DFF8507SF	606	183	DFF8507HF	778	235	DFF8507DF	1105	334	DFF8507TF
	800	517	156	DFF8508SF	727	220	DFF8508HF	933	282	DFF8508DF	1326	400	DFF8508TF
	900	603	182	DFF8509SF	848	256	DFF8509HF	1088	329	DFF8509DF	1548	467	DFF8509TF
	1000	689	208	DFF8510SF	970	293	DFF8510HF	1244	376	DFF8510DF	1768	534	DFF8510TF
	1100	775	234	DFF8511SF	1091	330	DFF8511HF	1399	423	DFF8511DF	1990	601	DFF8511TF
	1200	862	260	DFF8512SF	1212	366	DFF8512HF	1555	470	DFF8512DF	2211	668	DFF8512TF
	1300	948	286	DFF8513SF	1333	403	DFF8513HF	1711	517	DFF8513DF	2431	734	DFF8513TF
	1400	1034	312	DFF8514SF	1454	439	DFF8514HF	1865	563	DFF8514DF	2653	801	DFF8514TF
	1500	1120	338	DFF8515SF	1576	476	DFF8515HF	2021	610	DFF8515DF			
	1600	1206	364	DFF8516SF	1697	513	DFF8516HF	2177	657	DFF8516DF	3095	935	DFF8516TF
	1700	1292	390	DFF8517SF	1818	549	DFF8517HF	2333	704	DFF8517DF			
	1800	1379	416	DFF8518SF	1939	586	DFF8518HF	2488	751	DFF8518DF	3537	1068	DFF8518TF
	2000	1550	468	DFF8520SF	2182	659	DFF8520HF	2799	845	DFF8520DF	3979	1202	DFF8520TF
	2200	1723	520	DFF8522SF	2424	732	DFF8522HF	3110	939	DFF8522DF	4422	1335	DFF8522TF
	2400	1896	573	DFF8524SF	2666	805	DFF8524HF	3420	1033	DFF8524DF			
	2600	2067	624	DFF8526SF	2909	879	DFF8526HF	3732	1127	DFF8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



DeepClean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T20)



Casing Depth

145mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
950	600	390	118	DFF9506SF	548	166	DFF9506HF	699	211	DFF9506DF	992	300	DFF9506TF
	700	488	147	DFF9507SF	685	207	DFF9507HF	874	264	DFF9507DF	1241	375	DFF9507TF
	800	586	177	DFF9508SF	821	248	DFF9508HF	1048	317	DFF9508DF	1489	450	DFF9508TF
	900	683	206	DFF9509SF	959	289	DFF9509HF	1223	369	DFF9509DF	1737	525	DFF9509TF
	1000	781	236	DFF9510SF	1096	331	DFF9510HF	1397	422	DFF9510DF	1985	599	DFF9510TF
	1100	878	265	DFF9511SF	1233	372	DFF9511HF	1573	475	DFF9511DF	2233	674	DFF9511TF
	1200	975	295	DFF9512SF	1370	414	DFF9512HF	1747	528	DFF9512DF	2481	749	DFF9512TF
	1300	1073	324	DFF9513SF	1507	455	DFF9513HF	1922	580	DFF9513DF	2730	824	DFF9513TF
	1400	1170	353	DFF9514SF	1644	496	DFF9514HF	2097	633	DFF9514DF	2978	899	DFF9514TF
	1500	1268	383	DFF9515SF	1781	538	DFF9515HF	2271	686	DFF9515DF			
	1600	1365	412	DFF9516SF	1918	579	DFF9516HF	2446	739	DFF9516DF	3474	1049	DFF9516TF
	1700	1463	442	DFF9517SF				2621	792	DFF9517DF			
	1800	1561	471	DFF9518SF	2191	662	DFF9518HF	2795	844	DFF9518DF	3970	1199	DFF9518TF
	2000	1756	530	DFF9520SF	2465	745	DFF9520HF	3144	950	DFF9520DF			
	2200	1951	589	DFF9522SF				3494	1055	DFF9522DF			
	2400	2146	648	DFF9524SF				3844	1161	DFF9524DF			
	2600	2341	707	DFF9526SF				4193	1266	DFF9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




DeepClean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T20)



145mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1150	600	469	142	DFF1106SF	665	201	DFF1106HF	834	252	DFF1106DF	1180	356	DFF1106TF
	700	587	177	DFF1107SF	831	251	DFF1107HF	1043	315	DFF1107DF	1476	446	DFF1107TF
	800	704	213	DFF1108SF	998	301	DFF1108HF	1251	378	DFF1108DF	1771	535	DFF1108TF
	900	821	248	DFF1109SF	1164	352	DFF1109HF	1460	441	DFF1109DF	2066	624	DFF1109TF
	1000	938	283	DFF1110SF	1330	402	DFF1110HF	1668	504	DFF1110DF	2361	713	DFF1110TF
	1100	1056	319	DFF1111SF				1877	567	DFF1111DF	2656	802	DFF1111TF
	1200	1173	354	DFF1112SF				2085	630	DFF1112DF	2951	891	DFF1112TF
	1300	1290	390	DFF1113SF									
	1400	1408	425	DFF1114SF				2503	756	DFF1114DF			
	1600	1642	496	DFF1116SF				2919	882	DFF1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*