



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T24)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
550	600	183	70	DFF5506SF	272	104	DFF5506HF	350	134	DFF5506DF			
	700	230	88	DFF5507SF	341	131	DFF5507HF	438	168	DFF5507DF	622	238	DFF5507TF
	800	275	105	DFF5508SF	409	157	DFF5508HF	525	201	DFF5508DF	747	286	DFF5508TF
	900	321	123	DFF5509SF	477	183	DFF5509HF	612	235	DFF5509DF	871	334	DFF5509TF
	1000	367	140	DFF5510SF	546	209	DFF5510HF	700	268	DFF5510DF			
	1100	413	158	DFF5511SF	613	235	DFF5511HF	788	302	DFF5511DF	1120	429	DFF5511TF
	1200	458	176	DFF5512SF	682	261	DFF5512HF	875	335	DFF5512DF	1244	477	DFF5512TF
	1300	505	193	DFF5513SF	750	287	DFF5513HF	962	368	DFF5513DF	1369	524	DFF5513TF
	1400	550	211	DFF5514SF	818	313	DFF5514HF	1050	402	DFF5514DF	1493	572	DFF5514TF
	1500	596	228	DFF5515SF									
	1600	642	246	DFF5516SF	954	365	DFF5516HF	1225	469	DFF5516DF	1742	667	DFF5516TF
	1800	733	281	DFF5518SF	1091	418	DFF5518HF	1400	536	DFF5518DF	1991	763	DFF5518TF
	2000	825	316	DFF5520SF	1227	470	DFF5520HF	1574	603	DFF5520DF	2239	858	DFF5520TF
	2200	917	351	DFF5522SF				1750	670	DFF5522DF	2488	953	DFF5522TF
	2400	1008	386	DFF5524SF				1925	737	DFF5524DF			
	2600	1100	421	DFF5526SF				2100	804	DFF5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T24)



145mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
650	600	241	92	DFF6506SF	348	133	DFF6506HF	449	172	DFF6506DF			
	700	302	116	DFF6507SF	435	167	DFF6507HF	561	215	DFF6507DF	797	305	DFF6507TF
	800	361	138	DFF6508SF	522	200	DFF6508HF	672	257	DFF6508DF	957	366	DFF6508TF
	900	422	162	DFF6509SF	609	233	DFF6509HF	784	300	DFF6509DF	1116	427	DFF6509TF
	1000	482	185	DFF6510SF	696	267	DFF6510HF	896	343	DFF6510DF	1275	488	DFF6510TF
	1100	542	208	DFF6511SF	782	300	DFF6511HF	1008	386	DFF6511DF	1435	549	DFF6511TF
	1200	603	231	DFF6512SF	870	333	DFF6512HF	1121	429	DFF6512DF	1594	610	DFF6512TF
	1300	663	254	DFF6513SF	957	366	DFF6513HF	1233	472	DFF6513DF	1753	672	DFF6513TF
	1400	723	277	DFF6514SF	1043	399	DFF6514HF	1345	515	DFF6514DF	1913	733	DFF6514TF
	1500	783	300	DFF6515SF	1130	433	DFF6515HF	1457	558	DFF6515DF			
	1600	844	323	DFF6516SF	1218	466	DFF6516HF	1569	601	DFF6516DF			
	1700	904	346	DFF6517SF	1305	500	DFF6517HF	1681	644	DFF6517DF			
	1800	964	369	DFF6518SF	1391	533	DFF6518HF	1792	687	DFF6518DF	2551	977	DFF6518TF
	2000	1085	416	DFF6520SF	1566	600	DFF6520HF	2017	772	DFF6520DF	2869	1099	DFF6520TF
	2200	1205	462	DFF6522SF	1739	666	DFF6522HF	2241	858	DFF6522DF	3188	1221	DFF6522TF
	2400	1325	508	DFF6524SF	1913	733	DFF6524HF	2465	944	DFF6524DF	3507	1343	DFF6524TF
	2600	1446	554	DFF6526SF	2087	799	DFF6526HF	2690	1030	DFF6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T24)



145mm



165mm



200mm




260mm

Casing Depth



Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
750	600	295	113	DFF7506SF	418	160	DFF7506HF	538	206	DFF7506DF			
	700	368	141	DFF7507SF	523	200	DFF7507HF	674	258	DFF7507DF	959	367	DFF7507TF
	800	442	169	DFF7508SF	627	240	DFF7508HF	808	310	DFF7508DF	1150	440	DFF7508TF
	900	516	198	DFF7509SF	732	281	DFF7509HF	943	361	DFF7509DF	1341	514	DFF7509TF
	1000	589	226	DFF7510SF	837	320	DFF7510HF	1077	412	DFF7510DF	1533	587	DFF7510TF
	1100	663	254	DFF7511SF	942	361	DFF7511HF	1212	464	DFF7511DF	1725	661	DFF7511TF
	1200	737	282	DFF7512SF	1046	401	DFF7512HF	1347	516	DFF7512DF	1916	734	DFF7512TF
	1300	811	311	DFF7513SF	1151	441	DFF7513HF	1481	567	DFF7513DF	2108	807	DFF7513TF
	1400	885	339	DFF7514SF	1255	481	DFF7514HF	1616	619	DFF7514DF	2300	881	DFF7514TF
	1500	958	367	DFF7515SF	1360	521	DFF7515HF	1751	670	DFF7515DF	2491	954	DFF7515TF
	1600	1032	395	DFF7516SF	1464	561	DFF7516HF	1885	722	DFF7516DF	2682	1027	DFF7516TF
	1700	1105	423	DFF7517SF	1569	601	DFF7517HF	2020	774	DFF7517DF			
	1800	1179	452	DFF7518SF	1673	641	DFF7518HF	2155	825	DFF7518DF			
	2000	1326	508	DFF7520SF	1882	721	DFF7520HF	2423	928	DFF7520DF	3449	1321	DFF7520TF
	2200	1474	564	DFF7522SF	2092	801	DFF7522HF	2693	1031	DFF7522DF	3832	1468	DFF7522TF
	2400	1622	621	DFF7524SF	2301	881	DFF7524HF	2963	1135	DFF7524DF	4216	1615	DFF7524TF
	2600	1768	677	DFF7526SF	2510	961	DFF7526HF	3232	1238	DFF7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T24)



Casing Depth

145mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
850	500	259	99	DFF8505SF	364	139	DFF8505HF	466	179	DFF8505DF			
	600	344	132	DFF8506SF	485	186	DFF8506HF	622	238	DFF8506DF	885	339	DFF8506TF
	700	431	165	DFF8507SF	606	232	DFF8507HF	778	298	DFF8507DF	1105	423	DFF8507TF
	800	517	198	DFF8508SF	727	278	DFF8508HF	933	357	DFF8508DF	1326	508	DFF8508TF
	900	603	231	DFF8509SF	848	325	DFF8509HF	1088	417	DFF8509DF	1548	593	DFF8509TF
	1000	689	264	DFF8510SF	970	372	DFF8510HF	1244	477	DFF8510DF	1768	677	DFF8510TF
	1100	775	297	DFF8511SF	1091	418	DFF8511HF	1399	536	DFF8511DF	1990	762	DFF8511TF
	1200	862	330	DFF8512SF	1212	464	DFF8512HF	1555	595	DFF8512DF	2211	847	DFF8512TF
	1300	948	363	DFF8513SF	1333	511	DFF8513HF	1711	655	DFF8513DF	2431	931	DFF8513TF
	1400	1034	396	DFF8514SF	1454	557	DFF8514HF	1865	714	DFF8514DF	2653	1016	DFF8514TF
	1500	1120	429	DFF8515SF	1576	604	DFF8515HF	2021	774	DFF8515DF			
	1600	1206	462	DFF8516SF	1697	650	DFF8516HF	2177	834	DFF8516DF	3095	1186	DFF8516TF
	1700	1292	495	DFF8517SF	1818	696	DFF8517HF	2333	893	DFF8517DF			
	1800	1379	528	DFF8518SF	1939	743	DFF8518HF	2488	953	DFF8518DF	3537	1355	DFF8518TF
	2000	1550	594	DFF8520SF	2182	836	DFF8520HF	2799	1072	DFF8520DF	3979	1524	DFF8520TF
	2200	1723	660	DFF8522SF	2424	929	DFF8522HF	3110	1191	DFF8522DF	4422	1693	DFF8522TF
	2400	1896	726	DFF8524SF	2666	1021	DFF8524HF	3420	1310	DFF8524DF			
	2600	2067	792	DFF8526SF	2909	1114	DFF8526HF	3732	1429	DFF8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T24)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
950	600				548	210	DFF9506HF	699	268	DFF9506DF	992	380	DFF9506TF
	700	488	187	DFF9507SF	685	262	DFF9507HF	874	335	DFF9507DF	1241	475	DFF9507TF
	800	586	224	DFF9508SF	821	315	DFF9508HF	1048	402	DFF9508DF	1489	570	DFF9508TF
	900	683	261	DFF9509SF	959	367	DFF9509HF	1223	468	DFF9509DF	1737	665	DFF9509TF
	1000	781	299	DFF9510SF	1096	420	DFF9510HF	1397	535	DFF9510DF	1985	760	DFF9510TF
	1100	878	336	DFF9511SF	1233	472	DFF9511HF	1573	602	DFF9511DF	2233	855	DFF9511TF
	1200	975	374	DFF9512SF	1370	525	DFF9512HF	1747	669	DFF9512DF	2481	950	DFF9512TF
	1300	1073	411	DFF9513SF	1507	577	DFF9513HF	1922	736	DFF9513DF	2730	1045	DFF9513TF
	1400	1170	448	DFF9514SF	1644	630	DFF9514HF	2097	803	DFF9514DF	2978	1141	DFF9514TF
	1500	1268	486	DFF9515SF	1781	682	DFF9515HF	2271	870	DFF9515DF			
	1600	1365	523	DFF9516SF	1918	735	DFF9516HF	2446	937	DFF9516DF	3474	1330	DFF9516TF
	1700	1463	560	DFF9517SF				2621	1004	DFF9517DF			
	1800	1561	598	DFF9518SF	2191	839	DFF9518HF	2795	1071	DFF9518DF	3970	1521	DFF9518TF
	2000	1756	673	DFF9520SF	2465	944	DFF9520HF	3144	1204	DFF9520DF			
	2200	1951	747	DFF9522SF				3494	1338	DFF9522DF			
	2400	2146	822	DFF9524SF				3844	1472	DFF9524DF			
	2600	2341	896	DFF9526SF				4193	1606	DFF9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T24)



145mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1150	600	469	180	DFF1106SF	665	255	DFF1106HF	834	319	DFF1106DF	1180	452	DFF1106TF
	700	587	225	DFF1107SF	831	318	DFF1107HF	1043	399	DFF1107DF	1476	565	DFF1107TF
	800	704	270	DFF1108SF	998	382	DFF1108HF	1251	479	DFF1108DF	1771	678	DFF1108TF
	900	821	315	DFF1109SF	1164	446	DFF1109HF	1460	559	DFF1109DF	2066	791	DFF1109TF
	1000	938	359	DFF1110SF	1330	509	DFF1110HF	1668	639	DFF1110DF	2361	904	DFF1110TF
	1100	1056	404	DFF1111SF				1877	719	DFF1111DF	2656	1017	DFF1111TF
	1200	1173	449	DFF1112SF				2085	799	DFF1112DF	2951	1130	DFF1112TF
	1300	1290	494	DFF1113SF									
	1400	1408	539	DFF1114SF				2503	959	DFF1114DF			
	1600	1642	629	DFF1116SF				2919	1118	DFF1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*