



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T30)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
550	600	183	94	DFF5506SF	272	140	DFF5506HF	350	179	DFF5506DF			
	700	230	118	DFF5507SF	341	175	DFF5507HF	438	225	DFF5507DF	622	319	DFF5507TF
	800	275	141	DFF5508SF	409	210	DFF5508HF	525	269	DFF5508DF	747	383	DFF5508TF
	900	321	165	DFF5509SF	477	245	DFF5509HF	612	314	DFF5509DF	871	447	DFF5509TF
	1000	367	188	DFF5510SF	546	280	DFF5510HF	700	359	DFF5510DF			
	1100	413	212	DFF5511SF	613	315	DFF5511HF	788	404	DFF5511DF	1120	574	DFF5511TF
	1200	458	235	DFF5512SF	682	350	DFF5512HF	875	449	DFF5512DF	1244	638	DFF5512TF
	1300	505	259	DFF5513SF	750	385	DFF5513HF	962	494	DFF5513DF	1369	702	DFF5513TF
	1400	550	282	DFF5514SF	818	420	DFF5514HF	1050	539	DFF5514DF	1493	766	DFF5514TF
	1500	596	306	DFF5515SF									
	1600	642	329	DFF5516SF	954	489	DFF5516HF	1225	628	DFF5516DF	1742	894	DFF5516TF
	1800	733	376	DFF5518SF	1091	560	DFF5518HF	1400	718	DFF5518DF	1991	1021	DFF5518TF
	2000	825	423	DFF5520SF	1227	630	DFF5520HF	1574	808	DFF5520DF	2239	1149	DFF5520TF
	2200	917	470	DFF5522SF				1750	898	DFF5522DF	2488	1277	DFF5522TF
	2400	1008	517	DFF5524SF				1925	988	DFF5524DF			
	2600	1100	564	DFF5526SF				2100	1077	DFF5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T30)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
650	600	241	124	DFF6506SF	348	179	DFF6506HF	449	230	DFF6506DF			
	700	302	155	DFF6507SF	435	223	DFF6507HF	561	288	DFF6507DF	797	409	DFF6507TF
	800	361	185	DFF6508SF	522	268	DFF6508HF	672	345	DFF6508DF	957	491	DFF6508TF
	900	422	216	DFF6509SF	609	312	DFF6509HF	784	402	DFF6509DF	1116	573	DFF6509TF
	1000	482	247	DFF6510SF	696	357	DFF6510HF	896	460	DFF6510DF	1275	654	DFF6510TF
	1100	542	278	DFF6511SF	782	401	DFF6511HF	1008	517	DFF6511DF	1435	736	DFF6511TF
	1200	603	309	DFF6512SF	870	446	DFF6512HF	1121	575	DFF6512DF	1594	818	DFF6512TF
	1300	663	340	DFF6513SF	957	491	DFF6513HF	1233	632	DFF6513DF	1753	899	DFF6513TF
	1400	723	371	DFF6514SF	1043	535	DFF6514HF	1345	690	DFF6514DF	1913	981	DFF6514TF
	1500	783	402	DFF6515SF	1130	580	DFF6515HF	1457	747	DFF6515DF			
	1600	844	433	DFF6516SF	1218	625	DFF6516HF	1569	805	DFF6516DF			
	1700	904	464	DFF6517SF	1305	669	DFF6517HF	1681	862	DFF6517DF			
	1800	964	494	DFF6518SF	1391	714	DFF6518HF	1792	920	DFF6518DF	2551	1309	DFF6518TF
	2000	1085	557	DFF6520SF	1566	803	DFF6520HF	2017	1035	DFF6520DF	2869	1472	DFF6520TF
	2200	1205	618	DFF6522SF	1739	892	DFF6522HF	2241	1150	DFF6522DF	3188	1635	DFF6522TF
	2400	1325	680	DFF6524SF	1913	981	DFF6524HF	2465	1265	DFF6524DF	3507	1799	DFF6524TF
	2600	1446	742	DFF6526SF	2087	1071	DFF6526HF	2690	1380	DFF6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

145mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
750	600	295	151	DFF7506SF	418	215	DFF7506HF	538	276	DFF7506DF			
	700	368	189	DFF7507SF	523	268	DFF7507HF	674	346	DFF7507DF	959	492	DFF7507TF
	800	442	227	DFF7508SF	627	322	DFF7508HF	808	415	DFF7508DF	1150	590	DFF7508TF
	900	516	265	DFF7509SF	732	376	DFF7509HF	943	484	DFF7509DF	1341	688	DFF7509TF
	1000	589	302	DFF7510SF	837	429	DFF7510HF	1077	552	DFF7510DF	1533	786	DFF7510TF
	1100	663	340	DFF7511SF	942	483	DFF7511HF	1212	622	DFF7511DF	1725	885	DFF7511TF
	1200	737	378	DFF7512SF	1046	536	DFF7512HF	1347	691	DFF7512DF	1916	983	DFF7512TF
	1300	811	416	DFF7513SF	1151	590	DFF7513HF	1481	760	DFF7513DF	2108	1081	DFF7513TF
	1400	885	454	DFF7514SF	1255	644	DFF7514HF	1616	829	DFF7514DF	2300	1180	DFF7514TF
	1500	958	491	DFF7515SF	1360	698	DFF7515HF	1751	898	DFF7515DF	2491	1278	DFF7515TF
	1600	1032	529	DFF7516SF	1464	751	DFF7516HF	1885	967	DFF7516DF	2682	1376	DFF7516TF
	1700	1105	567	DFF7517SF	1569	805	DFF7517HF	2020	1036	DFF7517DF			
	1800	1179	605	DFF7518SF	1673	858	DFF7518HF	2155	1105	DFF7518DF			
	2000	1326	680	DFF7520SF	1882	966	DFF7520HF	2423	1243	DFF7520DF	3449	1769	DFF7520TF
	2200	1474	756	DFF7522SF	2092	1073	DFF7522HF	2693	1382	DFF7522DF	3832	1966	DFF7522TF
	2400	1622	832	DFF7524SF	2301	1180	DFF7524HF	2963	1520	DFF7524DF	4216	2163	DFF7524TF
	2600	1768	907	DFF7526SF	2510	1288	DFF7526HF	3232	1658	DFF7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

145mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
850	500				364	187	DFF8505HF	466	239	DFF8505DF			
	600	344	177	DFF8506SF	485	249	DFF8506HF	622	319	DFF8506DF	885	454	DFF8506TF
	700	431	221	DFF8507SF	606	311	DFF8507HF	778	399	DFF8507DF	1105	567	DFF8507TF
	800	517	265	DFF8508SF	727	373	DFF8508HF	933	478	DFF8508DF	1326	680	DFF8508TF
	900	603	310	DFF8509SF	848	435	DFF8509HF	1088	558	DFF8509DF	1548	794	DFF8509TF
	1000	689	353	DFF8510SF	970	498	DFF8510HF	1244	638	DFF8510DF	1768	907	DFF8510TF
	1100	775	398	DFF8511SF	1091	560	DFF8511HF	1399	718	DFF8511DF	1990	1021	DFF8511TF
	1200	862	442	DFF8512SF	1212	622	DFF8512HF	1555	798	DFF8512DF	2211	1134	DFF8512TF
	1300	948	486	DFF8513SF	1333	684	DFF8513HF	1711	878	DFF8513DF	2431	1247	DFF8513TF
	1400	1034	531	DFF8514SF	1454	746	DFF8514HF	1865	957	DFF8514DF	2653	1361	DFF8514TF
	1500	1120	574	DFF8515SF	1576	809	DFF8515HF	2021	1037	DFF8515DF			
	1600	1206	619	DFF8516SF	1697	871	DFF8516HF	2177	1117	DFF8516DF	3095	1588	DFF8516TF
	1700	1292	663	DFF8517SF	1818	933	DFF8517HF	2333	1197	DFF8517DF			
	1800	1379	707	DFF8518SF	1939	995	DFF8518HF	2488	1276	DFF8518DF	3537	1814	DFF8518TF
	2000	1550	795	DFF8520SF	2182	1120	DFF8520HF	2799	1436	DFF8520DF	3979	2041	DFF8520TF
	2200	1723	884	DFF8522SF	2424	1244	DFF8522HF	3110	1595	DFF8522DF	4422	2268	DFF8522TF
	2400	1896	972	DFF8524SF	2666	1368	DFF8524HF	3420	1755	DFF8524DF			
	2600	2067	1061	DFF8526SF	2909	1493	DFF8526HF	3732	1914	DFF8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T30)



145mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
950	600	390	200	DFF9506SF	548	281	DFF9506HF	699	358	DFF9506DF	992	509	DFF9506TF
	700	488	250	DFF9507SF	685	352	DFF9507HF	874	448	DFF9507DF	1241	636	DFF9507TF
	800	586	300	DFF9508SF	821	421	DFF9508HF	1048	538	DFF9508DF	1489	764	DFF9508TF
	900	683	350	DFF9509SF	959	492	DFF9509HF	1223	627	DFF9509DF	1737	891	DFF9509TF
	1000	781	400	DFF9510SF	1096	562	DFF9510HF	1397	717	DFF9510DF	1985	1018	DFF9510TF
	1100	878	450	DFF9511SF	1233	632	DFF9511HF	1573	807	DFF9511DF	2233	1146	DFF9511TF
	1200	975	500	DFF9512SF	1370	703	DFF9512HF	1747	896	DFF9512DF	2481	1273	DFF9512TF
	1300	1073	551	DFF9513SF	1507	773	DFF9513HF	1922	986	DFF9513DF	2730	1400	DFF9513TF
	1400	1170	600	DFF9514SF	1644	843	DFF9514HF	2097	1076	DFF9514DF	2978	1528	DFF9514TF
	1500	1268	651	DFF9515SF	1781	914	DFF9515HF	2271	1165	DFF9515DF			
	1600	1365	700	DFF9516SF	1918	984	DFF9516HF	2446	1255	DFF9516DF	3474	1782	DFF9516TF
	1700	1463	751	DFF9517SF				2621	1345	DFF9517DF			
	1800	1561	801	DFF9518SF	2191	1124	DFF9518HF	2795	1434	DFF9518DF	3970	2037	DFF9518TF
	2000	1756	901	DFF9520SF	2465	1265	DFF9520HF	3144	1613	DFF9520DF			
	2200	1951	1001	DFF9522SF				3494	1792	DFF9522DF			
	2400	2146	1101	DFF9524SF				3844	1972	DFF9524DF			
	2600	2341	1201	DFF9526SF				4193	2151	DFF9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

145mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1150	600	469	241	DFF1106SF	665	341	DFF1106HF	834	428	DFF1106DF	1180	605	DFF1106TF
	700	587	301	DFF1107SF	831	426	DFF1107HF	1043	535	DFF1107DF	1476	757	DFF1107TF
	800	704	361	DFF1108SF	998	512	DFF1108HF	1251	642	DFF1108DF	1771	909	DFF1108TF
	900	821	421	DFF1109SF	1164	597	DFF1109HF	1460	749	DFF1109DF	2066	1060	DFF1109TF
	1000	938	481	DFF1110SF	1330	682	DFF1110HF	1668	856	DFF1110DF	2361	1211	DFF1110TF
	1100	1056	541	DFF1111SF				1877	963	DFF1111DF	2656	1362	DFF1111TF
	1200	1173	602	DFF1112SF				2085	1070	DFF1112DF	2951	1514	DFF1112TF
	1300	1290	662	DFF1113SF									
	1400	1408	722	DFF1114SF				2503	1284	DFF1114DF			
	1600	1642	842	DFF1116SF				2919	1498	DFF1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*