



Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
550	600	183	55	DFW5506SF	272	82	DFW5506HF	350	106	DFW5506DF			
	700	230	69	DFW5507SF	341	103	DFW5507HF	438	132	DFW5507DF	622	188	DFW5507TF
	800	275	83	DFW5508SF	409	124	DFW5508HF	525	159	DFW5508DF	747	226	DFW5508TF
	900	321	97	DFW5509SF	477	144	DFW5509HF	612	185	DFW5509DF	871	263	DFW5509TF
	1000	367	111	DFW5510SF	546	165	DFW5510HF	700	211	DFW5510DF			
	1100	413	125	DFW5511SF	613	185	DFW5511HF	788	238	DFW5511DF	1120	338	DFW5511TF
	1200	458	138	DFW5512SF	682	206	DFW5512HF	875	264	DFW5512DF	1244	376	DFW5512TF
	1300	505	152	DFW5513SF	750	227	DFW5513HF	962	291	DFW5513DF	1369	413	DFW5513TF
	1400	550	166	DFW5514SF	818	247	DFW5514HF	1050	317	DFW5514DF	1493	451	DFW5514TF
	1500	596	180	DFW5515SF									
	1600	642	194	DFW5516SF	954	288	DFW5516HF	1225	370	DFW5516DF	1742	526	DFW5516TF
	1800	733	221	DFW5518SF	1091	330	DFW5518HF	1400	423	DFW5518DF	1991	601	DFW5518TF
	2000	825	249	DFW5520SF	1227	371	DFW5520HF	1574	475	DFW5520DF	2239	676	DFW5520TF
	2200	917	277	DFW5522SF				1750	528	DFW5522DF	2488	752	DFW5522TF
	2400	1008	305	DFW5524SF				1925	581	DFW5524DF			
	2600	1100	332	DFW5526SF				2100	634	DFW5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
650	600	241	73	DFW6506SF	348	105	DFW6506HF	449	135	DFW6506DF			
	700	302	91	DFW6507SF	435	131	DFW6507HF	561	169	DFW6507DF	797	241	DFW6507TF
	800	361	109	DFW6508SF	522	158	DFW6508HF	672	203	DFW6508DF	957	289	DFW6508TF
	900	422	127	DFW6509SF	609	184	DFW6509HF	784	237	DFW6509DF	1116	337	DFW6509TF
	1000	482	146	DFW6510SF	696	210	DFW6510HF	896	271	DFW6510DF	1275	385	DFW6510TF
	1100	542	164	DFW6511SF	782	236	DFW6511HF	1008	305	DFW6511DF	1435	433	DFW6511TF
	1200	603	182	DFW6512SF	870	263	DFW6512HF	1121	338	DFW6512DF	1594	481	DFW6512TF
	1300	663	200	DFW6513SF	957	289	DFW6513HF	1233	372	DFW6513DF	1753	529	DFW6513TF
	1400	723	218	DFW6514SF	1043	315	DFW6514HF	1345	406	DFW6514DF	1913	578	DFW6514TF
	1500	783	237	DFW6515SF	1130	341	DFW6515HF	1457	440	DFW6515DF			
	1600	844	255	DFW6516SF	1218	368	DFW6516HF	1569	474	DFW6516DF			
	1700	904	273	DFW6517SF	1305	394	DFW6517HF	1681	508	DFW6517DF			
	1800	964	291	DFW6518SF	1391	420	DFW6518HF	1792	541	DFW6518DF	2551	770	DFW6518TF
	2000	1085	328	DFW6520SF	1566	473	DFW6520HF	2017	609	DFW6520DF	2869	867	DFW6520TF
	2200	1205	364	DFW6522SF	1739	525	DFW6522HF	2241	677	DFW6522DF	3188	963	DFW6522TF
	2400	1325	400	DFW6524SF	1913	578	DFW6524HF	2465	745	DFW6524DF	3507	1059	DFW6524TF
	2600	1446	437	DFW6526SF	2087	630	DFW6526HF	2690	812	DFW6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
750	500	223	67	DFW7505SF									
	600	295	89	DFW7506SF	418	126	DFW7506HF	538	163	DFW7506DF			
	700	368	111	DFW7507SF	523	158	DFW7507HF	674	203	DFW7507DF	959	289	DFW7507TF
	800	442	134	DFW7508SF	627	189	DFW7508HF	808	244	DFW7508DF	1150	347	DFW7508TF
	900	516	156	DFW7509SF	732	221	DFW7509HF	943	285	DFW7509DF	1341	405	DFW7509TF
	1000	589	178	DFW7510SF	837	253	DFW7510HF	1077	325	DFW7510DF	1533	463	DFW7510TF
	1100	663	200	DFW7511SF	942	284	DFW7511HF	1212	366	DFW7511DF	1725	521	DFW7511TF
	1200	737	223	DFW7512SF	1046	316	DFW7512HF	1347	407	DFW7512DF	1916	579	DFW7512TF
	1300	811	245	DFW7513SF	1151	348	DFW7513HF	1481	447	DFW7513DF	2108	636	DFW7513TF
	1400	885	267	DFW7514SF	1255	379	DFW7514HF	1616	488	DFW7514DF	2300	695	DFW7514TF
	1500	958	289	DFW7515SF	1360	411	DFW7515HF	1751	529	DFW7515DF	2491	752	DFW7515TF
	1600	1032	312	DFW7516SF	1464	442	DFW7516HF	1885	569	DFW7516DF	2682	810	DFW7516TF
	1700	1105	334	DFW7517SF	1569	474	DFW7517HF	2020	610	DFW7517DF			
	1800	1179	356	DFW7518SF	1673	505	DFW7518HF	2155	651	DFW7518DF			
	2000	1326	400	DFW7520SF	1882	568	DFW7520HF	2423	732	DFW7520DF	3449	1042	DFW7520TF
	2200	1474	445	DFW7522SF	2092	632	DFW7522HF	2693	813	DFW7522DF	3832	1157	DFW7522TF
	2400	1622	490	DFW7524SF	2301	695	DFW7524HF	2963	895	DFW7524DF	4216	1273	DFW7524TF
	2600	1768	534	DFW7526SF	2510	758	DFW7526HF	3232	976	DFW7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
850	500	259	78	DFW8505SF	364	110	DFW8505HF	466	141	DFW8505DF			
	600	344	104	DFW8506SF	485	146	DFW8506HF	622	188	DFW8506DF	885	267	DFW8506TF
	700	431	130	DFW8507SF	606	183	DFW8507HF	778	235	DFW8507DF	1105	334	DFW8507TF
	800	517	156	DFW8508SF	727	220	DFW8508HF	933	282	DFW8508DF	1326	400	DFW8508TF
	900	603	182	DFW8509SF	848	256	DFW8509HF	1088	329	DFW8509DF	1548	467	DFW8509TF
	1000	689	208	DFW8510SF	970	293	DFW8510HF	1244	376	DFW8510DF	1768	534	DFW8510TF
	1100	775	234	DFW8511SF	1091	330	DFW8511HF	1399	423	DFW8511DF	1990	601	DFW8511TF
	1200	862	260	DFW8512SF	1212	366	DFW8512HF	1555	470	DFW8512DF	2211	668	DFW8512TF
	1300	948	286	DFW8513SF	1333	403	DFW8513HF	1711	517	DFW8513DF	2431	734	DFW8513TF
	1400	1034	312	DFW8514SF	1454	439	DFW8514HF	1865	563	DFW8514DF	2653	801	DFW8514TF
	1500	1120	338	DFW8515SF	1576	476	DFW8515HF	2021	610	DFW8515DF			
	1600	1206	364	DFW8516SF	1697	513	DFW8516HF	2177	657	DFW8516DF	3095	935	DFW8516TF
	1700	1292	390	DFW8517SF	1818	549	DFW8517HF	2333	704	DFW8517DF			
	1800	1379	416	DFW8518SF	1939	586	DFW8518HF	2488	751	DFW8518DF	3537	1068	DFW8518TF
	2000	1550	468	DFW8520SF	2182	659	DFW8520HF	2799	845	DFW8520DF	3979	1202	DFW8520TF
	2200	1723	520	DFW8522SF	2424	732	DFW8522HF	3110	939	DFW8522DF	4422	1335	DFW8522TF
	2400	1896	573	DFW8524SF	2666	805	DFW8524HF	3420	1033	DFW8524DF			
	2600	2067	624	DFW8526SF	2909	879	DFW8526HF	3732	1127	DFW8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
950	600	390	118	DFW9506SF	548	166	DFW9506HF	699	211	DFW9506DF	992	300	DFW9506TF
	700	488	147	DFW9507SF	685	207	DFW9507HF	874	264	DFW9507DF	1241	375	DFW9507TF
	800	586	177	DFW9508SF	821	248	DFW9508HF	1048	317	DFW9508DF	1489	450	DFW9508TF
	900	683	206	DFW9509SF	959	289	DFW9509HF	1223	369	DFW9509DF	1737	525	DFW9509TF
	1000	781	236	DFW9510SF	1096	331	DFW9510HF	1397	422	DFW9510DF	1985	599	DFW9510TF
	1100	878	265	DFW9511SF	1233	372	DFW9511HF	1573	475	DFW9511DF	2233	674	DFW9511TF
	1200	975	295	DFW9512SF	1370	414	DFW9512HF	1747	528	DFW9512DF	2481	749	DFW9512TF
	1300	1073	324	DFW9513SF	1507	455	DFW9513HF	1922	580	DFW9513DF	2730	824	DFW9513TF
	1400	1170	353	DFW9514SF	1644	496	DFW9514HF	2097	633	DFW9514DF	2978	899	DFW9514TF
	1500	1268	383	DFW9515SF	1781	538	DFW9515HF	2271	686	DFW9515DF			
	1600	1365	412	DFW9516SF	1918	579	DFW9516HF	2446	739	DFW9516DF	3474	1049	DFW9516TF
	1700	1463	442	DFW9517SF				2621	792	DFW9517DF			
	1800	1561	471	DFW9518SF	2191	662	DFW9518HF	2795	844	DFW9518DF	3970	1199	DFW9518TF
	2000	1756	530	DFW9520SF	2465	745	DFW9520HF	3144	950	DFW9520DF			
	2200	1951	589	DFW9522SF				3494	1055	DFW9522DF			
	2400	2146	648	DFW9524SF				3844	1161	DFW9524DF			
	2600	2341	707	DFW9526SF				4193	1266	DFW9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1150	600	469	142	DFW1106SF	665	201	DFW1106HF	834	252	DFW1106DF	1180	356	DFW1106TF
	700	587	177	DFW1107SF	831	251	DFW1107HF	1043	315	DFW1107DF	1476	446	DFW1107TF
	800	704	213	DFW1108SF	998	301	DFW1108HF	1251	378	DFW1108DF	1771	535	DFW1108TF
	900	821	248	DFW1109SF	1164	352	DFW1109HF	1460	441	DFW1109DF	2066	624	DFW1109TF
	1000	938	283	DFW1110SF	1330	402	DFW1110HF	1668	504	DFW1110DF	2361	713	DFW1110TF
	1100	1056	319	DFW1111SF				1877	567	DFW1111DF	2656	802	DFW1111TF
	1200	1173	354	DFW1112SF				2085	630	DFW1112DF	2951	891	DFW1112TF
	1300	1290	390	DFW1113SF				2455	741	DFW1113DF			
	1400	1408	425	DFW1114SF				2503	756	DFW1114DF			
	1500							2901	876	DFW1115DF			
	1600	1642	496	DFW1116SF				2919	882	DFW1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*