


Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
550	600	183	70	DFW5506SF	272	104	DFW5506HF	350	134	DFW5506DF			
	700	230	88	DFW5507SF	341	131	DFW5507HF	438	168	DFW5507DF	622	238	DFW5507TF
	800	275	105	DFW5508SF	409	157	DFW5508HF	525	201	DFW5508DF	747	286	DFW5508TF
	900	321	123	DFW5509SF	477	183	DFW5509HF	612	235	DFW5509DF	871	334	DFW5509TF
	1000	367	140	DFW5510SF	546	209	DFW5510HF	700	268	DFW5510DF			
	1100	413	158	DFW5511SF	613	235	DFW5511HF	788	302	DFW5511DF	1120	429	DFW5511TF
	1200	458	176	DFW5512SF	682	261	DFW5512HF	875	335	DFW5512DF	1244	477	DFW5512TF
	1300	505	193	DFW5513SF	750	287	DFW5513HF	962	368	DFW5513DF	1369	524	DFW5513TF
	1400	550	211	DFW5514SF	818	313	DFW5514HF	1050	402	DFW5514DF	1493	572	DFW5514TF
	1500	596	228	DFW5515SF									
	1600	642	246	DFW5516SF	954	365	DFW5516HF	1225	469	DFW5516DF	1742	667	DFW5516TF
	1800	733	281	DFW5518SF	1091	418	DFW5518HF	1400	536	DFW5518DF	1991	763	DFW5518TF
	2000	825	316	DFW5520SF	1227	470	DFW5520HF	1574	603	DFW5520DF	2239	858	DFW5520TF
	2200	917	351	DFW5522SF				1750	670	DFW5522DF	2488	953	DFW5522TF
	2400	1008	386	DFW5524SF				1925	737	DFW5524DF			
	2600	1100	421	DFW5526SF				2100	804	DFW5526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
650	600	241	92	DFW6506SF	348	133	DFW6506HF	449	172	DFW6506DF			
	700	302	116	DFW6507SF	435	167	DFW6507HF	561	215	DFW6507DF	797	305	DFW6507TF
	800	361	138	DFW6508SF	522	200	DFW6508HF	672	257	DFW6508DF	957	366	DFW6508TF
	900	422	162	DFW6509SF	609	233	DFW6509HF	784	300	DFW6509DF	1116	427	DFW6509TF
	1000	482	185	DFW6510SF	696	267	DFW6510HF	896	343	DFW6510DF	1275	488	DFW6510TF
	1100	542	208	DFW6511SF	782	300	DFW6511HF	1008	386	DFW6511DF	1435	549	DFW6511TF
	1200	603	231	DFW6512SF	870	333	DFW6512HF	1121	429	DFW6512DF	1594	610	DFW6512TF
	1300	663	254	DFW6513SF	957	366	DFW6513HF	1233	472	DFW6513DF	1753	672	DFW6513TF
	1400	723	277	DFW6514SF	1043	399	DFW6514HF	1345	515	DFW6514DF	1913	733	DFW6514TF
	1500	783	300	DFW6515SF	1130	433	DFW6515HF	1457	558	DFW6515DF			
	1600	844	323	DFW6516SF	1218	466	DFW6516HF	1569	601	DFW6516DF			
	1700	904	346	DFW6517SF	1305	500	DFW6517HF	1681	644	DFW6517DF			
	1800	964	369	DFW6518SF	1391	533	DFW6518HF	1792	687	DFW6518DF	2551	977	DFW6518TF
	2000	1085	416	DFW6520SF	1566	600	DFW6520HF	2017	772	DFW6520DF	2869	1099	DFW6520TF
	2200	1205	462	DFW6522SF	1739	666	DFW6522HF	2241	858	DFW6522DF	3188	1221	DFW6522TF
	2400	1325	508	DFW6524SF	1913	733	DFW6524HF	2465	944	DFW6524DF	3507	1343	DFW6524TF
	2600	1446	554	DFW6526SF	2087	799	DFW6526HF	2690	1030	DFW6526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
750	600	295	113	DFW7506SF	418	160	DFW7506HF	538	206	DFW7506DF			
	700	368	141	DFW7507SF	523	200	DFW7507HF	674	258	DFW7507DF	959	367	DFW7507TF
	800	442	169	DFW7508SF	627	240	DFW7508HF	808	310	DFW7508DF	1150	440	DFW7508TF
	900	516	198	DFW7509SF	732	281	DFW7509HF	943	361	DFW7509DF	1341	514	DFW7509TF
	1000	589	226	DFW7510SF	837	320	DFW7510HF	1077	412	DFW7510DF	1533	587	DFW7510TF
	1100	663	254	DFW7511SF	942	361	DFW7511HF	1212	464	DFW7511DF	1725	661	DFW7511TF
	1200	737	282	DFW7512SF	1046	401	DFW7512HF	1347	516	DFW7512DF	1916	734	DFW7512TF
	1300	811	311	DFW7513SF	1151	441	DFW7513HF	1481	567	DFW7513DF	2108	807	DFW7513TF
	1400	885	339	DFW7514SF	1255	481	DFW7514HF	1616	619	DFW7514DF	2300	881	DFW7514TF
	1500	958	367	DFW7515SF	1360	521	DFW7515HF	1751	670	DFW7515DF	2491	954	DFW7515TF
	1600	1032	395	DFW7516SF	1464	561	DFW7516HF	1885	722	DFW7516DF	2682	1027	DFW7516TF
	1700	1105	423	DFW7517SF	1569	601	DFW7517HF	2020	774	DFW7517DF			
	1800	1179	452	DFW7518SF	1673	641	DFW7518HF	2155	825	DFW7518DF			
	2000	1326	508	DFW7520SF	1882	721	DFW7520HF	2423	928	DFW7520DF	3449	1321	DFW7520TF
	2200	1474	564	DFW7522SF	2092	801	DFW7522HF	2693	1031	DFW7522DF	3832	1468	DFW7522TF
	2400	1622	621	DFW7524SF	2301	881	DFW7524HF	2963	1135	DFW7524DF	4216	1615	DFW7524TF
	2600	1768	677	DFW7526SF	2510	961	DFW7526HF	3232	1238	DFW7526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
850	500				364	139	DFW8505HF	466	179	DFW8505DF			
	600	344	132	DFW8506SF	485	186	DFW8506HF	622	238	DFW8506DF	885	339	DFW8506TF
	700	431	165	DFW8507SF	606	232	DFW8507HF	778	298	DFW8507DF	1105	423	DFW8507TF
	800	517	198	DFW8508SF	727	278	DFW8508HF	933	357	DFW8508DF	1326	508	DFW8508TF
	900	603	231	DFW8509SF	848	325	DFW8509HF	1088	417	DFW8509DF	1548	593	DFW8509TF
	1000	689	264	DFW8510SF	970	372	DFW8510HF	1244	477	DFW8510DF	1768	677	DFW8510TF
	1100	775	297	DFW8511SF	1091	418	DFW8511HF	1399	536	DFW8511DF	1990	762	DFW8511TF
	1200	862	330	DFW8512SF	1212	464	DFW8512HF	1555	595	DFW8512DF	2211	847	DFW8512TF
	1300	948	363	DFW8513SF	1333	511	DFW8513HF	1711	655	DFW8513DF	2431	931	DFW8513TF
	1400	1034	396	DFW8514SF	1454	557	DFW8514HF	1865	714	DFW8514DF	2653	1016	DFW8514TF
	1500	1120	429	DFW8515SF	1576	604	DFW8515HF	2021	774	DFW8515DF			
	1600	1206	462	DFW8516SF	1697	650	DFW8516HF	2177	834	DFW8516DF	3095	1186	DFW8516TF
	1700	1292	495	DFW8517SF	1818	696	DFW8517HF	2333	893	DFW8517DF			
	1800	1379	528	DFW8518SF	1939	743	DFW8518HF	2488	953	DFW8518DF	3537	1355	DFW8518TF
	2000	1550	594	DFW8520SF	2182	836	DFW8520HF	2799	1072	DFW8520DF	3979	1524	DFW8520TF
	2200	1723	660	DFW8522SF	2424	929	DFW8522HF	3110	1191	DFW8522DF	4422	1693	DFW8522TF
	2400	1896	726	DFW8524SF	2666	1021	DFW8524HF	3420	1310	DFW8524DF			
	2600	2067	792	DFW8526SF	2909	1114	DFW8526HF	3732	1429	DFW8526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
950	600	390	149	DFW9506SF	548	210	DFW9506HF	699	268	DFW9506DF	992	380	DFW9506TF
	700	488	187	DFW9507SF	685	262	DFW9507HF	874	335	DFW9507DF	1241	475	DFW9507TF
	800	586	224	DFW9508SF	821	315	DFW9508HF	1048	402	DFW9508DF	1489	570	DFW9508TF
	900	683	261	DFW9509SF	959	367	DFW9509HF	1223	468	DFW9509DF	1737	665	DFW9509TF
	1000	781	299	DFW9510SF	1096	420	DFW9510HF	1397	535	DFW9510DF	1985	760	DFW9510TF
	1100	878	336	DFW9511SF	1233	472	DFW9511HF	1573	602	DFW9511DF	2233	855	DFW9511TF
	1200	975	374	DFW9512SF	1370	525	DFW9512HF	1747	669	DFW9512DF	2481	950	DFW9512TF
	1300	1073	411	DFW9513SF	1507	577	DFW9513HF	1922	736	DFW9513DF	2730	1045	DFW9513TF
	1400	1170	448	DFW9514SF	1644	630	DFW9514HF	2097	803	DFW9514DF	2978	1141	DFW9514TF
	1500	1268	486	DFW9515SF	1781	682	DFW9515HF	2271	870	DFW9515DF			
	1600	1365	523	DFW9516SF	1918	735	DFW9516HF	2446	937	DFW9516DF	3474	1330	DFW9516TF
	1700	1463	560	DFW9517SF				2621	1004	DFW9517DF			
	1800	1561	598	DFW9518SF	2191	839	DFW9518HF	2795	1071	DFW9518DF	3970	1521	DFW9518TF
	2000	1756	673	DFW9520SF	2465	944	DFW9520HF	3144	1204	DFW9520DF			
	2200	1951	747	DFW9522SF				3494	1338	DFW9522DF			
	2400	2146	822	DFW9524SF				3844	1472	DFW9524DF			
	2600	2341	896	DFW9526SF				4193	1606	DFW9526DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Flat Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1150	600	469	180	DFW1106SF	665	255	DFW1106HF	834	319	DFW1106DF	1180	452	DFW1106TF
	700	587	225	DFW1107SF	831	318	DFW1107HF	1043	399	DFW1107DF	1476	565	DFW1107TF
	800	704	270	DFW1108SF	998	382	DFW1108HF	1251	479	DFW1108DF	1771	678	DFW1108TF
	900	821	315	DFW1109SF	1164	446	DFW1109HF	1460	559	DFW1109DF	2066	791	DFW1109TF
	1000	938	359	DFW1110SF	1330	509	DFW1110HF	1668	639	DFW1110DF	2361	904	DFW1110TF
	1100	1056	404	DFW1111SF				1877	719	DFW1111DF	2656	1017	DFW1111TF
	1200	1173	449	DFW1112SF				2085	799	DFW1112DF	2951	1130	DFW1112TF
	1300	1290	494	DFW1113SF									
	1400	1408	539	DFW1114SF				2503	959	DFW1114DF			
	1600	1642	629	DFW1116SF				2919	1118	DFW1116DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*