

Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
600	600	183	55	DSW6006SF	272	82	DSW6006HF	350	106	DSW6006DF			
	700	230	69	DSW6007SF	341	103	DSW6007HF	438	132	DSW6007DF	622	188	DSW6007TF
	800	275	83	DSW6008SF	409	124	DSW6008HF	525	159	DSW6008DF	747	226	DSW6008TF
	900	321	97	DSW6009SF	477	144	DSW6009HF	612	185	DSW6009DF	871	263	DSW6009TF
	1000	367	111	DSW6010SF	546	165	DSW6010HF	700	211	DSW6010DF			
	1100	413	125	DSW6011SF	613	185	DSW6011HF	788	238	DSW6011DF	1120	338	DSW6011TF
	1200	458	138	DSW6012SF	682	206	DSW6012HF	875	264	DSW6012DF	1244	376	DSW6012TF
	1300	505	152	DSW6013SF	750	227	DSW6013HF	962	291	DSW6013DF	1369	413	DSW6013TF
	1400	550	166	DSW6014SF	818	247	DSW6014HF	1050	317	DSW6014DF	1493	451	DSW6014TF
	1500	596	180	DSW6015SF									
	1600	642	194	DSW6016SF	954	288	DSW6016HF	1225	370	DSW6016DF	1742	526	DSW6016TF
	1800	733	221	DSW6018SF	1091	330	DSW6018HF	1400	423	DSW6018DF	1991	601	DSW6018TF
	2000	825	249	DSW6020SF	1227	371	DSW6020HF	1574	475	DSW6020DF	2239	676	DSW6020TF
	2200	917	277	DSW6022SF				1750	528	DSW6022DF	2488	752	DSW6022TF
	2400	1008	305	DSW6024SF				1925	581	DSW6024DF			
	2600	1100	332	DSW6026SF				2100	634	DSW6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm



Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
700	600	241	73	DSW7006SF	348	105	DSW7006HF	449	135	DSW7006DF			
	700	302	91	DSW7007SF	435	131	DSW7007HF	561	169	DSW7007DF	797	241	DSW7007TF
	800	361	109	DSW7008SF	522	158	DSW7008HF	672	203	DSW7008DF	957	289	DSW7008TF
	900	422	127	DSW7009SF	609	184	DSW7009HF	784	237	DSW7009DF	1116	337	DSW7009TF
	1000	482	146	DSW7010SF	696	210	DSW7010HF	896	271	DSW7010DF	1275	385	DSW7010TF
	1100	542	164	DSW7011SF	782	236	DSW7011HF	1008	305	DSW7011DF	1435	433	DSW7011TF
	1200	603	182	DSW7012SF	870	263	DSW7012HF	1121	338	DSW7012DF	1594	481	DSW7012TF
	1300	663	200	DSW7013SF	957	289	DSW7013HF	1233	372	DSW7013DF	1753	529	DSW7013TF
	1400	723	218	DSW7014SF	1043	315	DSW7014HF	1345	406	DSW7014DF	1913	578	DSW7014TF
	1500	783	237	DSW7015SF	1130	341	DSW7015HF	1457	440	DSW7015DF			
	1600	844	255	DSW7016SF	1218	368	DSW7016HF	1569	474	DSW7016DF			
	1700	904	273	DSW7017SF	1305	394	DSW7017HF	1681	508	DSW7017DF			
	1800	964	291	DSW7018SF	1391	420	DSW7018HF	1792	541	DSW7018DF	2551	770	DSW7018TF
	2000	1085	328	DSW7020SF	1566	473	DSW7020HF	2017	609	DSW7020DF	2869	867	DSW7020TF
	2200	1205	364	DSW7022SF	1739	525	DSW7022HF	2241	677	DSW7022DF	3188	963	DSW7022TF
	2400	1325	400	DSW7024SF	1913	578	DSW7024HF	2465	745	DSW7024DF	3507	1059	DSW7024TF
	2600	1446	437	DSW7026SF	2087	630	DSW7026HF	2690	812	DSW7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
800	600	295	89	DSW8006SF	418	126	DSW8006HF	538	163	DSW8006DF			
	700	368	111	DSW8007SF	523	158	DSW8007HF	674	203	DSW8007DF	959	289	DSW8007TF
	800	442	134	DSW8008SF	627	189	DSW8008HF	808	244	DSW8008DF	1150	347	DSW8008TF
	900	516	156	DSW8009SF	732	221	DSW8009HF	943	285	DSW8009DF	1341	405	DSW8009TF
	1000	589	178	DSW8010SF	837	253	DSW8010HF	1077	325	DSW8010DF	1533	463	DSW8010TF
	1100	663	200	DSW8011SF	942	284	DSW8011HF	1212	366	DSW8011DF	1725	521	DSW8011TF
	1200	737	223	DSW8012SF	1046	316	DSW8012HF	1347	407	DSW8012DF	1916	579	DSW8012TF
	1300	811	245	DSW8013SF	1151	348	DSW8013HF	1481	447	DSW8013DF	2108	636	DSW8013TF
	1400	885	267	DSW8014SF	1255	379	DSW8014HF	1616	488	DSW8014DF	2300	695	DSW8014TF
	1500	958	289	DSW8015SF	1360	411	DSW8015HF	1751	529	DSW8015DF	2491	752	DSW8015TF
	1600	1032	312	DSW8016SF	1464	442	DSW8016HF	1885	569	DSW8016DF	2682	810	DSW8016TF
	1700	1105	334	DSW8017SF	1569	474	DSW8017HF	2020	610	DSW8017DF			
	1800	1179	356	DSW8018SF	1673	505	DSW8018HF	2155	651	DSW8018DF			
	2000	1326	400	DSW8020SF	1882	568	DSW8020HF	2423	732	DSW8020DF	3449	1042	DSW8020TF
	2200	1474	445	DSW8022SF	2092	632	DSW8022HF	2693	813	DSW8022DF	3832	1157	DSW8022TF
	2400	1622	490	DSW8024SF	2301	695	DSW8024HF	2963	895	DSW8024DF	4216	1273	DSW8024TF
	2600	1768	534	DSW8026SF	2510	758	DSW8026HF	3232	976	DSW8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
900	500				364	110	DSW9005HF	466	141	DSW9005DF			
	600	344	104	DSW9006SF	485	146	DSW9006HF	622	188	DSW9006DF	885	267	DSW9006TF
	700	431	130	DSW9007SF	606	183	DSW9007HF	778	235	DSW9007DF	1105	334	DSW9007TF
	800	517	156	DSW9008SF	727	220	DSW9008HF	933	282	DSW9008DF	1326	400	DSW9008TF
	900	603	182	DSW9009SF	848	256	DSW9009HF	1088	329	DSW9009DF	1548	467	DSW9009TF
	1000	689	208	DSW9010SF	970	293	DSW9010HF	1244	376	DSW9010DF	1768	534	DSW9010TF
	1100	775	234	DSW9011SF	1091	330	DSW9011HF	1399	423	DSW9011DF	1990	601	DSW9011TF
	1200	862	260	DSW9012SF	1212	366	DSW9012HF	1555	470	DSW9012DF	2211	668	DSW9012TF
	1300	948	286	DSW9013SF	1333	403	DSW9013HF	1711	517	DSW9013DF	2431	734	DSW9013TF
	1400	1034	312	DSW9014SF	1454	439	DSW9014HF	1865	563	DSW9014DF	2653	801	DSW9014TF
	1500	1120	338	DSW9015SF	1576	476	DSW9015HF	2021	610	DSW9015DF			
	1600	1206	364	DSW9016SF	1697	513	DSW9016HF	2177	657	DSW9016DF	3095	935	DSW9016TF
	1700	1292	390	DSW9017SF	1818	549	DSW9017HF	2333	704	DSW9017DF			
	1800	1379	416	DSW9018SF	1939	586	DSW9018HF	2488	751	DSW9018DF	3537	1068	DSW9018TF
	2000	1550	468	DSW9020SF	2182	659	DSW9020HF	2799	845	DSW9020DF	3979	1202	DSW9020TF
	2200	1723	520	DSW9022SF	2424	732	DSW9022HF	3110	939	DSW9022DF	4422	1335	DSW9022TF
	2400	1896	573	DSW9024SF	2666	805	DSW9024HF	3420	1033	DSW9024DF			
	2600	2067	624	DSW9026SF	2909	879	DSW9026HF	3732	1127	DSW9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1000	600	390	118	DSW1006SF	548	166	DSW1006HF	699	211	DSW1006DF	992	300	DSW1006TF
	700	488	147	DSW1007SF	685	207	DSW1007HF	874	264	DSW1007DF	1241	375	DSW1007TF
	800	586	177	DSW1008SF	821	248	DSW1008HF	1048	317	DSW1008DF	1489	450	DSW1008TF
	900	683	206	DSW1009SF	959	289	DSW1009HF	1223	369	DSW1009DF	1737	525	DSW1009TF
	1000	781	236	DSW1010SF	1096	331	DSW1010HF	1397	422	DSW1010DF	1985	599	DSW1010TF
	1100	878	265	DSW1011SF	1233	372	DSW1011HF	1573	475	DSW1011DF	2233	674	DSW1011TF
	1200	975	295	DSW1012SF	1370	414	DSW1012HF	1747	528	DSW1012DF	2481	749	DSW1012TF
	1300	1073	324	DSW1013SF	1507	455	DSW1013HF	1922	580	DSW1013DF	2730	824	DSW1013TF
	1400	1170	353	DSW1014SF	1644	496	DSW1014HF	2097	633	DSW1014DF	2978	899	DSW1014TF
	1500	1268	383	DSW1015SF	1781	538	DSW1015HF	2271	686	DSW1015DF			
	1600	1365	412	DSW1016SF	1918	579	DSW1016HF	2446	739	DSW1016DF	3474	1049	DSW1016TF
	1700	1463	442	DSW1017SF				2621	792	DSW1017DF			
	1800	1561	471	DSW1018SF	2191	662	DSW1018HF	2795	844	DSW1018DF	3970	1199	DSW1018TF
	2000	1756	530	DSW1020SF	2465	745	DSW1020HF	3144	950	DSW1020DF			
	2200	1951	589	DSW1022SF				3494	1055	DSW1022DF			
	2400	2146	648	DSW1024SF				3844	1161	DSW1024DF			
	2600	2341	707	DSW1026SF				4193	1266	DSW1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1200	600	469	142	DSW1206SF	665	201	DSW1206HF	834	252	DSW1206DF	1180	356	DSW1206TF
	700	587	177	DSW1207SF	831	251	DSW1207HF	1043	315	DSW1207DF	1476	446	DSW1207TF
	800	704	213	DSW1208SF	998	301	DSW1208HF	1251	378	DSW1208DF	1771	535	DSW1208TF
	900	821	248	DSW1209SF	1164	352	DSW1209HF	1460	441	DSW1209DF	2066	624	DSW1209TF
	1000	938	283	DSW1210SF	1330	402	DSW1210HF	1668	504	DSW1210DF	2361	713	DSW1210TF
	1100	1056	319	DSW1211SF				1877	567	DSW1211DF	2656	802	DSW1211TF
	1200	1173	354	DSW1212SF				2085	630	DSW1212DF	2951	891	DSW1212TF
	1300	1290	390	DSW1213SF									
	1400	1408	425	DSW1214SF				2503	756	DSW1214DF			
	1600	1642	496	DSW1216SF				2919	882	DSW1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*