

Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
600	600	183	55	DSF6006SF	272	82	DSF6006HF	350	106	DSF6006DF			
	700	230	69	DSF6007SF	341	103	DSF6007HF	438	132	DSF6007DF	622	188	DSF6007TF
	800	275	83	DSF6008SF	409	124	DSF6008HF	525	159	DSF6008DF	747	226	DSF6008TF
	900	321	97	DSF6009SF	477	144	DSF6009HF	612	185	DSF6009DF	871	263	DSF6009TF
	1000	367	111	DSF6010SF	546	165	DSF6010HF	700	211	DSF6010DF			
	1100	413	125	DSF6011SF	613	185	DSF6011HF	788	238	DSF6011DF	1120	338	DSF6011TF
	1200	458	138	DSF6012SF	682	206	DSF6012HF	875	264	DSF6012DF	1244	376	DSF6012TF
	1300	505	152	DSF6013SF	750	227	DSF6013HF	962	291	DSF6013DF	1369	413	DSF6013TF
	1400	550	166	DSF6014SF	818	247	DSF6014HF	1050	317	DSF6014DF	1493	451	DSF6014TF
	1500	596	180	DSF6015SF									
	1600	642	194	DSF6016SF	954	288	DSF6016HF	1225	370	DSF6016DF	1742	526	DSF6016TF
	1800	733	221	DSF6018SF	1091	330	DSF6018HF	1400	423	DSF6018DF	1991	601	DSF6018TF
	2000	825	249	DSF6020SF	1227	371	DSF6020HF	1574	475	DSF6020DF	2239	676	DSF6020TF
	2200	917	277	DSF6022SF				1750	528	DSF6022DF	2488	752	DSF6022TF
	2400	1008	305	DSF6024SF				1925	581	DSF6024DF			
	2600	1100	332	DSF6026SF				2100	634	DSF6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
700	600	241	73	DSF7006SF	348	105	DSF7006HF	449	135	DSF7006DF			
	700	302	91	DSF7007SF	435	131	DSF7007HF	561	169	DSF7007DF	797	241	DSF7007TF
	800	361	109	DSF7008SF	522	158	DSF7008HF	672	203	DSF7008DF	957	289	DSF7008TF
	900	422	127	DSF7009SF	609	184	DSF7009HF	784	237	DSF7009DF	1116	337	DSF7009TF
	1000	482	146	DSF7010SF	696	210	DSF7010HF	896	271	DSF7010DF	1275	385	DSF7010TF
	1100	542	164	DSF7011SF	782	236	DSF7011HF	1008	305	DSF7011DF	1435	433	DSF7011TF
	1200	603	182	DSF7012SF	870	263	DSF7012HF	1121	338	DSF7012DF	1594	481	DSF7012TF
	1300	663	200	DSF7013SF	957	289	DSF7013HF	1233	372	DSF7013DF	1753	529	DSF7013TF
	1400	723	218	DSF7014SF	1043	315	DSF7014HF	1345	406	DSF7014DF	1913	578	DSF7014TF
	1500	783	237	DSF7015SF	1130	341	DSF7015HF	1457	440	DSF7015DF			
	1600	844	255	DSF7016SF	1218	368	DSF7016HF	1569	474	DSF7016DF			
	1700	904	273	DSF7017SF	1305	394	DSF7017HF	1681	508	DSF7017DF			
	1800	964	291	DSF7018SF	1391	420	DSF7018HF	1792	541	DSF7018DF	2551	770	DSF7018TF
	2000	1085	328	DSF7020SF	1566	473	DSF7020HF	2017	609	DSF7020DF	2869	867	DSF7020TF
	2200	1205	364	DSF7022SF	1739	525	DSF7022HF	2241	677	DSF7022DF	3188	963	DSF7022TF
	2400	1325	400	DSF7024SF	1913	578	DSF7024HF	2465	745	DSF7024DF	3507	1059	DSF7024TF
	2600	1446	437	DSF7026SF	2087	630	DSF7026HF	2690	812	DSF7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
800	600	295	89	DSF8006SF	418	126	DSF8006HF	538	163	DSF8006DF			
	700	368	111	DSF8007SF	523	158	DSF8007HF	674	203	DSF8007DF	959	289	DSF8007TF
	800	442	134	DSF8008SF	627	189	DSF8008HF	808	244	DSF8008DF	1150	347	DSF8008TF
	900	516	156	DSF8009SF	732	221	DSF8009HF	943	285	DSF8009DF	1341	405	DSF8009TF
	1000	589	178	DSF8010SF	837	253	DSF8010HF	1077	325	DSF8010DF	1533	463	DSF8010TF
	1100	663	200	DSF8011SF	942	284	DSF8011HF	1212	366	DSF8011DF	1725	521	DSF8011TF
	1200	737	223	DSF8012SF	1046	316	DSF8012HF	1347	407	DSF8012DF	1916	579	DSF8012TF
	1300	811	245	DSF8013SF	1151	348	DSF8013HF	1481	447	DSF8013DF	2108	636	DSF8013TF
	1400	885	267	DSF8014SF	1255	379	DSF8014HF	1616	488	DSF8014DF	2300	695	DSF8014TF
	1500	958	289	DSF8015SF	1360	411	DSF8015HF	1751	529	DSF8015DF	2491	752	DSF8015TF
	1600	1032	312	DSF8016SF	1464	442	DSF8016HF	1885	569	DSF8016DF	2682	810	DSF8016TF
	1700	1105	334	DSF8017SF	1569	474	DSF8017HF	2020	610	DSF8017DF			
	1800	1179	356	DSF8018SF	1673	505	DSF8018HF	2155	651	DSF8018DF			
	2000	1326	400	DSF8020SF	1882	568	DSF8020HF	2423	732	DSF8020DF	3449	1042	DSF8020TF
	2200	1474	445	DSF8022SF	2092	632	DSF8022HF	2693	813	DSF8022DF	3832	1157	DSF8022TF
	2400	1622	490	DSF8024SF	2301	695	DSF8024HF	2963	895	DSF8024DF	4216	1273	DSF8024TF
	2600	1768	534	DSF8026SF	2510	758	DSF8026HF	3232	976	DSF8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T20)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
900	500				364	110	DSF9005HF	466	141	DSF9005DF			
	600	344	104	DSF9006SF	485	146	DSF9006HF	622	188	DSF9006DF	885	267	DSF9006TF
	700	431	130	DSF9007SF	606	183	DSF9007HF	778	235	DSF9007DF	1105	334	DSF9007TF
	800	517	156	DSF9008SF	727	220	DSF9008HF	933	282	DSF9008DF	1326	400	DSF9008TF
	900	603	182	DSF9009SF	848	256	DSF9009HF	1088	329	DSF9009DF	1548	467	DSF9009TF
	1000	689	208	DSF9010SF	970	293	DSF9010HF	1244	376	DSF9010DF	1768	534	DSF9010TF
	1100	775	234	DSF9011SF	1091	330	DSF9011HF	1399	423	DSF9011DF	1990	601	DSF9011TF
	1200	862	260	DSF9012SF	1212	366	DSF9012HF	1555	470	DSF9012DF	2211	668	DSF9012TF
	1300	948	286	DSF9013SF	1333	403	DSF9013HF	1711	517	DSF9013DF	2431	734	DSF9013TF
	1400	1034	312	DSF9014SF	1454	439	DSF9014HF	1865	563	DSF9014DF	2653	801	DSF9014TF
	1500	1120	338	DSF9015SF	1576	476	DSF9015HF	2021	610	DSF9015DF			
	1600	1206	364	DSF9016SF	1697	513	DSF9016HF	2177	657	DSF9016DF	3095	935	DSF9016TF
	1700	1292	390	DSF9017SF	1818	549	DSF9017HF	2333	704	DSF9017DF			
	1800	1379	416	DSF9018SF	1939	586	DSF9018HF	2488	751	DSF9018DF	3537	1068	DSF9018TF
	2000	1550	468	DSF9020SF	2182	659	DSF9020HF	2799	845	DSF9020DF	3979	1202	DSF9020TF
	2200	1723	520	DSF9022SF	2424	732	DSF9022HF	3110	939	DSF9022DF	4422	1335	DSF9022TF
	2400	1896	573	DSF9024SF	2666	805	DSF9024HF	3420	1033	DSF9024DF			
	2600	2067	624	DSF9026SF	2909	879	DSF9026HF	3732	1127	DSF9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1000	600	390	118	DSF1006SF	548	166	DSF1006HF	699	211	DSF1006DF	992	300	DSF1006TF
	700	488	147	DSF1007SF	685	207	DSF1007HF	874	264	DSF1007DF	1241	375	DSF1007TF
	800	586	177	DSF1008SF	821	248	DSF1008HF	1048	317	DSF1008DF	1489	450	DSF1008TF
	900	683	206	DSF1009SF	959	289	DSF1009HF	1223	369	DSF1009DF	1737	525	DSF1009TF
	1000	781	236	DSF1010SF	1096	331	DSF1010HF	1397	422	DSF1010DF	1985	599	DSF1010TF
	1100	878	265	DSF1011SF	1233	372	DSF1011HF	1573	475	DSF1011DF	2233	674	DSF1011TF
	1200	975	295	DSF1012SF	1370	414	DSF1012HF	1747	528	DSF1012DF	2481	749	DSF1012TF
	1300	1073	324	DSF1013SF	1507	455	DSF1013HF	1922	580	DSF1013DF	2730	824	DSF1013TF
	1400	1170	353	DSF1014SF	1644	496	DSF1014HF	2097	633	DSF1014DF	2978	899	DSF1014TF
	1500	1268	383	DSF1015SF	1781	538	DSF1015HF	2271	686	DSF1015DF			
	1600	1365	412	DSF1016SF	1918	579	DSF1016HF	2446	739	DSF1016DF	3474	1049	DSF1016TF
	1700	1463	442	DSF1017SF				2621	792	DSF1017DF			
	1800	1561	471	DSF1018SF	2191	662	DSF1018HF	2795	844	DSF1018DF	3970	1199	DSF1018TF
	2000	1756	530	DSF1020SF	2465	745	DSF1020HF	3144	950	DSF1020DF			
	2200	1951	589	DSF1022SF				3494	1055	DSF1022DF			
	2400	2146	648	DSF1024SF				3844	1161	DSF1024DF			
	2600	2341	707	DSF1026SF				4193	1266	DSF1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T20)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1200	600	469	142	DSF1206SF	665	201	DSF1206HF	834	252	DSF1206DF	1180	356	DSF1206TF
	700	587	177	DSF1207SF	831	251	DSF1207HF	1043	315	DSF1207DF	1476	446	DSF1207TF
	800	704	213	DSF1208SF	998	301	DSF1208HF	1251	378	DSF1208DF	1771	535	DSF1208TF
	900	821	248	DSF1209SF	1164	352	DSF1209HF	1460	441	DSF1209DF	2066	624	DSF1209TF
	1000	938	283	DSF1210SF	1330	402	DSF1210HF	1668	504	DSF1210DF	2361	713	DSF1210TF
	1100	1056	319	DSF1211SF				1877	567	DSF1211DF	2656	802	DSF1211TF
	1200	1173	354	DSF1212SF				2085	630	DSF1212DF	2951	891	DSF1212TF
	1300	1290	390	DSF1213SF									
	1400	1408	425	DSF1214SF				2503	756	DSF1214DF			
	1600	1642	496	DSF1216SF				2919	882	DSF1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*