



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
600	600	183	70	DSW6006SF	272	104	DSW6006HF	350	134	DSW6006DF			
	700	230	88	DSW6007SF	341	131	DSW6007HF	438	168	DSW6007DF	622	238	DSW6007TF
	800	275	105	DSW6008SF	409	157	DSW6008HF	525	201	DSW6008DF	747	286	DSW6008TF
	900	321	123	DSW6009SF	477	183	DSW6009HF	612	235	DSW6009DF	871	334	DSW6009TF
	1000	367	140	DSW6010SF	546	209	DSW6010HF	700	268	DSW6010DF			
	1100	413	158	DSW6011SF	613	235	DSW6011HF	788	302	DSW6011DF	1120	429	DSW6011TF
	1200	458	176	DSW6012SF	682	261	DSW6012HF	875	335	DSW6012DF	1244	477	DSW6012TF
	1300	505	193	DSW6013SF	750	287	DSW6013HF	962	368	DSW6013DF	1369	524	DSW6013TF
	1400	550	211	DSW6014SF	818	313	DSW6014HF	1050	402	DSW6014DF	1493	572	DSW6014TF
	1500	596	228	DSW6015SF									
	1600	642	246	DSW6016SF	954	365	DSW6016HF	1225	469	DSW6016DF	1742	667	DSW6016TF
	1800	733	281	DSW6018SF	1091	418	DSW6018HF	1400	536	DSW6018DF	1991	763	DSW6018TF
	2000	825	316	DSW6020SF	1227	470	DSW6020HF	1574	603	DSW6020DF	2239	858	DSW6020TF
	2200	917	351	DSW6022SF				1750	670	DSW6022DF	2488	953	DSW6022TF
	2400	1008	386	DSW6024SF				1925	737	DSW6024DF			
	2600	1100	421	DSW6026SF				2100	804	DSW6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
700	600	241	92	DSW7006SF	348	133	DSW7006HF	449	172	DSW7006DF			
	700	302	116	DSW7007SF	435	167	DSW7007HF	561	215	DSW7007DF	797	305	DSW7007TF
	800	361	138	DSW7008SF	522	200	DSW7008HF	672	257	DSW7008DF	957	366	DSW7008TF
	900	422	162	DSW7009SF	609	233	DSW7009HF	784	300	DSW7009DF	1116	427	DSW7009TF
	1000	482	185	DSW7010SF	696	267	DSW7010HF	896	343	DSW7010DF	1275	488	DSW7010TF
	1100	542	208	DSW7011SF	782	300	DSW7011HF	1008	386	DSW7011DF	1435	549	DSW7011TF
	1200	603	231	DSW7012SF	870	333	DSW7012HF	1121	429	DSW7012DF	1594	610	DSW7012TF
	1300	663	254	DSW7013SF	957	366	DSW7013HF	1233	472	DSW7013DF	1753	672	DSW7013TF
	1400	723	277	DSW7014SF	1043	399	DSW7014HF	1345	515	DSW7014DF	1913	733	DSW7014TF
	1500	783	300	DSW7015SF	1130	433	DSW7015HF	1457	558	DSW7015DF			
	1600	844	323	DSW7016SF	1218	466	DSW7016HF	1569	601	DSW7016DF			
	1700	904	346	DSW7017SF	1305	500	DSW7017HF	1681	644	DSW7017DF			
	1800	964	369	DSW7018SF	1391	533	DSW7018HF	1792	687	DSW7018DF	2551	977	DSW7018TF
	2000	1085	416	DSW7020SF	1566	600	DSW7020HF	2017	772	DSW7020DF	2869	1099	DSW7020TF
	2200	1205	462	DSW7022SF	1739	666	DSW7022HF	2241	858	DSW7022DF	3188	1221	DSW7022TF
	2400	1325	508	DSW7024SF	1913	733	DSW7024HF	2465	944	DSW7024DF	3507	1343	DSW7024TF
	2600	1446	554	DSW7026SF	2087	799	DSW7026HF	2690	1030	DSW7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
800	600	295	113	DSW8006SF	418	160	DSW8006HF	538	206	DSW8006DF			
	700	368	141	DSW8007SF	523	200	DSW8007HF	674	258	DSW8007DF	959	367	DSW8007TF
	800	442	169	DSW8008SF	627	240	DSW8008HF	808	310	DSW8008DF	1150	440	DSW8008TF
	900	516	198	DSW8009SF	732	281	DSW8009HF	943	361	DSW8009DF	1341	514	DSW8009TF
	1000	589	226	DSW8010SF	837	320	DSW8010HF	1077	412	DSW8010DF	1533	587	DSW8010TF
	1100	663	254	DSW8011SF	942	361	DSW8011HF	1212	464	DSW8011DF	1725	661	DSW8011TF
	1200	737	282	DSW8012SF	1046	401	DSW8012HF	1347	516	DSW8012DF	1916	734	DSW8012TF
	1300	811	311	DSW8013SF	1151	441	DSW8013HF	1481	567	DSW8013DF	2108	807	DSW8013TF
	1400	885	339	DSW8014SF	1255	481	DSW8014HF	1616	619	DSW8014DF	2300	881	DSW8014TF
	1500	958	367	DSW8015SF	1360	521	DSW8015HF	1751	670	DSW8015DF	2491	954	DSW8015TF
	1600	1032	395	DSW8016SF	1464	561	DSW8016HF	1885	722	DSW8016DF	2682	1027	DSW8016TF
	1700	1105	423	DSW8017SF	1569	601	DSW8017HF	2020	774	DSW8017DF			
	1800	1179	452	DSW8018SF	1673	641	DSW8018HF	2155	825	DSW8018DF			
	2000	1326	508	DSW8020SF	1882	721	DSW8020HF	2423	928	DSW8020DF	3449	1321	DSW8020TF
	2200	1474	564	DSW8022SF	2092	801	DSW8022HF	2693	1031	DSW8022DF	3832	1468	DSW8022TF
	2400	1622	621	DSW8024SF	2301	881	DSW8024HF	2963	1135	DSW8024DF	4216	1615	DSW8024TF
	2600	1768	677	DSW8026SF	2510	961	DSW8026HF	3232	1238	DSW8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
900	500				364	139	DSW9005HF	466	179	DSW9005DF			
	600	344	132	DSW9006SF	485	186	DSW9006HF	622	238	DSW9006DF	885	339	DSW9006TF
	700	431	165	DSW9007SF	606	232	DSW9007HF	778	298	DSW9007DF	1105	423	DSW9007TF
	800	517	198	DSW9008SF	727	278	DSW9008HF	933	357	DSW9008DF	1326	508	DSW9008TF
	900	603	231	DSW9009SF	848	325	DSW9009HF	1088	417	DSW9009DF	1548	593	DSW9009TF
	1000	689	264	DSW9010SF	970	372	DSW9010HF	1244	477	DSW9010DF	1768	677	DSW9010TF
	1100	775	297	DSW9011SF	1091	418	DSW9011HF	1399	536	DSW9011DF	1990	762	DSW9011TF
	1200	862	330	DSW9012SF	1212	464	DSW9012HF	1555	595	DSW9012DF	2211	847	DSW9012TF
	1300	948	363	DSW9013SF	1333	511	DSW9013HF	1711	655	DSW9013DF	2431	931	DSW9013TF
	1400	1034	396	DSW9014SF	1454	557	DSW9014HF	1865	714	DSW9014DF	2653	1016	DSW9014TF
	1500	1120	429	DSW9015SF	1576	604	DSW9015HF	2021	774	DSW9015DF			
	1600	1206	462	DSW9016SF	1697	650	DSW9016HF	2177	834	DSW9016DF	3095	1186	DSW9016TF
	1700	1292	495	DSW9017SF	1818	696	DSW9017HF	2333	893	DSW9017DF			
	1800	1379	528	DSW9018SF	1939	743	DSW9018HF	2488	953	DSW9018DF	3537	1355	DSW9018TF
	2000	1550	594	DSW9020SF	2182	836	DSW9020HF	2799	1072	DSW9020DF	3979	1524	DSW9020TF
	2200	1723	660	DSW9022SF	2424	929	DSW9022HF	3110	1191	DSW9022DF	4422	1693	DSW9022TF
	2400	1896	726	DSW9024SF	2666	1021	DSW9024HF	3420	1310	DSW9024DF			
	2600	2067	792	DSW9026SF	2909	1114	DSW9026HF	3732	1429	DSW9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1000	600	390	149	DSW1006SF	548	210	DSW1006HF	699	268	DSW1006DF	992	380	DSW1006TF
	700	488	187	DSW1007SF	685	262	DSW1007HF	874	335	DSW1007DF	1241	475	DSW1007TF
	800	586	224	DSW1008SF	821	315	DSW1008HF	1048	402	DSW1008DF	1489	570	DSW1008TF
	900	683	261	DSW1009SF	959	367	DSW1009HF	1223	468	DSW1009DF	1737	665	DSW1009TF
	1000	781	299	DSW1010SF	1096	420	DSW1010HF	1397	535	DSW1010DF	1985	760	DSW1010TF
	1100	878	336	DSW1011SF	1233	472	DSW1011HF	1573	602	DSW1011DF	2233	855	DSW1011TF
	1200	975	374	DSW1012SF	1370	525	DSW1012HF	1747	669	DSW1012DF	2481	950	DSW1012TF
	1300	1073	411	DSW1013SF	1507	577	DSW1013HF	1922	736	DSW1013DF	2730	1045	DSW1013TF
	1400	1170	448	DSW1014SF	1644	630	DSW1014HF	2097	803	DSW1014DF	2978	1141	DSW1014TF
	1500	1268	486	DSW1015SF	1781	682	DSW1015HF	2271	870	DSW1015DF			
	1600	1365	523	DSW1016SF	1918	735	DSW1016HF	2446	937	DSW1016DF	3474	1330	DSW1016TF
	1700	1463	560	DSW1017SF				2621	1004	DSW1017DF			
	1800	1561	598	DSW1018SF	2191	839	DSW1018HF	2795	1071	DSW1018DF	3970	1521	DSW1018TF
	2000	1756	673	DSW1020SF	2465	944	DSW1020HF	3144	1204	DSW1020DF			
	2200	1951	747	DSW1022SF				3494	1338	DSW1022DF			
	2400	2146	822	DSW1024SF				3844	1472	DSW1024DF			
	2600	2341	896	DSW1026SF				4193	1606	DSW1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1200	600	469	180	DSW1206SF	665	255	DSW1206HF	834	319	DSW1206DF	1180	452	DSW1206TF
	700	587	225	DSW1207SF	831	318	DSW1207HF	1043	399	DSW1207DF	1476	565	DSW1207TF
	800	704	270	DSW1208SF	998	382	DSW1208HF	1251	479	DSW1208DF	1771	678	DSW1208TF
	900	821	315	DSW1209SF	1164	446	DSW1209HF	1460	559	DSW1209DF	2066	791	DSW1209TF
	1000	938	359	DSW1210SF	1330	509	DSW1210HF	1668	639	DSW1210DF	2361	904	DSW1210TF
	1100	1056	404	DSW1211SF				1877	719	DSW1211DF	2656	1017	DSW1211TF
	1200	1173	449	DSW1212SF				2085	799	DSW1212DF	2951	1130	DSW1212TF
	1300	1290	494	DSW1213SF									
	1400	1408	539	DSW1214SF				2503	959	DSW1214DF			
	1600	1642	629	DSW1216SF				2919	1118	DSW1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*