

Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
600	600	183	70	DSF6006SF	272	104	DSF6006HF	350	134	DSF6006DF			
	700	230	88	DSF6007SF	341	131	DSF6007HF	438	168	DSF6007DF	622	238	DSF6007TF
	800	275	105	DSF6008SF	409	157	DSF6008HF	525	201	DSF6008DF	747	286	DSF6008TF
	900	321	123	DSF6009SF	477	183	DSF6009HF	612	235	DSF6009DF	871	334	DSF6009TF
	1000	367	140	DSF6010SF	546	209	DSF6010HF	700	268	DSF6010DF			
	1100	413	158	DSF6011SF	613	235	DSF6011HF	788	302	DSF6011DF	1120	429	DSF6011TF
	1200	458	176	DSF6012SF	682	261	DSF6012HF	875	335	DSF6012DF	1244	477	DSF6012TF
	1300	505	193	DSF6013SF	750	287	DSF6013HF	962	368	DSF6013DF	1369	524	DSF6013TF
	1400	550	211	DSF6014SF	818	313	DSF6014HF	1050	402	DSF6014DF	1493	572	DSF6014TF
	1500	596	228	DSF6015SF									
	1600	642	246	DSF6016SF	954	365	DSF6016HF	1225	469	DSF6016DF	1742	667	DSF6016TF
	1800	733	281	DSF6018SF	1091	418	DSF6018HF	1400	536	DSF6018DF	1991	763	DSF6018TF
	2000	825	316	DSF6020SF	1227	470	DSF6020HF	1574	603	DSF6020DF	2239	858	DSF6020TF
	2200	917	351	DSF6022SF				1750	670	DSF6022DF	2488	953	DSF6022TF
	2400	1008	386	DSF6024SF				1925	737	DSF6024DF			
	2600	1100	421	DSF6026SF				2100	804	DSF6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm



Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
700	600	241	92	DSF7006SF	348	133	DSF7006HF	449	172	DSF7006DF			
	700	302	116	DSF7007SF	435	167	DSF7007HF	561	215	DSF7007DF	797	305	DSF7007TF
	800	361	138	DSF7008SF	522	200	DSF7008HF	672	257	DSF7008DF	957	366	DSF7008TF
	900	422	162	DSF7009SF	609	233	DSF7009HF	784	300	DSF7009DF	1116	427	DSF7009TF
	1000	482	185	DSF7010SF	696	267	DSF7010HF	896	343	DSF7010DF	1275	488	DSF7010TF
	1100	542	208	DSF7011SF	782	300	DSF7011HF	1008	386	DSF7011DF	1435	549	DSF7011TF
	1200	603	231	DSF7012SF	870	333	DSF7012HF	1121	429	DSF7012DF	1594	610	DSF7012TF
	1300	663	254	DSF7013SF	957	366	DSF7013HF	1233	472	DSF7013DF	1753	672	DSF7013TF
	1400	723	277	DSF7014SF	1043	399	DSF7014HF	1345	515	DSF7014DF	1913	733	DSF7014TF
	1500	783	300	DSF7015SF	1130	433	DSF7015HF	1457	558	DSF7015DF			
	1600	844	323	DSF7016SF	1218	466	DSF7016HF	1569	601	DSF7016DF			
	1700	904	346	DSF7017SF	1305	500	DSF7017HF	1681	644	DSF7017DF			
	1800	964	369	DSF7018SF	1391	533	DSF7018HF	1792	687	DSF7018DF	2551	977	DSF7018TF
	2000	1085	416	DSF7020SF	1566	600	DSF7020HF	2017	772	DSF7020DF	2869	1099	DSF7020TF
	2200	1205	462	DSF7022SF	1739	666	DSF7022HF	2241	858	DSF7022DF	3188	1221	DSF7022TF
	2400	1325	508	DSF7024SF	1913	733	DSF7024HF	2465	944	DSF7024DF	3507	1343	DSF7024TF
	2600	1446	554	DSF7026SF	2087	799	DSF7026HF	2690	1030	DSF7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
800	600	295	113	DSF8006SF	418	160	DSF8006HF	538	206	DSF8006DF			
	700	368	141	DSF8007SF	523	200	DSF8007HF	674	258	DSF8007DF	959	367	DSF8007TF
	800	442	169	DSF8008SF	627	240	DSF8008HF	808	310	DSF8008DF	1150	440	DSF8008TF
	900	516	198	DSF8009SF	732	281	DSF8009HF	943	361	DSF8009DF	1341	514	DSF8009TF
	1000	589	226	DSF8010SF	837	320	DSF8010HF	1077	412	DSF8010DF	1533	587	DSF8010TF
	1100	663	254	DSF8011SF	942	361	DSF8011HF	1212	464	DSF8011DF	1725	661	DSF8011TF
	1200	737	282	DSF8012SF	1046	401	DSF8012HF	1347	516	DSF8012DF	1916	734	DSF8012TF
	1300	811	311	DSF8013SF	1151	441	DSF8013HF	1481	567	DSF8013DF	2108	807	DSF8013TF
	1400	885	339	DSF8014SF	1255	481	DSF8014HF	1616	619	DSF8014DF	2300	881	DSF8014TF
	1500	958	367	DSF8015SF	1360	521	DSF8015HF	1751	670	DSF8015DF	2491	954	DSF8015TF
	1600	1032	395	DSF8016SF	1464	561	DSF8016HF	1885	722	DSF8016DF	2682	1027	DSF8016TF
	1700	1105	423	DSF8017SF	1569	601	DSF8017HF	2020	774	DSF8017DF			
	1800	1179	452	DSF8018SF	1673	641	DSF8018HF	2155	825	DSF8018DF			
	2000	1326	508	DSF8020SF	1882	721	DSF8020HF	2423	928	DSF8020DF	3449	1321	DSF8020TF
	2200	1474	564	DSF8022SF	2092	801	DSF8022HF	2693	1031	DSF8022DF	3832	1468	DSF8022TF
	2400	1622	621	DSF8024SF	2301	881	DSF8024HF	2963	1135	DSF8024DF	4216	1615	DSF8024TF
	2600	1768	677	DSF8026SF	2510	961	DSF8026HF	3232	1238	DSF8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T24)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
900	500				364	139	DSF9005HF	466	179	DSF9005DF			
	600	344	132	DSF9006SF	485	186	DSF9006HF	622	238	DSF9006DF	885	339	DSF9006TF
	700	431	165	DSF9007SF	606	232	DSF9007HF	778	298	DSF9007DF	1105	423	DSF9007TF
	800	517	198	DSF9008SF	727	278	DSF9008HF	933	357	DSF9008DF	1326	508	DSF9008TF
	900	603	231	DSF9009SF	848	325	DSF9009HF	1088	417	DSF9009DF	1548	593	DSF9009TF
	1000	689	264	DSF9010SF	970	372	DSF9010HF	1244	477	DSF9010DF	1768	677	DSF9010TF
	1100	775	297	DSF9011SF	1091	418	DSF9011HF	1399	536	DSF9011DF	1990	762	DSF9011TF
	1200	862	330	DSF9012SF	1212	464	DSF9012HF	1555	595	DSF9012DF	2211	847	DSF9012TF
	1300	948	363	DSF9013SF	1333	511	DSF9013HF	1711	655	DSF9013DF	2431	931	DSF9013TF
	1400	1034	396	DSF9014SF	1454	557	DSF9014HF	1865	714	DSF9014DF	2653	1016	DSF9014TF
	1500	1120	429	DSF9015SF	1576	604	DSF9015HF	2021	774	DSF9015DF			
	1600	1206	462	DSF9016SF	1697	650	DSF9016HF	2177	834	DSF9016DF	3095	1186	DSF9016TF
	1700	1292	495	DSF9017SF	1818	696	DSF9017HF	2333	893	DSF9017DF			
	1800	1379	528	DSF9018SF	1939	743	DSF9018HF	2488	953	DSF9018DF	3537	1355	DSF9018TF
	2000	1550	594	DSF9020SF	2182	836	DSF9020HF	2799	1072	DSF9020DF	3979	1524	DSF9020TF
	2200	1723	660	DSF9022SF	2424	929	DSF9022HF	3110	1191	DSF9022DF	4422	1693	DSF9022TF
	2400	1896	726	DSF9024SF	2666	1021	DSF9024HF	3420	1310	DSF9024DF			
	2600	2067	792	DSF9026SF	2909	1114	DSF9026HF	3732	1429	DSF9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1000	600	390	149	DSF1006SF	548	210	DSF1006HF	699	268	DSF1006DF	992	380	DSF1006TF
	700	488	187	DSF1007SF	685	262	DSF1007HF	874	335	DSF1007DF	1241	475	DSF1007TF
	800	586	224	DSF1008SF	821	315	DSF1008HF	1048	402	DSF1008DF	1489	570	DSF1008TF
	900	683	261	DSF1009SF	959	367	DSF1009HF	1223	468	DSF1009DF	1737	665	DSF1009TF
	1000	781	299	DSF1010SF	1096	420	DSF1010HF	1397	535	DSF1010DF	1985	760	DSF1010TF
	1100	878	336	DSF1011SF	1233	472	DSF1011HF	1573	602	DSF1011DF	2233	855	DSF1011TF
	1200	975	374	DSF1012SF	1370	525	DSF1012HF	1747	669	DSF1012DF	2481	950	DSF1012TF
	1300	1073	411	DSF1013SF	1507	577	DSF1013HF	1922	736	DSF1013DF	2730	1045	DSF1013TF
	1400	1170	448	DSF1014SF	1644	630	DSF1014HF	2097	803	DSF1014DF	2978	1141	DSF1014TF
	1500	1268	486	DSF1015SF	1781	682	DSF1015HF	2271	870	DSF1015DF			
	1600	1365	523	DSF1016SF	1918	735	DSF1016HF	2446	937	DSF1016DF	3474	1330	DSF1016TF
	1700	1463	560	DSF1017SF				2621	1004	DSF1017DF			
	1800	1561	598	DSF1018SF	2191	839	DSF1018HF	2795	1071	DSF1018DF	3970	1521	DSF1018TF
	2000	1756	673	DSF1020SF	2465	944	DSF1020HF	3144	1204	DSF1020DF			
	2200	1951	747	DSF1022SF				3494	1338	DSF1022DF			
	2400	2146	822	DSF1024SF				3844	1472	DSF1024DF			
	2600	2341	896	DSF1026SF				4193	1606	DSF1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T24)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT24)	Product Code
1200	600	469	180	DSF1206SF	665	255	DSF1206HF	834	319	DSF1206DF	1180	452	DSF1206TF
	700	587	225	DSF1207SF	831	318	DSF1207HF	1043	399	DSF1207DF	1476	565	DSF1207TF
	800	704	270	DSF1208SF	998	382	DSF1208HF	1251	479	DSF1208DF	1771	678	DSF1208TF
	900	821	315	DSF1209SF	1164	446	DSF1209HF	1460	559	DSF1209DF	2066	791	DSF1209TF
	1000	938	359	DSF1210SF	1330	509	DSF1210HF	1668	639	DSF1210DF	2361	904	DSF1210TF
	1100	1056	404	DSF1211SF				1877	719	DSF1211DF	2656	1017	DSF1211TF
	1200	1173	449	DSF1212SF				2085	799	DSF1212DF	2951	1130	DSF1212TF
	1300	1290	494	DSF1213SF									
	1400	1408	539	DSF1214SF				2503	959	DSF1214DF			
	1600	1642	629	DSF1216SF				2919	1118	DSF1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*