



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T30)



150mm



165mm



200mm




260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
600	600	183	94	DSW6006SF	272	140	DSW6006HF	350	179	DSW6006DF			
	700	230	118	DSW6007SF	341	175	DSW6007HF	438	225	DSW6007DF	622	319	DSW6007TF
	800	275	141	DSW6008SF	409	210	DSW6008HF	525	269	DSW6008DF	747	383	DSW6008TF
	900	321	165	DSW6009SF	477	245	DSW6009HF	612	314	DSW6009DF	871	447	DSW6009TF
	1000	367	188	DSW6010SF	546	280	DSW6010HF	700	359	DSW6010DF			
	1100	413	212	DSW6011SF	613	315	DSW6011HF	788	404	DSW6011DF	1120	574	DSW6011TF
	1200	458	235	DSW6012SF	682	350	DSW6012HF	875	449	DSW6012DF	1244	638	DSW6012TF
	1300	505	259	DSW6013SF	750	385	DSW6013HF	962	494	DSW6013DF	1369	702	DSW6013TF
	1400	550	282	DSW6014SF	818	420	DSW6014HF	1050	539	DSW6014DF	1493	766	DSW6014TF
	1500	596	306	DSW6015SF									
	1600	642	329	DSW6016SF	954	489	DSW6016HF	1225	628	DSW6016DF	1742	894	DSW6016TF
	1800	733	376	DSW6018SF	1091	560	DSW6018HF	1400	718	DSW6018DF	1991	1021	DSW6018TF
	2000	825	423	DSW6020SF	1227	630	DSW6020HF	1574	808	DSW6020DF	2239	1149	DSW6020TF
	2200	917	470	DSW6022SF				1750	898	DSW6022DF	2488	1277	DSW6022TF
	2400	1008	517	DSW6024SF				1925	988	DSW6024DF			
	2600	1100	564	DSW6026SF				2100	1077	DSW6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
700	600	241	124	DSW7006SF	348	179	DSW7006HF	449	230	DSW7006DF			
	700	302	155	DSW7007SF	435	223	DSW7007HF	561	288	DSW7007DF	797	409	DSW7007TF
	800	361	185	DSW7008SF	522	268	DSW7008HF	672	345	DSW7008DF	957	491	DSW7008TF
	900	422	216	DSW7009SF	609	312	DSW7009HF	784	402	DSW7009DF	1116	573	DSW7009TF
	1000	482	247	DSW7010SF	696	357	DSW7010HF	896	460	DSW7010DF	1275	654	DSW7010TF
	1100	542	278	DSW7011SF	782	401	DSW7011HF	1008	517	DSW7011DF	1435	736	DSW7011TF
	1200	603	309	DSW7012SF	870	446	DSW7012HF	1121	575	DSW7012DF	1594	818	DSW7012TF
	1300	663	340	DSW7013SF	957	491	DSW7013HF	1233	632	DSW7013DF	1753	899	DSW7013TF
	1400	723	371	DSW7014SF	1043	535	DSW7014HF	1345	690	DSW7014DF	1913	981	DSW7014TF
	1500	783	402	DSW7015SF	1130	580	DSW7015HF	1457	747	DSW7015DF			
	1600	844	433	DSW7016SF	1218	625	DSW7016HF	1569	805	DSW7016DF			
	1700	904	464	DSW7017SF	1305	669	DSW7017HF	1681	862	DSW7017DF			
	1800	964	494	DSW7018SF	1391	714	DSW7018HF	1792	920	DSW7018DF	2551	1309	DSW7018TF
	2000	1085	557	DSW7020SF	1566	803	DSW7020HF	2017	1035	DSW7020DF	2869	1472	DSW7020TF
	2200	1205	618	DSW7022SF	1739	892	DSW7022HF	2241	1150	DSW7022DF	3188	1635	DSW7022TF
	2400	1325	680	DSW7024SF	1913	981	DSW7024HF	2465	1265	DSW7024DF	3507	1799	DSW7024TF
	2600	1446	742	DSW7026SF	2087	1071	DSW7026HF	2690	1380	DSW7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
800	600	295	151	DSW8006SF	418	215	DSW8006HF	538	276	DSW8006DF			
	700	368	189	DSW8007SF	523	268	DSW8007HF	674	346	DSW8007DF	959	492	DSW8007TF
	800	442	227	DSW8008SF	627	322	DSW8008HF	808	415	DSW8008DF	1150	590	DSW8008TF
	900	516	265	DSW8009SF	732	376	DSW8009HF	943	484	DSW8009DF	1341	688	DSW8009TF
	1000	589	302	DSW8010SF	837	429	DSW8010HF	1077	552	DSW8010DF	1533	786	DSW8010TF
	1100	663	340	DSW8011SF	942	483	DSW8011HF	1212	622	DSW8011DF	1725	885	DSW8011TF
	1200	737	378	DSW8012SF	1046	536	DSW8012HF	1347	691	DSW8012DF	1916	983	DSW8012TF
	1300	811	416	DSW8013SF	1151	590	DSW8013HF	1481	760	DSW8013DF	2108	1081	DSW8013TF
	1400	885	454	DSW8014SF	1255	644	DSW8014HF	1616	829	DSW8014DF	2300	1180	DSW8014TF
	1500	958	491	DSW8015SF	1360	698	DSW8015HF	1751	898	DSW8015DF	2491	1278	DSW8015TF
	1600	1032	529	DSW8016SF	1464	751	DSW8016HF	1885	967	DSW8016DF	2682	1376	DSW8016TF
	1700	1105	567	DSW8017SF	1569	805	DSW8017HF	2020	1036	DSW8017DF			
	1800	1179	605	DSW8018SF	1673	858	DSW8018HF	2155	1105	DSW8018DF			
	2000	1326	680	DSW8020SF	1882	966	DSW8020HF	2423	1243	DSW8020DF	3449	1769	DSW8020TF
	2200	1474	756	DSW8022SF	2092	1073	DSW8022HF	2693	1382	DSW8022DF	3832	1966	DSW8022TF
	2400	1622	832	DSW8024SF	2301	1180	DSW8024HF	2963	1520	DSW8024DF	4216	2163	DSW8024TF
	2600	1768	907	DSW8026SF	2510	1288	DSW8026HF	3232	1658	DSW8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
900	500				364	187	DSW9005HF	466	239	DSW9005DF			
	600	344	177	DSW9006SF	485	249	DSW9006HF	622	319	DSW9006DF	885	454	DSW9006TF
	700	431	221	DSW9007SF	606	311	DSW9007HF	778	399	DSW9007DF	1105	567	DSW9007TF
	800	517	265	DSW9008SF	727	373	DSW9008HF	933	478	DSW9008DF	1326	680	DSW9008TF
	900	603	310	DSW9009SF	848	435	DSW9009HF	1088	558	DSW9009DF	1548	794	DSW9009TF
	1000	689	353	DSW9010SF	970	498	DSW9010HF	1244	638	DSW9010DF	1768	907	DSW9010TF
	1100	775	398	DSW9011SF	1091	560	DSW9011HF	1399	718	DSW9011DF	1990	1021	DSW9011TF
	1200	862	442	DSW9012SF	1212	622	DSW9012HF	1555	798	DSW9012DF	2211	1134	DSW9012TF
	1300	948	486	DSW9013SF	1333	684	DSW9013HF	1711	878	DSW9013DF	2431	1247	DSW9013TF
	1400	1034	531	DSW9014SF	1454	746	DSW9014HF	1865	957	DSW9014DF	2653	1361	DSW9014TF
	1500	1120	574	DSW9015SF	1576	809	DSW9015HF	2021	1037	DSW9015DF			
	1600	1206	619	DSW9016SF	1697	871	DSW9016HF	2177	1117	DSW9016DF	3095	1588	DSW9016TF
	1700	1292	663	DSW9017SF	1818	933	DSW9017HF	2333	1197	DSW9017DF			
	1800	1379	707	DSW9018SF	1939	995	DSW9018HF	2488	1276	DSW9018DF	3537	1814	DSW9018TF
	2000	1550	795	DSW9020SF	2182	1120	DSW9020HF	2799	1436	DSW9020DF	3979	2041	DSW9020TF
	2200	1723	884	DSW9022SF	2424	1244	DSW9022HF	3110	1595	DSW9022DF	4422	2268	DSW9022TF
	2400	1896	972	DSW9024SF	2666	1368	DSW9024HF	3420	1755	DSW9024DF			
	2600	2067	1061	DSW9026SF	2909	1493	DSW9026HF	3732	1914	DSW9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1000	600	390	200	DSW1006SF	548	281	DSW1006HF	699	358	DSW1006DF	992	509	DSW1006TF
	700	488	250	DSW1007SF	685	352	DSW1007HF	874	448	DSW1007DF	1241	636	DSW1007TF
	800	586	300	DSW1008SF	821	421	DSW1008HF	1048	538	DSW1008DF	1489	764	DSW1008TF
	900	683	350	DSW1009SF	959	492	DSW1009HF	1223	627	DSW1009DF	1737	891	DSW1009TF
	1000	781	400	DSW1010SF	1096	562	DSW1010HF	1397	717	DSW1010DF	1985	1018	DSW1010TF
	1100	878	450	DSW1011SF	1233	632	DSW1011HF	1573	807	DSW1011DF	2233	1146	DSW1011TF
	1200	975	500	DSW1012SF	1370	703	DSW1012HF	1747	896	DSW1012DF	2481	1273	DSW1012TF
	1300	1073	551	DSW1013SF	1507	773	DSW1013HF	1922	986	DSW1013DF	2730	1400	DSW1013TF
	1400	1170	600	DSW1014SF	1644	843	DSW1014HF	2097	1076	DSW1014DF	2978	1528	DSW1014TF
	1500	1268	651	DSW1015SF	1781	914	DSW1015HF	2271	1165	DSW1015DF			
	1600	1365	700	DSW1016SF	1918	984	DSW1016HF	2446	1255	DSW1016DF	3474	1782	DSW1016TF
	1700	1463	751	DSW1017SF				2621	1345	DSW1017DF			
	1800	1561	801	DSW1018SF	2191	1124	DSW1018HF	2795	1434	DSW1018DF	3970	2037	DSW1018TF
	2000	1756	901	DSW1020SF	2465	1265	DSW1020HF	3144	1613	DSW1020DF			
	2200	1951	1001	DSW1022SF				3494	1792	DSW1022DF			
	2400	2146	1101	DSW1024SF				3844	1972	DSW1024DF			
	2600	2341	1201	DSW1026SF				4193	2151	DSW1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Wall Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1200	600	469	241	DSW1206SF	665	341	DSW1206HF	834	428	DSW1206DF	1180	605	DSW1206TF
	700	587	301	DSW1207SF	831	426	DSW1207HF	1043	535	DSW1207DF	1476	757	DSW1207TF
	800	704	361	DSW1208SF	998	512	DSW1208HF	1251	642	DSW1208DF	1771	909	DSW1208TF
	900	821	421	DSW1209SF	1164	597	DSW1209HF	1460	749	DSW1209DF	2066	1060	DSW1209TF
	1000	938	481	DSW1210SF	1330	682	DSW1210HF	1668	856	DSW1210DF	2361	1211	DSW1210TF
	1100	1056	541	DSW1211SF				1877	963	DSW1211DF	2656	1362	DSW1211TF
	1200	1173	602	DSW1212SF				2085	1070	DSW1212DF	2951	1514	DSW1212TF
	1300	1290	662	DSW1213SF									
	1400	1408	722	DSW1214SF				2503	1284	DSW1214DF			
	1600	1642	842	DSW1216SF				2919	1498	DSW1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*