


Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T30)



150mm



165mm



200mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
600	600	183	94	DSF6006SF	272	140	DSF6006HF	350	179	DSF6006DF			
	700	230	118	DSF6007SF	341	175	DSF6007HF	438	225	DSF6007DF	622	319	DSF6007TF
	800	275	141	DSF6008SF	409	210	DSF6008HF	525	269	DSF6008DF	747	383	DSF6008TF
	900	321	165	DSF6009SF	477	245	DSF6009HF	612	314	DSF6009DF	871	447	DSF6009TF
	1000	367	188	DSF6010SF	546	280	DSF6010HF	700	359	DSF6010DF			
	1100	413	212	DSF6011SF	613	315	DSF6011HF	788	404	DSF6011DF	1120	574	DSF6011TF
	1200	458	235	DSF6012SF	682	350	DSF6012HF	875	449	DSF6012DF	1244	638	DSF6012TF
	1300	505	259	DSF6013SF	750	385	DSF6013HF	962	494	DSF6013DF	1369	702	DSF6013TF
	1400	550	282	DSF6014SF	818	420	DSF6014HF	1050	539	DSF6014DF	1493	766	DSF6014TF
	1500	596	306	DSF6015SF									
	1600	642	329	DSF6016SF	954	489	DSF6016HF	1225	628	DSF6016DF	1742	894	DSF6016TF
	1800	733	376	DSF6018SF	1091	560	DSF6018HF	1400	718	DSF6018DF	1991	1021	DSF6018TF
	2000	825	423	DSF6020SF	1227	630	DSF6020HF	1574	808	DSF6020DF	2239	1149	DSF6020TF
	2200	917	470	DSF6022SF				1750	898	DSF6022DF	2488	1277	DSF6022TF
	2400	1008	517	DSF6024SF				1925	988	DSF6024DF			
	2600	1100	564	DSF6026SF				2100	1077	DSF6026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T30)



150mm



165mm



200mm




260mm

Casing Depth



Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
700	600	241	124	DSF7006SF	348	179	DSF7006HF	449	230	DSF7006DF			
	700	302	155	DSF7007SF	435	223	DSF7007HF	561	288	DSF7007DF	797	409	DSF7007TF
	800	361	185	DSF7008SF	522	268	DSF7008HF	672	345	DSF7008DF	957	491	DSF7008TF
	900	422	216	DSF7009SF	609	312	DSF7009HF	784	402	DSF7009DF	1116	573	DSF7009TF
	1000	482	247	DSF7010SF	696	357	DSF7010HF	896	460	DSF7010DF	1275	654	DSF7010TF
	1100	542	278	DSF7011SF	782	401	DSF7011HF	1008	517	DSF7011DF	1435	736	DSF7011TF
	1200	603	309	DSF7012SF	870	446	DSF7012HF	1121	575	DSF7012DF	1594	818	DSF7012TF
	1300	663	340	DSF7013SF	957	491	DSF7013HF	1233	632	DSF7013DF	1753	899	DSF7013TF
	1400	723	371	DSF7014SF	1043	535	DSF7014HF	1345	690	DSF7014DF	1913	981	DSF7014TF
	1500	783	402	DSF7015SF	1130	580	DSF7015HF	1457	747	DSF7015DF			
	1600	844	433	DSF7016SF	1218	625	DSF7016HF	1569	805	DSF7016DF			
	1700	904	464	DSF7017SF	1305	669	DSF7017HF	1681	862	DSF7017DF			
	1800	964	494	DSF7018SF	1391	714	DSF7018HF	1792	920	DSF7018DF	2551	1309	DSF7018TF
	2000	1085	557	DSF7020SF	1566	803	DSF7020HF	2017	1035	DSF7020DF	2869	1472	DSF7020TF
	2200	1205	618	DSF7022SF	1739	892	DSF7022HF	2241	1150	DSF7022DF	3188	1635	DSF7022TF
	2400	1325	680	DSF7024SF	1913	981	DSF7024HF	2465	1265	DSF7024DF	3507	1799	DSF7024TF
	2600	1446	742	DSF7026SF	2087	1071	DSF7026HF	2690	1380	DSF7026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
800	600	295	151	DSF8006SF	418	215	DSF8006HF	538	276	DSF8006DF			
	700	368	189	DSF8007SF	523	268	DSF8007HF	674	346	DSF8007DF	959	492	DSF8007TF
	800	442	227	DSF8008SF	627	322	DSF8008HF	808	415	DSF8008DF	1150	590	DSF8008TF
	900	516	265	DSF8009SF	732	376	DSF8009HF	943	484	DSF8009DF	1341	688	DSF8009TF
	1000	589	302	DSF8010SF	837	429	DSF8010HF	1077	552	DSF8010DF	1533	786	DSF8010TF
	1100	663	340	DSF8011SF	942	483	DSF8011HF	1212	622	DSF8011DF	1725	885	DSF8011TF
	1200	737	378	DSF8012SF	1046	536	DSF8012HF	1347	691	DSF8012DF	1916	983	DSF8012TF
	1300	811	416	DSF8013SF	1151	590	DSF8013HF	1481	760	DSF8013DF	2108	1081	DSF8013TF
	1400	885	454	DSF8014SF	1255	644	DSF8014HF	1616	829	DSF8014DF	2300	1180	DSF8014TF
	1500	958	491	DSF8015SF	1360	698	DSF8015HF	1751	898	DSF8015DF	2491	1278	DSF8015TF
	1600	1032	529	DSF8016SF	1464	751	DSF8016HF	1885	967	DSF8016DF	2682	1376	DSF8016TF
	1700	1105	567	DSF8017SF	1569	805	DSF8017HF	2020	1036	DSF8017DF			
	1800	1179	605	DSF8018SF	1673	858	DSF8018HF	2155	1105	DSF8018DF			
	2000	1326	680	DSF8020SF	1882	966	DSF8020HF	2423	1243	DSF8020DF	3449	1769	DSF8020TF
	2200	1474	756	DSF8022SF	2092	1073	DSF8022HF	2693	1382	DSF8022DF	3832	1966	DSF8022TF
	2400	1622	832	DSF8024SF	2301	1180	DSF8024HF	2963	1520	DSF8024DF	4216	2163	DSF8024TF
	2600	1768	907	DSF8026SF	2510	1288	DSF8026HF	3232	1658	DSF8026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
900	500				364	187	DSF9005HF	466	239	DSF9005DF			
	600	344	177	DSF9006SF	485	249	DSF9006HF	622	319	DSF9006DF	885	454	DSF9006TF
	700	431	221	DSF9007SF	606	311	DSF9007HF	778	399	DSF9007DF	1105	567	DSF9007TF
	800	517	265	DSF9008SF	727	373	DSF9008HF	933	478	DSF9008DF	1326	680	DSF9008TF
	900	603	310	DSF9009SF	848	435	DSF9009HF	1088	558	DSF9009DF	1548	794	DSF9009TF
	1000	689	353	DSF9010SF	970	498	DSF9010HF	1244	638	DSF9010DF	1768	907	DSF9010TF
	1100	775	398	DSF9011SF	1091	560	DSF9011HF	1399	718	DSF9011DF	1990	1021	DSF9011TF
	1200	862	442	DSF9012SF	1212	622	DSF9012HF	1555	798	DSF9012DF	2211	1134	DSF9012TF
	1300	948	486	DSF9013SF	1333	684	DSF9013HF	1711	878	DSF9013DF	2431	1247	DSF9013TF
	1400	1034	531	DSF9014SF	1454	746	DSF9014HF	1865	957	DSF9014DF	2653	1361	DSF9014TF
	1500	1120	574	DSF9015SF	1576	809	DSF9015HF	2021	1037	DSF9015DF			
	1600	1206	619	DSF9016SF	1697	871	DSF9016HF	2177	1117	DSF9016DF	3095	1588	DSF9016TF
	1700	1292	663	DSF9017SF	1818	933	DSF9017HF	2333	1197	DSF9017DF			
	1800	1379	707	DSF9018SF	1939	995	DSF9018HF	2488	1276	DSF9018DF	3537	1814	DSF9018TF
	2000	1550	795	DSF9020SF	2182	1120	DSF9020HF	2799	1436	DSF9020DF	3979	2041	DSF9020TF
	2200	1723	884	DSF9022SF	2424	1244	DSF9022HF	3110	1595	DSF9022DF	4422	2268	DSF9022TF
	2400	1896	972	DSF9024SF	2666	1368	DSF9024HF	3420	1755	DSF9024DF			
	2600	2067	1061	DSF9026SF	2909	1493	DSF9026HF	3732	1914	DSF9026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm


165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1000	600	390	200	DSF1006SF	548	281	DSF1006HF	699	358	DSF1006DF	992	509	DSF1006TF
	700	488	250	DSF1007SF	685	352	DSF1007HF	874	448	DSF1007DF	1241	636	DSF1007TF
	800	586	300	DSF1008SF	821	421	DSF1008HF	1048	538	DSF1008DF	1489	764	DSF1008TF
	900	683	350	DSF1009SF	959	492	DSF1009HF	1223	627	DSF1009DF	1737	891	DSF1009TF
	1000	781	400	DSF1010SF	1096	562	DSF1010HF	1397	717	DSF1010DF	1985	1018	DSF1010TF
	1100	878	450	DSF1011SF	1233	632	DSF1011HF	1573	807	DSF1011DF	2233	1146	DSF1011TF
	1200	975	500	DSF1012SF	1370	703	DSF1012HF	1747	896	DSF1012DF	2481	1273	DSF1012TF
	1300	1073	551	DSF1013SF	1507	773	DSF1013HF	1922	986	DSF1013DF	2730	1400	DSF1013TF
	1400	1170	600	DSF1014SF	1644	843	DSF1014HF	2097	1076	DSF1014DF	2978	1528	DSF1014TF
	1500	1268	651	DSF1015SF	1781	914	DSF1015HF	2271	1165	DSF1015DF			
	1600	1365	700	DSF1016SF	1918	984	DSF1016HF	2446	1255	DSF1016DF	3474	1782	DSF1016TF
	1700	1463	751	DSF1017SF				2621	1345	DSF1017DF			
	1800	1561	801	DSF1018SF	2191	1124	DSF1018HF	2795	1434	DSF1018DF	3970	2037	DSF1018TF
	2000	1756	901	DSF1020SF	2465	1265	DSF1020HF	3144	1613	DSF1020DF			
	2200	1951	1001	DSF1022SF				3494	1792	DSF1022DF			
	2400	2146	1101	DSF1024SF				3844	1972	DSF1024DF			
	2600	2341	1201	DSF1026SF				4193	2151	DSF1026DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Deepclean - Sloped Top - Floor Mounted - Standard Grilles

(T50 / T30)



Casing Depth

150mm

165mm

200mm

260mm

Casing Height (mm)	Casing Length (mm)	SF/Type 11			HF/Type 12			DF/Type 22			TF/Type 33		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1200	600	469	241	DSF1206SF	665	341	DSF1206HF	834	428	DSF1206DF	1180	605	DSF1206TF
	700	587	301	DSF1207SF	831	426	DSF1207HF	1043	535	DSF1207DF	1476	757	DSF1207TF
	800	704	361	DSF1208SF	998	512	DSF1208HF	1251	642	DSF1208DF	1771	909	DSF1208TF
	900	821	421	DSF1209SF	1164	597	DSF1209HF	1460	749	DSF1209DF	2066	1060	DSF1209TF
	1000	938	481	DSF1210SF	1330	682	DSF1210HF	1668	856	DSF1210DF	2361	1211	DSF1210TF
	1100	1056	541	DSF1211SF				1877	963	DSF1211DF	2656	1362	DSF1211TF
	1200	1173	602	DSF1212SF				2085	1070	DSF1212DF	2951	1514	DSF1212TF
	1300	1290	662	DSF1213SF									
	1400	1408	722	DSF1214SF				2503	1284	DSF1214DF			
	1600	1642	842	DSF1216SF				2919	1498	DSF1216DF			

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*