



Triple Fin - Flat Top - Floor Mounted

(T50 / T20)



260mm




260mm

Casing Depth



Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
550	700	622	188	DFF5507TF	559	169	DEFF5507TF
	800	747	226	DFF5508TF	671	203	DEFF5508TF
	900	871	263	DFF5509TF	783	237	DEFF5509TF
	1100	1120	338	DFF5511TF	1006	304	DEFF5511TF
	1200	1244	376	DFF5512TF	1118	338	DEFF5512TF
	1300	1369	413	DFF5513TF	1230	372	DEFF5513TF
	1400	1493	451	DFF5514TF	1342	405	DEFF5514TF
	1600	1742	526	DFF5516TF	1566	473	DEFF5516TF
	1800	1991	601	DFF5518TF	1790	540	DEFF5518TF
	2000	2239	676	DFF5520TF	2013	608	DEFF5520TF
	2200	2488	752	DFF5522TF	2237	676	DEFF5522TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Triple Fin - Flat Top - Floor Mounted

(T50 / T20)




Casing Depth

260mm

260mm


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
650	700	797	241	DFF6507TF	717	216	DEFF6507TF
	800	957	289	DFF6508TF	860	260	DEFF6508TF
	900	1116	337	DFF6509TF	1003	303	DEFF6509TF
	1000	1275	385	DFF6510TF	1146	346	DEFF6510TF
	1100	1435	433	DFF6511TF	1290	389	DEFF6511TF
	1200	1594	481	DFF6512TF	1433	433	DEFF6512TF
	1300	1753	529	DFF6513TF	1576	476	DEFF6513TF
	1400	1913	578	DFF6514TF	1719	519	DEFF6514TF
	1800	2551	770	DFF6518TF	2293	692	DEFF6518TF
	2000	2869	867	DFF6520TF	2579	779	DEFF6520TF
	2200	3188	963	DFF6522TF	2866	865	DEFF6522TF
	2400	3507	1059	DFF6524TF	3152	952	DEFF6524TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
750	700	959	289	DFF7507TF	862	260	DEFF7507TF
	800	1150	347	DFF7508TF	1034	312	DEFF7508TF
	900	1341	405	DFF7509TF	1206	364	DEFF7509TF
	1000	1533	463	DFF7510TF	1378	416	DEFF7510TF
	1100	1725	521	DFF7511TF	1550	468	DEFF7511TF
	1200	1916	579	DFF7512TF	1722	520	DEFF7512TF
	1300	2108	636	DFF7513TF	1894	572	DEFF7513TF
	1400	2300	695	DFF7514TF	2067	624	DEFF7514TF
	1500	2491	752	DFF7515TF	2239	676	DEFF7515TF
	1600	2682	810	DFF7516TF	2411	728	DEFF7516TF
	2000	3449	1042	DFF7520TF	3100	936	DEFF7520TF
	2200	3832	1157	DFF7522TF	3445	1040	DEFF7522TF
	2400	4216	1273	DFF7524TF	3790	1144	DEFF7524TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts ($\Delta T50$)	Output Watts ($\Delta T20$)	Product Code	Output Watts ($\Delta T50$)	Output Watts ($\Delta T20$)	Product Code
850	600	885	267	DFF8506TF	795	240	DEFF8506TF
	700	1105	334	DFF8507TF	994	300	DEFF8507TF
	800	1326	400	DFF8508TF	1192	360	DEFF8508TF
	900	1548	467	DFF8509TF	1391	420	DEFF8509TF
	1000	1768	534	DFF8510TF	1590	480	DEFF8510TF
	1100	1990	601	DFF8511TF	1789	540	DEFF8511TF
	1200	2211	668	DFF8512TF	1987	600	DEFF8512TF
	1300	2431	734	DFF8513TF	2186	660	DEFF8513TF
	1400	2653	801	DFF8514TF	2385	720	DEFF8514TF
	1600	3095	935	DFF8516TF	2782	840	DEFF8516TF
	1800	3537	1068	DFF8518TF	3179	960	DEFF8518TF
	2000	3979	1202	DFF8520TF	3577	1080	DEFF8520TF
	2200	4422	1335	DFF8522TF	3974	1200	DEFF8522TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
950	600	992	300	DFF9506TF	892	269	DEFF9506TF
	700	1241	375	DFF9507TF	1115	337	DEFF9507TF
	800	1489	450	DFF9508TF	1338	404	DEFF9508TF
	900	1737	525	DFF9509TF	1562	472	DEFF9509TF
	1000	1985	599	DFF9510TF	1784	539	DEFF9510TF
	1100	2233	674	DFF9511TF	2007	606	DEFF9511TF
	1200	2481	749	DFF9512TF	2230	674	DEFF9512TF
	1300	2730	824	DFF9513TF	2454	741	DEFF9513TF
	1400	2978	899	DFF9514TF	2677	808	DEFF9514TF
	1600	3474	1049	DFF9516TF	3122	943	DEFF9516TF
	1800	3970	1199	DFF9518TF	3569	1078	DEFF9518TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T20)



260mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (Δ T50)	Output Watts (Δ T20)	Product Code	Output Watts (Δ T50)	Output Watts (Δ T20)	Product Code
1150	600	1180	356	DFF1106TF	1061	320	DEFF1106TF
	700	1476	446	DFF1107TF	1326	401	DEFF1107TF
	800	1771	535	DFF1108TF	1592	481	DEFF1108TF
	900	2066	624	DFF1109TF	1857	561	DEFF1109TF
	1000	2361	713	DFF1110TF	2122	641	DEFF1110TF
	1100	2656	802	DFF1111TF	2387	721	DEFF1111TF
	1200	2951	891	DFF1112TF	2653	801	DEFF1112TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*