



Triple Fin - Flat Top - Floor Mounted

(T50 / T30)



260mm




260mm

Casing Depth



Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
550	700	622	319	DFF5507TF	559	287	DEFF5507TF
	800	747	383	DFF5508TF	671	344	DEFF5508TF
	900	871	447	DFF5509TF	783	402	DEFF5509TF
	1100	1120	574	DFF5511TF	1006	516	DEFF5511TF
	1200	1244	638	DFF5512TF	1118	574	DEFF5512TF
	1300	1369	702	DFF5513TF	1230	631	DEFF5513TF
	1400	1493	766	DFF5514TF	1342	689	DEFF5514TF
	1600	1742	894	DFF5516TF	1566	803	DEFF5516TF
	1800	1991	1021	DFF5518TF	1790	918	DEFF5518TF
	2000	2239	1149	DFF5520TF	2013	1033	DEFF5520TF
	2200	2488	1277	DFF5522TF	2237	1147	DEFF5522TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*



Triple Fin - Flat Top - Floor Mounted

(T50 / T30)




Casing Depth

260mm

260mm


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
650	700	797	409	DFF6507TF	717	368	DEFF6507TF
	800	957	491	DFF6508TF	860	441	DEFF6508TF
	900	1116	573	DFF6509TF	1003	515	DEFF6509TF
	1000	1275	654	DFF6510TF	1146	588	DEFF6510TF
	1100	1435	736	DFF6511TF	1290	662	DEFF6511TF
	1200	1594	818	DFF6512TF	1433	735	DEFF6512TF
	1300	1753	899	DFF6513TF	1576	808	DEFF6513TF
	1400	1913	981	DFF6514TF	1719	882	DEFF6514TF
	1800	2551	1309	DFF6518TF	2293	1176	DEFF6518TF
	2000	2869	1472	DFF6520TF	2579	1323	DEFF6520TF
	2200	3188	1635	DFF6522TF	2866	1470	DEFF6522TF
	2400	3507	1799	DFF6524TF	3152	1617	DEFF6524TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T30)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
750	700	959	492	DFF7507TF	862	442	DEFF7507TF
	800	1150	590	DFF7508TF	1034	530	DEFF7508TF
	900	1341	688	DFF7509TF	1206	618	DEFF7509TF
	1000	1533	786	DFF7510TF	1378	707	DEFF7510TF
	1100	1725	885	DFF7511TF	1550	795	DEFF7511TF
	1200	1916	983	DFF7512TF	1722	884	DEFF7512TF
	1300	2108	1081	DFF7513TF	1894	972	DEFF7513TF
	1400	2300	1180	DFF7514TF	2067	1060	DEFF7514TF
	1500	2491	1278	DFF7515TF	2239	1149	DEFF7515TF
	1600	2682	1376	DFF7516TF	2411	1237	DEFF7516TF
	2000	3449	1769	DFF7520TF	3100	1590	DEFF7520TF
	2200	3832	1966	DFF7522TF	3445	1767	DEFF7522TF
	2400	4216	2163	DFF7524TF	3790	1944	DEFF7524TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T30)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (Δ T50)	Output Watts (Δ T30)	Product Code	Output Watts (Δ T50)	Output Watts (Δ T30)	Product Code
850	600	885	454	DFF8506TF	795	408	DEFF8506TF
	700	1105	567	DFF8507TF	994	510	DEFF8507TF
	800	1326	680	DFF8508TF	1192	611	DEFF8508TF
	900	1548	794	DFF8509TF	1391	714	DEFF8509TF
	1000	1768	907	DFF8510TF	1590	815	DEFF8510TF
	1100	1990	1021	DFF8511TF	1789	918	DEFF8511TF
	1200	2211	1134	DFF8512TF	1987	1019	DEFF8512TF
	1300	2431	1247	DFF8513TF	2186	1121	DEFF8513TF
	1400	2653	1361	DFF8514TF	2385	1223	DEFF8514TF
	1600	3095	1588	DFF8516TF	2782	1427	DEFF8516TF
	1800	3537	1814	DFF8518TF	3179	1631	DEFF8518TF
	2000	3979	2041	DFF8520TF	3577	1835	DEFF8520TF
	2200	4422	2268	DFF8522TF	3974	2039	DEFF8522TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T30)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts ($\Delta T50$)	Output Watts ($\Delta T30$)	Product Code	Output Watts ($\Delta T50$)	Output Watts ($\Delta T30$)	Product Code
950	600	992	509	DFF9506TF	892	458	DEFF9506TF
	700	1241	636	DFF9507TF	1115	572	DEFF9507TF
	800	1489	764	DFF9508TF	1338	687	DEFF9508TF
	900	1737	891	DFF9509TF	1562	801	DEFF9509TF
	1000	1985	1018	DFF9510TF	1784	915	DEFF9510TF
	1100	2233	1146	DFF9511TF	2007	1030	DEFF9511TF
	1200	2481	1273	DFF9512TF	2230	1144	DEFF9512TF
	1300	2730	1400	DFF9513TF	2454	1259	DEFF9513TF
	1400	2978	1528	DFF9514TF	2677	1373	DEFF9514TF
	1600	3474	1782	DFF9516TF	3122	1602	DEFF9516TF
	1800	3970	2037	DFF9518TF	3569	1831	DEFF9518TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Flat Top - Floor Mounted

(T50 / T30)



260mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT30)	Product Code
1150	600	1180	605	DFF1106TF	1061	544	DEFF1106TF
	700	1476	757	DFF1107TF	1326	680	DEFF1107TF
	800	1771	909	DFF1108TF	1592	817	DEFF1108TF
	900	2066	1060	DFF1109TF	1857	953	DEFF1109TF
	1000	2361	1211	DFF1110TF	2122	1089	DEFF1110TF
	1100	2656	1362	DFF1111TF	2387	1225	DEFF1111TF
	1200	2951	1514	DFF1112TF	2653	1361	DEFF1112TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*