



Triple Fin - Sloped Top - Wall Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
600	700	622	188	DSW6007TF	559	169	DESW6007TF
	800	747	226	DSW6008TF	671	203	DESW6008TF
	900	871	263	DSW6009TF	783	237	DESW6009TF
	1100	1120	338	DSW6011TF	1006	304	DESW6011TF
	1200	1244	376	DSW6012TF	1118	338	DESW6012TF
	1300	1369	413	DSW6013TF	1230	372	DESW6013TF
	1400	1493	451	DSW6014TF	1342	405	DESW6014TF
	1600	1742	526	DSW6016TF	1566	473	DESW6016TF
	1800	1991	601	DSW6018TF	1790	540	DESW6018TF
	2000	2239	676	DSW6020TF	2013	608	DESW6020TF
	2200	2488	752	DSW6022TF	2237	676	DESW6022TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Sloped Top - Wall Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
700	700	797	241	DSW7007TF	717	216	DESW7007TF
	800	957	289	DSW7008TF	860	260	DESW7008TF
	900	1116	337	DSW7009TF	1003	303	DESW7009TF
	1000	1275	385	DSW7010TF	1146	346	DESW7010TF
	1100	1435	433	DSW7011TF	1290	389	DESW7011TF
	1200	1594	481	DSW7012TF	1433	433	DESW7012TF
	1300	1753	529	DSW7013TF	1576	476	DESW7013TF
	1400	1913	578	DSW7014TF	1719	519	DESW7014TF
	1800	2551	770	DSW7018TF	2293	692	DESW7018TF
	2000	2869	867	DSW7020TF	2579	779	DESW7020TF
	2200	3188	963	DSW7022TF	2866	865	DESW7022TF
	2400	3507	1059	DSW7024TF	3152	952	DESW7024TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Sloped Top - Wall Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
800	700	959	289	DSW8007TF	862	260	DESW8007TF
	800	1150	347	DSW8008TF	1034	312	DESW8008TF
	900	1341	405	DSW8009TF	1206	364	DESW8009TF
	1000	1533	463	DSW8010TF	1378	416	DESW8010TF
	1100	1725	521	DSW8011TF	1550	468	DESW8011TF
	1200	1916	579	DSW8012TF	1722	520	DESW8012TF
	1300	2108	636	DSW8013TF	1894	572	DESW8013TF
	1400	2300	695	DSW8014TF	2067	624	DESW8014TF
	1500	2491	752	DSW8015TF	2239	676	DESW8015TF
	1600	2682	810	DSW8016TF	2411	728	DESW8016TF
	2000	3449	1042	DSW8020TF	3100	936	DESW8020TF
	2200	3832	1157	DSW8022TF	3445	1040	DESW8022TF
	2400	4216	1273	DSW8024TF	3790	1144	DESW8024TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Sloped Top - Wall Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
900	600	885	267	DSW9006TF	795	240	DESW9006TF
	700	1105	334	DSW9007TF	994	300	DESW9007TF
	800	1326	400	DSW9008TF	1192	360	DESW9008TF
	900	1548	467	DSW9009TF	1391	420	DESW9009TF
	1000	1768	534	DSW9010TF	1590	480	DESW9010TF
	1100	1990	601	DSW9011TF	1789	540	DESW9011TF
	1200	2211	668	DSW9012TF	1987	600	DESW9012TF
	1300	2431	734	DSW9013TF	2186	660	DESW9013TF
	1400	2653	801	DSW9014TF	2385	720	DESW9014TF
	1600	3095	935	DSW9016TF	2782	840	DESW9016TF
	1800	3537	1068	DSW9018TF	3179	960	DESW9018TF
	2000	3979	1202	DSW9020TF	3577	1080	DESW9020TF
	2200	4422	1335	DSW9022TF	3974	1200	DESW9022TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Sloped Top - Wall Mounted

(T50 / T20)



260mm




260mm

Casing Depth


Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1000	600	992	300	DSW1006TF	892	269	DESW1006TF
	700	1241	375	DSW1007TF	1115	337	DESW1007TF
	800	1489	450	DSW1008TF	1338	404	DESW1008TF
	900	1737	525	DSW1009TF	1562	472	DESW1009TF
	1000	1985	599	DSW1010TF	1784	539	DESW1010TF
	1100	2233	674	DSW1011TF	2007	606	DESW1011TF
	1200	2481	749	DSW1012TF	2230	674	DESW1012TF
	1300	2730	824	DSW1013TF	2454	741	DESW1013TF
	1400	2978	899	DSW1014TF	2677	808	DESW1014TF
	1600	3474	1049	DSW1016TF	3122	943	DESW1016TF
	1800	3970	1199	DSW1018TF	3569	1078	DESW1018TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*




Triple Fin - Sloped Top - Wall Mounted

(T50 / T20)



260mm



260mm

Casing Depth

Casing Height (mm)	Casing Length (mm)	DeepClean			Deepclean Extra		
		Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code	Output Watts (ΔT50)	Output Watts (ΔT20)	Product Code
1200	600	1180	356	DSW1206TF	1061	320	DESW1206TF
	700	1476	446	DSW1207TF	1326	401	DESW1207TF
	800	1771	535	DSW1208TF	1592	481	DESW1208TF
	900	2066	624	DSW1209TF	1857	561	DESW1209TF
	1000	2361	713	DSW1210TF	2122	641	DESW1210TF
	1100	2656	802	DSW1211TF	2387	721	DESW1211TF
	1200	2951	891	DSW1212TF	2653	801	DESW1212TF

*For installations into wet rooms or high-humidity environments, casings are available in Magnelis Steel for corrosion resistance. Add **MAG** to the end of the product code.*